

The FS-D indicator is ideal for today's food processing industry and busy production environments. The 0.5 second measurement time and bright three color lights mean quick weighing and error-free comparator judgments. The refresh rate of 20 times/second allows fast data acquisition using optional serial interfaces.



Manufacture: AND Weighing
SKU: FS-D
Weight: 6.00 lb
 Free Ground Shipping within the 48 continental US States

Please Call
(800)832-0055

Features

The FS-D indicator is ideal for today's food processing industry and busy production environments. The 0.5 second measurement time and bright three color lights mean quick weighing and error-free comparator judgments. The refresh rate of 20 times/second allows fast data acquisition using optional serial interfaces. The FS-D comes with a desktop/wall mount stand and connector plug for use with platforms from A&D Weighing and most manufacturers **Stainless Steel and IP65 Water & Dustproof Construction** NSF certified and easy to wash and keep hygienic, the FS-D is reliable under harsh conditions. **Auto-tare Function** Eliminate repeatedly pressing the TARE key in consecutive measurements – the FS-D can automatically perform a tare each time the weight reaches a target range. **Negative Comparison** You can now compare negative values by removing weights from the scale

Eight Fixed Capacities Models can be configured to one of the following eight capacities in 3 different resolutions that range from 1/3000 to 1/12,000 to 1/15,000.

Fixed Capacities	Resolution		
	Low	Med	High
6 kg		6,000	12,000
15 kg		7,500	15,000
30 kg		6,000	12,000
60 kg	3,000	6,000	12,000
150 kg		7,500	15,000
300 kg		6,000	12,000

Specifications

Model	FS-D
Input sensitivity	0.2 μ V / d (d: the smallest min. display of kg)
Input signal range	0 mV to 13 mV
Weighing resolutions	1/3,000, 1/6,000 (or 1/7,500), and 1/12,000 (or 1/15,000) (Only one can be selected at a time.)
Load cell excitation voltage	DC 5 V \pm 5% (no remote sensing)
Load cell drive capacity	Up to four 350 ω load cells
Temperature coefficient	Zero: \pm (0.2 μ V \pm 0.001% of zero adjustment voltage) / $^{\circ}$ C (typ.) Span: \pm 0.001% / $^{\circ}$ C of reading (typ.)
Available units of weighing	lb, kg, g, oz, and lb-oz
Linearity	\pm 0.01% of full scale
Memory Capacity	100 sets of comparator limits
Display	7-segment LCD (Character height: 18.6 mm) with backlight
Dimensions	250 (W) x 202 (D) x 266 (H) mm 9.8 (W) x 8.0 (D) x 10.5 (H) in.
Power supply	AC main (100 V to 240 V) or SLA rechargeable battery (option), approx. 80 hours (depends on usage)

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.