

Features the revolutionary Super Hybrid Sensor technology - increases response speed and minimizes maintenance costs. With max 0.001 readability. With data memory function, multiple weighing modes, RS232, IP554, interval weighing and more.



Manufacture: AND Weighing

SKU: GF-1200N

UPC:

B00G0PN9YS

Weight: 11.00 lb

Free Ground Shipping
within the 48
continental US States

Please Call
(800)832-0055

Features

The GF Series of lab scales incorporates our unique SHS technology and defies comparison with all others. Our revolutionary and patented Super Hybrid Sensor (SHS) technology improves response speed and minimizes maintenance costs. Its unique design provides the fastest response speed in its class--an amazing one-second. SHS combines the best of magnetic force restoration and single point parallelogram load sensing technologies.

- Some Models Legal for Trade (as noted below)
- Fast, new Super Hybrid Sensor (SHS) gives you the ultimate in response speed - Just ONE Second!
- Resolution Range among models: 1/60,000 to 1/600,000
- IP54 splashproof operator keyboard protects against dust and spills
- Stainless steel weighing pan.
- Standard RS232 bi-directional communication
- Large, bright Vacuum Fluorescent Display - see the display even in the dark
- Interval time setting for automatic weighings at intervals from 1 second to 10 minutes
- Weighs in grams, decimal ounces, pennyweight, milligrams, troy ounces, carats, grains, mommes, taels and tolas
- Percentage, Counting Functions & Comparator functions plus Density Determination, Animal Weighing and Percentage weighing functions
- ACAI Counting Function for highly accurate counting
- Bright, blue Vacuum Fluorescent Display
- GLP/GMP/ISO Compliance to either an AD-8121 printer or to a computer.

- Windows compatible data collection software
- USB compatible
- Auto re-zero function after each weighing
- 5 year warranty

Specifications

- Stabilization Time: 1 second
- Dimensions: 8.27 W x 12.5 D x 3.4 H in (210 W x 317 D x 86 H mm)
- Operating Temp: 5°C ~ 40 °C (14°F ~ 104°F)
- Power: approximately 11VA
- Standard Accessories: Manual, AC Adapter, Dust Cover

Model	Price	Capacity x Readability	Linearity	Repeatability	Pan Size	NTEP Class II
GF-800	\$1874.95	810 g x 0.001 g	+/-0.003 g	0.001 g	5 x 5 in (128 x 128 mm)	-
GF-1000	\$1898.05	1100 g x 0.001 g	+/-0.003 g	0.001 g	5 x 5 in (128 x 128 mm)	-
GF-1200	\$940	1210 g x 0.01 g	+/-0.02 g	0.01 g	6.5 x 6.5 in (165 x 165 mm)	-
GF-1200N	\$1060	1210 g x 0.01 g	+/-0.02 g	0.01 g		e-0.1 g d - 0.01 g
GF-200	\$985	210 g x 0.001 g	+/-0.002 g	0.001 g		-
GF-2000	\$985	2100 g x 0.01 g	+/-0.02 g	0.01 g		-
GF-2000N	\$1075	2100 g x 0.01 g	+/-0.02 g	0.01 g		e=0.1 g d = 0.01 g
GF-200N	\$1075	210 g x 0.001 g	+/-0.002 g	0.001 g		e=0.01 g d = 0.001 g
GF-300	\$1100	310 g x 0.001 g	+/-0.002 g	0.001 g	5 x 5 in (128 x 128 mm)	-
GF-3000	\$1100	3100 g x 0.01 g	+/-0.02 g	0.01 g	6.5 x 6.5 in (165 x 165 mm)	-
GF-3000N	\$1165	3100 g x 0.01 g	+/-0.02 g	0.01 g		e = 0.1 g d = 0.01 g
GF-300N	\$1165	310 g x 0.001 g	+/-0.002 g	0.001 g	5 x 5 in (128 x 128 mm)	e = 0.01 g d = 0.001 g
GF-400	\$1295	410 g x 0.001 g	+/-0.002 g	0.001 g	n/a	-
GF-4000	\$1295	4100 g x 0.01 g	+/-0.02 g	0.01 g		-
GF-600	\$1750	610 g x 0.001 g	+/-0.01 g	0.01 g		-

GF-6000	\$1300	6100 g x 0.1 g	+/-0.1 g	0.1 g	6.5 x 6.5 in (165 x 165 mm)	-
GF-6000N	\$1435	6100 g x 0.1 g	+/-0.1 g	0.1 g		e = 1 g d = 0.1 g
GF-6100	\$1780	6100 g x 0.01 g	+/-0.02 g	0.01 g		-
GF-8000	\$1525	8100 g x 0.1 g	+/-0.1 g	0.1 g		-

i81u812

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.