

## AND Weighing HV-60KC232 Legal For Trade Platform Scale with RS-232 30 x 0.01 lb - 60 x 0.02 lb - 150 x 0.05 lb

The HV/HW-C/CP scale family is designed to integrate easily into your weighing process. It offers a broad range of solutions for your checkweighing, parts counting or quality assurance applications. Raise your throughput, increase process security and improve your product and delivered quality





Manufature: AND Weighing SKU: HV-60KC232

Weight: 24.00 lb Free Ground Shipping within the 48 continental US States

Please Call (800)832-0055

## **Features**

Weighing for a Wide Variety of Applications

The HV/HW-C/CP scale family is designed to integrate easily into your weighing process. It offers a broad range of solutions for your checkweighing, parts counting or quality assurance applications. Raise your throughput, increase process security and improve your product and delivered quality

**Secure Compliance** Feel secure in your weighing process with built-in key lock function to prevent any unwanted changes and seamless data capture with available built-in printer. You can meet NTEP and Measurement Canada requirements with the HV-C and HV-CP models

**Increased Throughput** Speed up your weighing process with 1-second stabilization and a wide selection of accessories and connectivity options. Control the scale, change settings and output data via USB or RS-232C. Comparator lights reduce operator fatigue and errors.

**Improved Ergonomics** Large backlit terminal is visible even in dimly lit areas. Avoid neck and back strain with adjustable terminal head or with optional remote display and wall-mount bracket. Rollers make weighing heavy or large containers in production lines smoother and quicker.

**Reliable Counting & Portioning** Fast and efficient portioning and filling with Auto-Tare, which automatically tares the scale when the weight reaches a pre-set range. Combined with our Negative Checkweighing feature, you can now easily move parts from a master carton on the scale to containers on a production line.

**Robust & Dependable** IP65 rated base along with stainless steel weigh pan (SUS430) allow for wet weighing and is easy to keep clean and hygienic. All HV/W-C models can be easily moved and placed to best fit your process. They operate anywhere off of four standard D batteries.

	HV-C	HV-CP	HW-C	HW-CP
High-Speed Measurement	1 Second	1 Second		1.5 Second
Built-in Printer	-	YES	-	YES

Battery Operation	YES	-	YES	-
GLP/GMP	-	YES	-	YES
LED Comparator Lights	YES	YES	YES	YES
Auto-Tare	YES	YES	YES	YES
Negative Checkweighing	YES	YES	YES	YES
Legal for Trade	YES	YES	-	-
RS-232 Option HVW-03C	YES	YES	YES	YES
USB Option HVW-02CB	YES	YES	YES	YES

## Specifications

in o doi	111 10110	111 00110	117 200110	1111 10110	1111 00110	1111 100110	00
Model with RS-232	HV-15KC-232	HV-60KC-232	HV-200KC-232	-	-	-	-
Model with USB	HV-15KC-USB	HV-60KC-USB	HV-200KC-USB	-	-	-	-
Model with Build in Printer	HV-15KCP	HV-60KCP	HV-200KCP	HW-10KCP	HW-60KCP	HW-100KCP	HW-200
	3 x 0.001 kg 6 x 0.002 kg 15 x 0.005 kg	15 x 0.005 kg 30 x 0.01 kg 60 x 0.02 kg	60 x 0.02 kg 150 x 0.05 kg 220 x 0.1 kg	10 x 0.001 kg	60 x 0.005 kg	100 x 0.01 kg	220 x 0.02 kg
Capacity x Resolution	6 x 0.002 lb 15 x 0.005 lb 30 x 0.01 lb	30 x 0.01 lb 60 x 0.02 lb 150 x 0.05 lb	150 x 0.05 lb 300 x 0.1 lb 500 x 0.2 lb	20 x 0.002 lb	150 x 0.01 lb	200 x 0.02 lb	500 x 0.05 lb
	96 x 0.05 oz 240 x 0.1 oz 480 x 0.2 oz	480 x 0.2 oz 960 x 0.5 oz 2400 x 1 oz	2400 x 1 oz 4800 x 2 oz 8000 x 5 oz	320 x 0.05 oz	2400 x 0.2 oz	3200 x 0.5 oz	8000 x 1 oz
Max. countable number	150,000	120,000	110,000	100,000	120,00	100,000	110,000
Legal For Trade	NTEP #17-099			-	-	-	-
Number of samples	5, 10, 20, 50 or	100					
Stabilization time	Within 1 second	d		Within 1.5 seco	ond		
Repeatability (std. deviation) [kg]	0.001 0.002 0.005	0.005 0.01 0.02	0.02 0.05 0.1	0.002	0.01	0.02	0.04
Linearity [kg]	±0.001 ±0.002 ±0.005	±0.005 ±0.01 ±0.02	±0.02 ±0.05 ±0.1	±0.002	±0.01	±0.02	±0.04
Sensitivity drift	±20 ppm / °C (5	5 °C to 35 °C / 4′	1 °F to 95 °F)				

Model HV-15KC HV-60KC HV-200KC HW-10KC HW-60KC HW-100KC HW-200K

Display	7 segment LCD (Character height: 25 mm) with backlight; 3-color, 5-step LED comparator lights					
Display update	10 times / second					
Operating temperature	-10 °C to 40 °C / 14 °F to 104 °F, 85% R.H. or less (no condensation)					
Power	HV/W-C series: AC adapter or four D batteries (approx. 1200 hours using alkaline batteries, with display backlight and LED comparator lights OFF HV/W-CP series: AC adapter					
Weighing pan size	250 x 250 mm 9.8 x 9.8 in	330 x 424 mm 13.0 x 16.7 in	390 x 530 mm 15.4 x 20.9 in	250 x 250 mm 9.8 x 9.8 in	330 x 424 mm 13.0 x 16.7 in	390 x 530 mm 15.4 × 20.9 in
Dimensions (W × D × H)	275 x 474 x 368 mm 10.8 x 18.7 x 14.5 in	330 x 621 x 771 mm 13.0 x 24.5 x 30.4 in	390 x 712 x 773 mm 15.4 x 28.0 x 30.4 in	275 x 474 x 368 mm 10.8 x 18.7 x 14.5 in	330 x 621 x 771 mm 13.0 x 24.5 x 30.4 in	390 x 712 x 773 mm 15.4 x 28.0 x 30.4 in
Weight HV/W-C series	6 kg / 13 lb	11 kg / 24 lb	17 kg / 37 lb	6 kg / 13 lb	11 kg / 24 lb	17 kg / 37 lb
Weight HV/W-CP series	7 kg / 15 lb	12 kg / 26 lb	18 kg / 40 lb	7 kg / 15 lb	12 kg / 26 lb	18 kg / 40 lb

i81u812



Phone: (800)832-0055 or (718)336-5900
Chat with us via WhatsApp Chat
Address: 4802 Glenwood Rd. Brooklyn, NY 11234
© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.