

The SC/SE Series bench scale is constructed with a completely sealed indicator and a washdown base that meets IP68 standards. It provides exceptional performance with a stabilization speed of just 1 second!



Manufature: AND
Weighing
SKU:
SC-60KAM
Weight: 26.50 lb

Please Call
(800)832-0055

Features

The SC/SE Series bench scale is constructed with a completely sealed indicator and a washdown base that meets IP68 standards. It provides exceptional performance with a stabilization speed of just 1 second!

- IP68 dust and water-proof
- Washdown construction for easy cleaning
- 4500 hours of continuous operation with 6 D batteries¹
- Supersized LCD of 39 mm character height
- Easily switchable, multiple weighing units (kg, lb, oz, and pcs)
- Stabilization speed of 1 second
- Stainless steel weighing pan
- Waterproof and corrosion-resistant load cell²
- Quick USB interface³ or RS-232C + comparator relay output available as options
- [Manual](#)

1) Batteries are not included.

2) Aluminum anodized and coated with epoxy resin with protective silicon over wiring.

3) Cables are not included

Stainless Steel Construction Models	SC-30KAM	SC-60KAM	SC-150KAM	SC-60KAL	SC-150KAL
--	-----------------	-----------------	------------------	-----------------	------------------

Mild Steel Construction Models	SE-30KAM	SE-60KAM	SE-150KAM	SE-60KAL	SE-150KAL
Capacity X Readability	66 lb x 0.01 lb	130 lb x 0.02 lb	330 lb x 0.05 lb	130 lb x 0.02 lb	330 lb x 0.05 lb
	30 kg x 0.005 kg	60 kg x 0.01 kg	15 0kg x 0.02 kg	600 kg x 0.01 kg	150 kg x 0.02 kg
Repeatability (Std. deviation)	0.005 kg	0.01 kg	0.02 kg	0.01 kg	0.02 kg
Linearity	±0.01 kg	±0.02 kgb	±0.05 kg	±0.02 kg	±0.05 kg
Sensitivity drift	±20 ppm / °C (5°C to 35°C / 41°F to 95°F)				
No. of samples	5 pieces (can be changed to 10, 20, 50 or 100)				
Max. count	60,000 pcs	60,000 pcs	75,000 pcs	60,000 pcs	75,000 pcs
Min. unit weight	0.0005 kg	0.001 kg	0.002 kg	0.001 kg	0.002 kg
Units of Measure	lb, oz, kg				
Display	7 segment LCD display (character height 39 mm)				
Display update	10 times per second				
Operating temp.	-10°C to 40°C / 14°F to 104°F, 85% R.H. or less (non-condensing)				
Power supply	Size D batteries x6, Approximately 4,500 hours using alkaline batteries (models are battery power only)				
Weighing pan size	300 x 380 mm 11.8 x 15 in.			390 x 530 mm 15.4 x 20.9 in.	
Dimensions SC	300(W) x 543(D) x 717(H) mm 11.8(W) x 21.4(D) x 28.2(H) in.			390(W) x 688(D) x 717(H) mm 15.4(W) x 27.1(D) x 28.2(H) in.	
Dimensions SE	300(W) x 582(D) x 722(H) mm 11.8(W) x 22.9(D) x 28.4(H) in.			390(W) x 732(D) x 722(H) mm 15.4(W) x 28.8(D) x 28.4(H) in.	
Weight (approximately)	26.5 lb / 12 kg			35.3 lb / 16 kg	
Calibration weight	60 lb 30 kg	120 lb 60 kg	300 lb 150 kg	120 lb 60 kg	300 lb 150 kg

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

• Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)

• Chat with us via [WhatsApp Chat](#)

• Address: 4802 Glenwood Rd. Brooklyn, NY 11234

• © 2000 - 2023 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.