Ideal for industrial weighing and counting, AGB and AGF bench and floor scales feature sturdy construction and a rugged stainless steel indicator. 11.8 x 15.7 in 6 x 0.0005 lb





Capacity x Readability 16 lb x 0.0005 lb Pan Size 11.8 x 15.7 in

> Manufature: Adam Equipment SKU: AGB-16a

Please Call (800)832-0055

Features

Ideal for industrial weighing and counting, AGB and AGF bench and floor scales feature sturdy construction and a rugged stainless steel indicator. The scales are available in a choice of platform sizes and a wide selection of capacities. Operation is fast and easy, as results are readily visible on the backlit LCD that boasts 1.5in / 40mm-high digits. An internal rechargeable battery means the AGB/AGF can be used in locations where power is unavailable. Swiftly transmit results to computers or printers using the RS-232 interface.

- Hardware
- Color-coded keys facilitate quick recognition of the most frequently used buttons
- Heavy-duty rubber feet ensure stability of unit
- Large, grade 304 stainless steel pan allows swift cleaning
- Rugged construction stands up to industrial use
- RS-232 interface is available to provide speedy connection to computers and printers

Software

- External calibration allows for verification and adjustment with weights
- Hold function freezes the displayed weight, allowing time to elapse without losing the result
- Checkweighing with audible alarm
- Parts counting with preset sample sizes
- Selectable digital filtering for animal/dynamic weighing enables consistent results for moving subjects

• Display

• Backlit display changes color for quick notification of checkweighing limits

• Power

- Rechargeable battery included for operation almost anywhere
- Programmable auto power-off to save energy

Backlit LCD with sizeable digits means results are easy to read, speeding up weighing tasks Applications

Parts counting Percentage weighing Checkweighing

Specific	ations								
Model	AGB-16a	AGB-35a	AGB-65a	AGB-175a	AGB-260a	AGF-175a	AGF-350a	AGF-660a	AGF-1320
x	16 x 0.0005 lb y 8 kg x 0.2 g	35 x 0.001 lb 16 kg x 0.5 g	65 x 0.002 lb 30 kg x 1 g	175 x 0.005 lb 80 kg x 2 g	260 x 0.01 lb 120 kg x 5 g	175 x 0.005 lb 80 kg x 2 g	350 x 0.01 lb 160 kg x 5 g	660 x 0.02 lb 300 x 0.01 kg	1320 x 0.05 lb 600 x 0.02 kg
Repeatabi (S.D.)	liðy 001 lb / 0.5g	0.002 lb / 1g	0.004 lb / 2g	0.01 lb / 5g		0.005 lb / 2g	0.01 lb / 5g	0.00 lb /	0.05 lb / 0.02kg
Linearity (+/-)	0.001 lb / 0.5g	0.002 lb / 1g	0.004 lb / 2g	0.01 lb / 5g	0.02 lb / 10g	0.01 lb / 5g	0.02 lb / 10g	0.05 lb / 0.02 kg	0.1 lb / 0.04 kg
Platform Size	11.8 x 15.7 in15.7 x 19.7 in300 x 400 mm400 x 500 mm							23.6 x 31. in 600 x 800 mm	
Stabilizatio Time	2 Sec								
Weighing Units	g, kg, N, lb, lb:oz, oz, custom unit								
Interface	RS-232								
Calibration	nExternal								
Display	Backlit LCD with 1.6"/ 40mm -high digits								
Power supply	12VDC 800mA adapter / Internal rechargeable battery								
Operating temperatu	-10° to 40°C re	C / 14° to 104	ŀ°F						
Housing	Stainless st	eel indicator	with die-cast	t aluminum b	ase				
Overall Dim.(wxdx	11.8 x 20.5 x 25.8 in15.7 x 24.6 x 33.7 indx 13)00 x 520 x 655 mm400 x 625 x 855 mm								23.6 x 36. x 34.6 in 600 x 935 x 880 mm
Net Weight	30.9 lb / 14	kg				39.7 lb / 18	٨g		77.1lb / 35kg
700400103 307401050 300401321 112001464 112001115 110001129 600002028	4 1 6 7	RS-232 c RS-232 t Light tow AIP impa ATP ther Relay bo AdamDU	able to USB adap ver kit includi act printer mal printer x Data Collect	ption ter (must ord ng relay box tion Program	·	ding RS-232	cable)		

i81u812



© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.