Adam Equipment GGB-165a Gladiator Washdown IP67 11.8 x 15.7 inch Bench Scale 165 x 0.01 lb

Featuring a combination of durability and performance, Gladiator scales accomplish washdown weighing tasks in demanding food, pharmaceutical and industrial settings. With an IP67 rating for washdown capabilities, Gladiator features easy-to-clean stainless steel construction that is ideal for wet and dusty environments. 11.8 x 15.7 inch Bench Scale 165 x 0.01 lb

ADAM

Capacity x Readability
165 lb x 0.01 lb
Pan Size
11.8 x 15.7 in

Manufature: Adam Equipment
SKU: **GGB-165a**
Weight: 23.00 lb

**Please Call
(800)832-0055**

Features

Featuring a combination of durability and performance, Gladiator scales accomplish washdown weighing tasks in demanding food, pharmaceutical and industrial settings. With an IP67 rating for washdown capabilities, Gladiator features easy-to-clean stainless steel construction that is ideal for wet and dusty environments. Connectors on the bottom are IP67-rated for thorough protection. Gladiator can expedite checkweighing tasks, with a large, backlit display that changes color to show if the weight is over, under or within the set limit. The keypad is designed for maximum efficiency, with large, color-coded tactile keys for fast recognition and easy operation.

Features and Benefits

- **Approval**
- IP67-rated for protection against water and dust
- **Hardware**
- Large, grade 304 stainless steel pan allows swift cleaning
- Rugged stainless steel construction for ultimate durability
- Heavy-duty rubber feet ensure stability of unit
- Sealed keypad protects against dirt and spills
- Color-coded keys facilitate quick recognition of the most frequently used buttons
- RS-232 interface is available to provide speedy connection to computers and printers
- External calibration allows for verification and adjustment with weights
- Hold function freezes the displayed weight, allowing time to elapse without losing the result
- Parts counting with preset sample sizes
- Selectable digital filtering for animal/dynamic weighing enables consistent results for moving subjects
- **Display**
- Backlit display changes color for quick notification of checkweighing limits
- **Power**
- Rechargeable battery included for operation almost anywhere
- Programmable auto power-off to save energy

  Applications
- Weighing
- Parts counting
- Percentage weighing
- Checkweighing
- Check counting

- Display hold

Specifications

MODEL	GGS-16a	GGS-35a	GGS-65a	GGB-65a	GGB-65aH	GGB-165a	GGF-165a	GGF-165aH	GGF-330a	GGL-330a
Capacity x Readability	16 x 0.001 lb	35 x 0.002 lb	65 x 0.005 lb	65 x 0.005 lb	65 x 0.002 lb	165 x 0.01 lb	165 x 0.01 lb	165 x 0.005 lb	330 x 0.02 lb	330 x 0.02 lb
Capacity x Readability	8 kg x 0.5 g	16 kg x 1 g	35 kg x 2 g	35 kg x 2 g	35 kg x 1 g	75 kg x 5 g	75 kg x 5 g	75 kg x 2 g	150 kg x 10g	150 kg x 10g
Repeatability (S.D.)	0.002 lb 1g	0.004 lb 2g	0.01 lb 4g	0.01 lb 4g	0.004 lb 2g	0.02 lb 10g	0.02 lb 10g	0.01 lb 4g	0.04 lb 20g	0.04 lb 20g
Linearity (+/-)	0.04lb 1g	0.004lb 2g	0.01lb 4g	0.01lb 4g	0.006lb 2g	0.02lb 10g	0.02 lb 10g	0.0 1lb 4g	0.04 lb 20g	0.04 lb 20g
Pan Size	9.8" x 9.8" 250 x 250 mm			11.8" x 15.7" 300 x 400 mm			15.7" x 19.7" 400 x 500 mm			17.7" x 23.6" 450 x 600 mm
Weighing Units	g, kg, lb, lb:oz, oz, N, custom unit									
Stabilization Time (sec)	2 s									
IP Rating	IP67									
Interface	Bold 1-inch/25-mm high backlit LCD									
Standard I/O	Optional RS-232									
Calibration	External calibration									
Display	Backlit LCD with 1.6"/ 40mm -high digits									
Power Supply	Internal rechargeable battery / 12VDC 800mA adapter									
Operating Temperature	-10° to 40°C / 14° to 104°F									
Housing	Stainless steel									
Overall Dim.	9.8" x 13.8" x 22.6" 250 x 351 x 575 mm			11.8" x 20.6" x 26" 300 x 523 x 662 mm			15.8" x 23.8" x 40.6" 400 x 605 x 1032 mm			17.7" x 27.6" x 40.6" 450 x 702 x 1032 mm
Net Weight	14.99 lbs 6.80 kg			22.97 lbs 10.42 kg			28.80 lbs 13.06 kg			46.50 lbs 21.09 kg

i81u812