

Avery Berkel Models 6710 is designed for use in cafeterias, convenience stores, delicatessens, restaurants, candy shops or anywhere space is a premium.



Manufacture: Avery Berkel
SKU: 9504-16663
Weight: 17.00 lb

Please Call (800)832-0055

Features

Standard point-of-sale interface scale for linking to electronic cash registers or POS systems.

- Easy to Read Six-digit LCD external display with large 0.5" characters, tactile keys.
- Accurate and Reliable Quality load cell and electronics ensure repeatable weight measurements and troublefree operation.
- Easy to Install Bi-directional 9-pin RS232 port. Interfaces to most electronic cash registers and point-of-sale software programs.
- Quick Disconnects Makes all cable connections easy.
- OPOS Compatible OPOS developers tool kit available for POS systems integration.

Features & Benefits

- Auto Zero Tracking Zero light indicator and manual control when out of range.
- Interface Protocols NCI, ECR, 8213 (Sharp), 2250 (Swintec), ATT, 0400 (Olympia)
- Alternate Calibration Points Allows use of less than full capacity weight for calibration.
- Construction (6702/6710) Stainless steel weighing area with full skirt around perimeter of base, except where connectors are located at rear of scale. (6720) stainless steel weight platter, die cast aluminum base.
- Power Input: 120 VAC (+10% -15%)/ 60 Hz (±3 Hz)
Standard 3 wire with ground input
Output: 15 VDC @ 0.3 Amps minimum
Power cord: 6 foot

- Agency Approvals
NTEP COC # 95-070
Canada W&M, COC AM-5076
UL Listed, CSA certified power supply

6710 Series Scales					
Part Number	9504-16655	9504-16453	9504-16663	9504-16452	9504-13721
Capacity	15 lb x 0.005 lb	30 lb x 0.01	7 kg x 0.002 kg	15 kg x 0.005 kg	15lb x 0.005 lb
POSITOUCH Software Included	No				Yes
Dimensions	Weigh Platter: 10" x 10" (254 mm x 254 mm) Remote Display Enclosure: 5.8" W x 3.0" H x 1.4" D max (147 mm x 76 mm x 35 mm) Adjustable Height: 2.5" – 3.0" (63 mm – 76 mm)				
Power	Input: Wall mount transformer 120 VAC (+10% -15%)/ 60 Hz (±3 Hz) Standard 3 wire with ground input Output: 15 VDC @ 0.3 Amps minimum				
Display	Six-digit LCD external display with large 0.5" characters, tactile keys, 7 ft. cable and Velcro™ for mounting.				
Interfaces	RS-232, 4-bit parallel, 40-bit serial, and OPOS.				
Auto Zero Tracking	Zero light indicator and manual control when out of range.				
Construction	Stainless steel weighing area with full skirt around perimeter of base, except where connectors are located at rear of scale.				
Operating Environment	41°F to 104°F (5°C to 40°C) (Class III device) 10% to 90% RH (non-condensing)				
Certifications	Legal for Trade, NTEP Class III, USA COC #95-070A5 Canada: MOI approval #AM-5076 Rev. 2 Power Supply: UL Listed, CSA Certified				

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

• Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)

• Chat with us via [WhatsApp Chat](#)

• Address: 4802 Glenwood Rd. Brooklyn, NY 11234

• © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.