

The RWT-F Series wheel weigher pads are available in 4 different sizes and 4 capacities. The ultra low profile platforms are designed to weigh trucks with a multitude of axle configurations and capacity requirements. Each wheel weigher platform includes an integral weight display, and can be wirelessly interfaced up to 12 platforms via the RWT-5000F Indicator/ Printer. This kit includes 2 Scales and an indicator.



This Item Contains the following items

<u>2 x CAS</u>	<u>1 x CAS</u>
<u>RWT-710F</u>	<u>RWT-5000F</u>
<u>Wireless</u>	<u>Wireless</u>
<u>Wheel</u>	<u>Indicator for</u>
<u>Weighing</u>	<u>RWT</u>
<u>Scale</u>	<u>wireless</u>
<u>20,000 x 10</u>	<u>wheel</u>
<u>lb</u>	<u>weighers</u>

Manufacture: CAS
 SKU: **RWT710FK1**

Please Call
(800)832-0055

Features

This kit includes 2 Scales and an indicator

The RWT-F Series wheel weigher pads are available in 4 different sizes and 4 capacities. The ultra low profile platforms are designed to weigh trucks with a multitude of axle configurations and capacity requirements. Each wheel weigher platform includes an integral weight display, and can be wirelessly interfaced up to 12 platforms via the RWT-5000F Indicator/ Printer. **Full Featured & Fully Accessorized**

Each RWT-F Series wheel weigher includes (2) two rechargeable Lithium Polymer (Li-Po) batteries and optional lightweight urethane ramps

- 10K, 20K, 30K, & 40K Capacities
- Ultra Low Profile Design - 1.4" (34mm) high

- Rechargeable Lithium Polymer Battery Pack
- Optional Portable Indicator w/Thermal Printer
- Connect up to 12 Wireless Platforms Simultaneously
- Static and In-Motion Weighing Capabilities

Build the Right Wheel Weigher System for your specific needs!

Utilizing optional dummy plates and dummy plate connectors, build a wheel weigher system that fits your specific needs! For in-motion weighing applications, use a single axle layout (2 scale platforms) including sufficient ramps and dummy plates to insure optimum level weighing conditions. For static weighing, the RWT-F wheel weighers may be joined via optional plates and connectors, allowing up to 12 platforms to be wirelessly interfaced via the RWT-5000F Indicator/Printer.

The RWT-5000F Indicator/Printer is enclosed in a portable, water tight case and provides weight information that includes individual wheel weight, individual axle weight, and total weight. Also included in RWT-5000F are built in USB and RS-232C ports, optional USB memory stick, memory for up to 10,000 vehicles, and connectivity to model CRD2300F/3000F wireless Remote Display units. **Self Contained Portable Unit** The RWT-5000F Wireless Indicator is housed in a protective hardened plastic case with waterproof seals when closed. **Zigbee Wireless** The RW-Z Series Wheel Weighers features Zigbee Wireless technology. Connect up to 12 RWT-F Wheel Weighing Pads within the same communication range. **Printer** The RWT-5000F includes a high speed thermal printer. Prints receipts with 100 mm/sec speed and 202 dpi resolution. Use with CAS Receipt Paper #TS-25050 **Interface** The RWT-5000F is equipped with a RS-232 output for PC interface, USB port, DC jack, and wireless communication capabilities to CAS Wirelsss Remote Displays **Display & Keypad** The RWT-5000F is equipped with a backlit LCD Display and numeric keypad

Specifications

Model	RWT-505F	RWT-705F	RWT-710F	RWT-715F	RWT-910F	RWT-915F	RWT-920F
Capacity x Readability	10,000 x 5 lb	10,000 x 5 lb	20,000 x 10 lb	30,000 x 20 lb	20,000 x 10 lb	30,000 x 20 lb	40,000 x 20 lb
	5,000 x 2 kg	5,000 x 2 kg	10,000 x 5 kg	15,000 x 10 kg	10,000 x 5 kg	15,000 x 10 kg	20,000 x 10 kg
Display	5 Digit LCD - Height: 0.6 in/15mm - Backlight						
Keypad	On/Off, Zero, Sum, Backlight						
Accuracy	0.1%						
In-Motion Speed	Up to 6 miles per hour / 10 kilometers per hour						
Operating Time	Approx 70hr						
Operating Temp	-40 ^a F ~ 140 ^a F / -20 ^a C ~ +60 ^a C						
Power	3.7VDC Lithium Polymer Battery						
Product Weight	33.1 lbs / 15 kg	37.5 lbs / 17 kg		44.1 lbs / 20 kg	61.7 lbs / 28 kg	61.7 lbs / 28 kg	88.2 lbs / 40 kg
Safe Overload	150% of rated capacity						
Warranty	2						
Platform Dimensions	19.7 (W) x 15 (D) x 1.4 (H)	27.6 (W) x 16.1 (D) x 1.4 (H)			35.4 (W) x 20 (D) x 1.4 (H)		35.4 (W) x 24 (D) x 1.4 (H)

Dimensions (inches)(mm)	500 (W) x 380 (D) x 34 (H)	700 (W) x 410 (D) x 34 (H)	900 (W) x 510 (D) x 34 (H)	900 (W) x 600 (D) x 34 (H)
Total Dimensions (inches)(mm)	26.5 (W) x 20.9 (D) x 2 (H)	34.9 (W) x 28.8 (D) x 2 (H)	42 (W) x 33 (D) x 2 (H)	42 (W) x 37 (D) x 2 (H)
	674 (W) x 532 (D) x 50 (H)	886 (W) x 730 (D) x 50 (H)	1066 (W) x 840 (D) x 50 (H)	1066 (W) x 940 (D) x 50 (H)

i81u812

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.