

## CAS RWT-915F - Wireless Wheel Weighing Scale with Indicator 30,000 x 20 lb

The RWT-F Series wheel weigher pads are available in 4 different sizes and 4 capacities. The ultra low profile platforms are designed to weigh trucks with a multitude of axle configurations and capacity requirements. Each wheel weigher platform includes an integral weight display, and can be wirelessly interfaced up to 12 platforms via the RWT-5000F Indicator/ Printer. This kit includes 2 Scales and an Indicator.





# This Item Contains the following items

2 x CAS 1 x CAS RWT-915F RWT-5000F Wireless Wireless Indicator for Wheel Weighing RWT Scale wireless 30,000 x 20 wheel weighers lb\_

Manufature: CAS SKU: **RWT-915FK1** 

Please Call (800)832-0055

#### **Features**

This kit includes 2 Scales and an Indicator.

The RWT-F Series wheel weigher pads are available in 4 different sizes and 4 capacities. The ultra low profile platforms are designed to weigh trucks with a multitude of axle configurations and capacity requirements. Each wheel weigher platform includes an integral weight display, and can be wirelessly interfaced up to 12 platforms via the RWT-5000F Indicator/ Printer. **Full Featured & Fully Accessorized** 

Each RWT-F Series wheel weigher includes (2) two rechargeable Lithium Polymer (Li-Po) batteries and optional lightweight urethane ramps

- 10K, 20K, 30K, & 40K Capacities
- Ultra Low Profile Design 1.4" (34mm) high

- Rechargeable Lithium Polymer Battery Pack
- Optional Portable Indicator w/Thermal Printer
- Connect up to 12 Wireless Platforms Simultaneously
- Static and In-Motion Weighing Capabilities

#### **Build the Right Wheel Weigher System for your specific needs!**

Utilizing optional dummy plates and dummy plate connectors, build a wheel weigher system that fits your specific needs! For in-motion weighing applications, use a single axle layout (2 scale platforms) including sufficient ramps and dummy plates to insure optimum level weighing conditions. For static weighing, the RWT-F wheel weighers may be joined via optional plates and connectors, allowing up to 12 platforms to be wirelessly interfaced via the RWT-5000F Indicator/Printer.

The RWT-5000F Indicator/Printer is enclosed in a portable, water tight case and provides weight information that includes individual wheel weight, individual axle weight, and total weight. Also included in RWT-5000F are built in USB and RS-232C ports, optional USB memory stick, memory for up to 10,000 vehicles, and connectivity to model CRD2300F/3000F wireless Remote Display units. **Self Contained Portable Unit** The RWT-5000F Wireless Indicator is housed in a protective hardened plastic case with waterproof seals when closed. **Zigbee Wireless** The RW-Z Series Wheel Weighers features Zigbee Wireless technology. Connect up to 12 RWT-F Wheel Weighing Pads within the same communication range. **Printer** The RWT-5000F includes a high speed thermal printer. Prints receipts with 100 mm/sec speed and 202 dpi resolution. Use with CAS Receipt Paper #TS-25050 **Interface** The RWT-5000F is equipped with a RS-232 output for PC interface, USB port, DC jack, and wireless communication capabilities to CAS Wirelsss Remote Displays **Display & Keypad** The RWT-5000F is equipped with a backlit LCD Display and numeric keypad

### **Specifications**

Model	RWT-505F	RWT-705F	RWT-710F	RWT-715F	RWT-910F	RWT-915F	RWT-920F	
	10,000 x 5	10,000 x 5	20,000 x	30,000 x	20,000 x	30,000 x	40,000 x 20	
Capacity x	lb	lb	10 lb	20 lb	10 lb	20 lb	lb	
Readability	5,000 x 2	5,000 x 2	10,000 x 5	15,000 x	10,000 x 5	15,000 x	20,000 x 10	
	kg	kg	kg	10 kg	kg	10 kg	kg	
Display	5 Digit LCD - Height: 0.6 in/15mm - Backlight							
Keypad	On/Off, Zero, Sum, Backlight							
Accuracy	0.1%							
In-Motion	Up to 6 miles per hour / 10 kilometers per hour							
Speed	op to o tilles per flour / To kilottleters per flour							
Operating	Approx 70hr							
Time	Αρριολ Τοιιι							
Operating	-4¢°F ~ 140¢°F / -20¢°C ~ +60¢°C							
Temp	' ' ' '							
Power	3.7VDC Lithium Polymer Battery							
Product	33.1 lbs /	37.5 lbs	s / 17 kg	44.1 lbs /	61.7 lbs /	61.7 lbs /	88.2 lbs /	
Weight	15 kg			20 kg	28 kg	28 kg	40 kg	
Safe Overload	150% of rated capacity							
Warranty	2							
	19.7 (W) x				35.4 (W) >	( 20 (D) x	35.4 (W) x	
Platform	15 (D) x 27.6 (W) x 16.1 (D) x 1.4 (H)				1 4 (H) 24 (D		24 (D) x 1.4	
Dimaneione	1.4 (H)	1.4 (H) (H)						

(inches)(mm)	500 (W) x 380 (D) x 34 (H)	700 (W) x 410 (D) x 34 (H)	900 (W) x 510 (D) x 34 (H)	900 (W) x 600 (D) x 34 (H)
Total Dimensions (inches)(mm)	26.5 (W) x 20.9 (D) x 2 (H)	34.9 (W) x 28.8 (D) x 2 (H)	42 (W) x 33 (D) x 2 (H)	42 (W) x 37 (D) x 2 (H)
	674 (W) x 532 (D) x 50 (H)	886 (W) x 730 (D) x 50 (H)	1066 (W) x 840 (D) x 50 (H)	1066 (W) x 940 (D) x 50 (H)

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

Phone: <u>(800)832-0055</u> or <u>(718)336-5900</u> Chat with us via <u>WhatsApp Chat</u>

Address: 4802 Glenwood Rd. Brooklyn, NY 11234

© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.