

Cambridge CSW-15AT & CSW-15AT-B Wireless Remote Control and 1 1/2" Red LED Display Digital Weight Indicator Selectable NTEP 5,000 Division Non-NTEP 20,00 Division



C A M B R I D G E
SCALE WORKS INCORPORATED

Manufacture: Cambridge Scale

SKU: **CSW-15AT-B**

Dimensions

X: 8.50 Y: 7.00 Z: 3.00

Weight: 7.00 lb

Please Call (800)832-0055

Features

Standard Features Include

- Wireless Remote Control
- 1.5" Red LED Display
- Selectable NTEP 5,000 Division Non-NTEP 20,00 Division
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- 9 Pin Load Cell Connection
- Clearly, Visible Center of Zero Indication on Display
- Weight Totalization
- Keypad Calibration with Audit Trail
- 1 to 5 Points of Digital Calibration
- Span Adjustment @ Increasing or Decreasing Weights
- Lb/Kg Conversion
- Complete Digital Calibration
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
 - Printer Output of Gross/Tare/Net
 - Computer Data Output

- Scoreboard Continuous Output Alphanumeric or Numeric

- AC Adapter Provided
- Auto Zero Tracking
- Adjustable Motion Detection
- Die-Cast Aluminum Dust-Tight Enclosure with Swivel Stand

Applications:

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Axle Scales
- General Purpose Weighing
- Remote Display Configuration

Model CSW-15AT-B - For portable applications where battery operation is required. Includes all standard CSW-15AT-B features plus:

- Battery/AC Operation
- Internal Battery Charger
- Lithium-Ion Battery Charger
- Sleep Mode

Optional Features: for Model CSW-15AT-B

- Peak Weight Hold
- Digital Scroll Tare
- RFL-Radio Frequency Link
- WiFi transmitter to customers wireless hub
- Spare Battery
- Spare Battery Charger

Specifications

Model	CSW-15AT	CSW-15AT-B
Power	120 VAC Adapter / 12 VDC ±10%	8 VDC 3000 AH* Battery / 120 VAC
Battery Operated	NO	YES
NON-NTEP Resolution	20,000 Division	
Legal for Trade	NTEP #06-070A1	
	Measurement Canada #AM-5778C	
	NTEP Resolution 5000 Division	
Humidity	0-90% Non-condensing	
Dimensions	9.38" x 6.25" x 3.25" without Stand, +2.25 inch with Stand	
Enclosure	Die Cast Aliminum	
Display	High Efficient, Bright Adjustable LED—6 Digits—1.5" High	
Input	0-15mv	
Temperature	10" to +40" Celsius	
Linearity	0.001% of Full Scale	
Accuracy	0.001% of Full Scale	
Load Cell Supply	5VDC at 150ma (8 each 350 ohm load cells)	

Battery Oprating Time -

(1) 350 OHM Cell - 22hrs
(4) 350 OHM Cell - 20hrs
(8) 350 OHM Cell - 14hrs

Ports RS-232

Country of Origin USA

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
 - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.