



Cambridge CSW-15AT-B 1.5 LED Indicator Legal for Trade with Battery and Wireless Remote

Cambridge CSW-15AT & CSW-15AT-B Wireless Remote Control and 1 1/2" Red LED Display Digital Weight Indicator Selectable NTEP 5,000 Division Non-NTEP 20,00 Division



**C A M B R I D G E**  
SCALE WORKS INCORPORATED

Manufacture: Cambridge Scale

SKU: CSW-15AT-B

Dimensions

X: 8.50 Y: 7.00 Z: 3.00

Weight: 7.00 lb

**Please Call (800)832-0055**

## Features

### Standard Features Include

- Wireless Remote Control
- 1.5" Red LED Display
- Selectable NTEP 5,000 Division Non-NTEP 20,00 Division
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- 9 Pin Load Cell Connection
- Clearly, Visible Center of Zero Indication on Display
- Weight Totalization
- Keypad Calibration with Audit Trail
- 1 to 5 Points of Digital Calibration
- Span Adjustment @ Increasing or Decreasing Weights
- Lb/Kg Conversion
- Complete Digital Calibration
- Full Range Push Button Zero

- (1) RS-232 Port for Interface with:
  - Printer Output of Gross/Tare/Net
  - Computer Data Output
  - Scoreboard Continuous Output Alphanumeric or Numeric

- AC Adapter Provided
- Auto Zero Tracking
- Adjustable Motion Detection
- Die-Cast Aluminum Dust-Tight Enclosure with Swivel Stand

**Applications:**

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Axle Scales
- General Purpose Weighing
- Remote Display Configuration

**Model CSW-15AT-B** - For portable applications where battery operation is required. Includes all standard CSW-15AT-B features plus:

- Battery/AC Operation
- Internal Battery Charger
- Lithium-Ion Battery Charger
- Sleep Mode

Optional Features: for Model CSW-15AT-B

- Peak Weight Hold
- Digital Scroll Tare
- RFL-Radio Frequency Link
- WiFi transmitter to customers wireless hub
- Spare Battery
- Spare Battery Charger

## Specifications

Model	CSW-15AT	CSW-15AT-B
<b>Power</b>	120 VAC Adapter / 12 VDC ±10%	8 VDC 3000 AH* Battery / 120 VAC
<b>Battery Operated</b>	NO	YES
<b>NON-NTEP Resolution</b>	20,000 Division	
<b>Legal for Trade</b>	NTEP #06-070A1 Measurement Canada #AM-5778C NTEP Resolution 5000 Division	
<b>Humidity</b>	0-90% Non-condensing	
<b>Dimensions</b>	9.38" x 6.25" x 3.25" without Stand, +2.25 inch with Stand	
<b>Enclosure</b>	Die Cast Aliminum	
<b>Display</b>	High Efficient, Bright Adjustable LED—6 Digits—1.5" High	
<b>Input</b>	0-15mv	
<b>Temperature</b>	10" to +40" Celsius	
<b>Linearity</b>	0.001% of Full Scale	

<b>Accuracy</b>	0.001% of Full Scale
<b>Load Cell Supply</b>	5VDC at 150ma (8 each 350 ohm load cells)
<b>Battery Oprating Time -</b>	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs
<b>Ports</b>	RS-232
<b>Country of Origin</b>	USA

i81u812

[Contact US](#)

[718-336-5900](#)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](#) or [\(718\)336-5900](#)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.