

Cambridge Stainless Steel Model SSCSW-10AT & SSCSW-10AT-B Digital Weight Indicator Legal for Trade Stainless Steel NEMA 4X Enclosure with Stainless Steel Swivel Stand. Selectable NTEP 5,000 Divisions Non-NTEP 20,000 Divisions



C A M B R I D G E
SCALE WORKS INCORPORATED

Manufacture: Cambridge Scale

SKU: **SSCSW-10AT**

Dimensions

X: 8.50 Y: 7.00 Z: 3.00

Weight: 7.00 lb

Please Call (800)832-0055

Features

Cambridge CSW-10AT Digital Weight Indicator Legal for Trade

- Stainless Steel NEMA 4X Enclosure with Stainless Steel Swivel Stand
- Selectable NTEP 5,000 Divisions Non-NTEP 20,000 Divisions
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- Clearly, Visible Center of Zero Indication on Display
- Lb/Kg Conversion
- Keypad Calibration with Audit Trail
- Weight Totalization
- 1 to 5 points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
 - Printer Output of Gross/Tare/Net
 - Computer Data Output
 - Scoreboard Continuous Output Alphanumeric or Numeric
- 120 VAC Cord with Ground

- Auto Zero Tracking
- Adjustable Motion Detection
- (6) Pin Water Tight Signal Connection
- RFI / EMI Screened

Options: Models SSCSW-10AT

- 110 VAC Dry Contact Set Point
- Peak Weight Hold
- Digital Scroll Tare
- WiFi transmitter to customers wireless hub

Specifications

Model	CSW-10AT	CSW-10AT-B	SSCSW-10AT	SSCSW-10AT-B
Power	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 3000 mAH* Battery/120 VAC Adapter	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 3000 mAH* Battery/120 VAC Adapter
Battery Operated	NO	YES	NO	YES
NON-NTEP Resolution	20,000 Division			
Legal for Trade	NTEP #06-070A1 Measurement Canada #AM-5778C NTEP Resolution 5000 Division			
Humidity	0-90% Non-condensing			
Dimensions	6.5" x 4.3" x 2.5" without Stand, +1 inch with Stand		7.5" x 4.5" x 3" without Stand, +1 inch with Stand	
Enclosure	ABS Plastic		304 Stainless Steel NEMA 4X	
Display	High Efficient, Bright (Adjustable)LED—6 Digits—0.56" High			
Input	0-15mv			
Temperature	10" to +40" Celsius			
Linearity	0.001% of Full Scale			
Accuracy	0.001% of Full Scale			
Load Cell Supply	5VDC at 150ma (8 each 350 ohm load cells)			
Battery Oprating Time	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs
Ports	RS-232			
Country of Origin	USA			

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
 - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.