

Cambridge Stainless Steel Model SSCSW-10AT & SSCSW-10AT-B Digital Weight Indicator Legal for Trade Stainless Steel NEMA 4X Enclosure with Stainless Steel Swivel Stand. Selectable NTEP 5,000 Divisions Non-NTEP 20,000 Divisions



**C A M B R I D G E**  
SCALE WORKS INCORPORATED

Manufacture: Cambridge Scale

SKU: **SSCSW-10AT-B**

Dimensions

X: 8.50 Y: 7.00 Z: 3.00

Weight: 7.00 lb

**Please Call (800)832-0055**

## Features

- Stainless Steel NEMA 4X Enclosure with Stainless Steel Swivel Stand
- Selectable NTEP 5,000 Divisions Non-NTEP 20,000 Divisions
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- Clearly, Visible Center of Zero Indication on Display
- Lb/Kg Conversion
- Keypad Calibration with Audit Trail
- Weight Totalization
- 1 to 5 points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
  - Printer Output of Gross/Tare/Net
  - Computer Data Output
  - Scoreboard Continuous Output Alphanumeric or Numeric
- 120 VAC Cord with Ground
- Auto Zero Tracking

- Adjustable Motion Detection
- (6) Pin Water Tight Signal Connection
- RFI / EMI Screened

**Model SSCSW-10AT-B** For portable applications where battery operation is required. Includes all standard SSCSW-10AT features plus:

- Battery/AC Operation
- Internal Battery Charger
- Internal Lithium-Ion Battery
- Sleep Mode

**Options:** Models SSCSW-10AT-B

- Digital Scroll Tare
- Spare Battery (P/N 1165-1012-00)
- Peak Weight Hold

## Specifications

Model	CSW-10AT	CSW-10AT-B	SSCSW-10AT	SSCSW-10AT-B
<b>Power</b>	120 VAC Adapter / 12 VDC $\pm 10\%$	7.4 VDC 3000 mAH* Battery/120 VAC Adapter	120 VAC Adapter / 12 VDC $\pm 10\%$	7.4 VDC 3000 mAH* Battery/120 VAC Adapter
<b>Battery Operated</b>	NO	YES	NO	YES
<b>NON-NTEP Resolution</b>	20,000 Division			
<b>Legal for Trade</b>	NTEP #06-070A1 Measurement Canada #AM-5778C NTEP Resolution 5000 Division			
<b>Humidity</b>	0-90% Non-condensing			
<b>Dimensions</b>	6.5" x 4.3" x 2.5" without Stand, +1 inch with Stand		7.5" x 4.5" x 3" without Stand, +1 inch with Stand	
<b>Enclosure</b>	ABS Plastic		304 Stainless Steel NEMA 4X	
<b>Display</b>	High Efficient, Bright (Adjustable)LED—6 Digits—0.56" High			
<b>Input</b>	0-15mv			
<b>Temperature</b>	10" to +40" Celsius			
<b>Linearity</b>	0.001% of Full Scale			
<b>Accuracy</b>	0.001% of Full Scale			
<b>Load Cell Supply</b>	5VDC at 150ma (8 each 350 ohm load cells)			
<b>Battery Operating Time</b>	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs
<b>Ports</b>	RS-232			

i81u812

[Contact US](#)

[718-336-5900](#)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](#) or [\(718\)336-5900](#)
  - Chat with us via [WhatsApp Chat](#)
  - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.