



Cambridge SSCSW-20AT-B LED Indicator Stainless Steel Legal for Trade with Battery and Full Numeric Keypad

Cambridge CSW-20AT & CSW-20AT-B & SSCSW-20AT & SSCSW-20AT-B Digital Weight Indicators Legal for Trade, Full Numeric Keypad and two RS-232



**C A M B R I D G E**  
SCALE WORKS INCORPORATED

Manufacture: Cambridge Scale

SKU: SSCSW-20AT-B

Dimensions

X: 8.50 Y: 7.00 Z: 3.00

Weight: 7.00 lb

**Please Call (800)832-0055**

## Features

### Standard Features Include

- Stainless Steel Nema 4X Enclosure
- Stainless Steel Swivel Stand
- 6-Digit .56" Red LED Display
- 6-Pin Watertight Signal Cable Connections
- No Solder Strain Relief Communication Connections
- Red LED Annunciators
- Full Numeric Keypad
- 1 to 5 Points of Linearization
- Span Adjustment at Increasing or Decreasing Weights
- Keypad Configuration & Calibration with Audit Trail
- Front Panel Lock Out
- Keypad / Auto Tare
- Auto Zero Tracking
- Adjustable Motion Detecting
- Adjustable Digital Filtering
- Time & Date
- (2) RS-232 Ports
- Print Configuration

- Scale ID Entry (30 Alpha Numeric)
- Weight Totalization (99 Weights)
- ID# Entry (20 Digits)
- Piece Counting
- 120 VAC Cord with Ground
- Selectable: NTEP 5,000 Divisions NON-NTEP 20,000 Divisions

**Applications:**

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Fork Lift Scales
- Counting Scales
- General Purpose Weighing

**Optional Features for SSCSW-20AT:**

- 110 VAC Dry Contact Set Point
- RFL-Radio Frequency Link
- Bar Code Scanner (Pen or Laser)
- WiFi Transmitter Connection
- Ethernet Connection
- WI-CELL®-LT wireless communication from carriage to indicator now available

**Specifications**

Model	CSW-20AT	CSW-20AT-B	SSCSW-20AT	SSCSW-20AT-B
<b>Power</b>	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 2600 mAH* Battery / 120 VAC	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 2600 mAH* Battery / 120 VAC
<b>Battery Operated</b>	NO	YES	NO	YES
<b>NON-NTEP Resolution</b>	20,000 Division			
<b>Legal for Trade</b>	NTEP #06-070A1 Measurement Canada #AM-5778C NTEP Resolution 5000 Division			
<b>Humidity</b>	0-90% Non-condensing			
<b>Dimensions</b>	7" x 5.5" x 3" without Stand, +1 inch with Stand		7" x 6" x 3" without Stand, +1 inch with Stand	
<b>Enclosure</b>	Die Cast Aliminum		304 Stainless Steel Nema 4X	
<b>Display</b>	High Efficient, Bright (Adjustable) LED—6 Digits—0.56" High			
<b>Input</b>	0-15mv			
<b>Temperature</b>	10" to +40" Celsius			
<b>Linearity</b>	0.001% of Full Scale			
<b>Accuracy</b>	0.001% of Full Scale			
<b>Load Cell Supply</b>	5VDC at 150ma (8 each 350 ohm load cells)			

**Battery  
Operating Time**

-

(1) 350 OHM Cell -  
22hrs  
(4) 350 OHM Cell -  
20hrs  
(8) 350 OHM Cell -  
14hrs

-

(1) 350 OHM Cell -  
22hrs  
(4) 350 OHM Cell -  
20hrs  
(8) 350 OHM Cell -  
14hrs

**Ports**

2 x RS-232

**Country of  
Origin**

USA

[Contact US](#)

[718-336-5900](#)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](#) or [\(718\)336-5900](#)
  - Chat with us via [WhatsApp Chat](#)
  - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.

i81u812