

With built-in ramps for entering and exiting the scale, Detecto's 6500 portable bariatric scale is perfect for any wheelchair application.



Manufature: Detecto SKU: 6500 UPC: 809161139204 Dimensions X: 46.00 Y: 38.00 Z: 8.00

Please Call (800)832-0055

Features

With built-in ramps for entering and exiting the scale, Detectos 6500 portable bariatric scale is perfect for any wheelchair application. The integral wheels and handles plus battery power make this scale portable and easy to move from location to location. With the 6500, you may enter the wheelchair weight, so that only the patient weight is displayed. With a high capacity of 800 pounds, this scale is excellent for bariatric needs as well.

The 6500 offers a wide range of versatility and weighing positions: wheelchairs, standing, straight-legged chairs, and walkers.

Specifications

| Model | 6500 | 6500-AC | 6500-C | 6500-C-AC | |
|-------------|--------------------------|------------------|------------------|------------------|--|
| Capacity x | 1000 lb x 0.2 lb | 1000 lb x 0.2 lb | 1000 lb x 0.2 lb | 1000 lb x 0.2 lb | |
| Readability | 450 kg x 0.1 kg | 450 kg x 0.1 kg | 450 kg x 0.1 kg | 450 kg x 0.1 kg | |
| Platform | 32 in x 36 in x 2.2 in | | | | |
| Size | 81 cm x 91 cm x 5.6 cm | | | | |
| Ramp Size | 36 in W x 7.9 in L each | | | | |
| | 91 cm W x 20.2 cm L each | | | | |

| Cable Length | 6 ft / 1.8 m coiled cable, 14 ft / 4.2 m fully extended (from scale to indicator) | | | | | |
|--------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------|----------------------------------------------------------------------------------|------------------------------------------------------------------------------|--|--|
| Power | Optional model 6800-1045 AC adapter or 6 AA batteries (not included | AC adapter (included) or 6 C batteries (not included) | Optional model 6800-1045 AC adapter or 6 AA batteries (not included) | AC adapter (included) or 6 C batteries (not included) | | |
| Indicator | MedVue® Model MV1 | , | | | | |
| Indicator | 9.8 in W x 6.8 in H x 1 | | | | | |
| | 24.9 cm W x 17.2 cm l | | | | | |
| • | 0.9 in / 22 mm high LC | JD, 5 digit, 7 segment | | | | |
| Keypad Buttons | PRINT/ENTER, alpha | | IEI/ GRUSS, IANL, II | | | |
| Connectivity | RS232 serial and USB | RS232 serial and USB | RS232 serial, USB, and WiFi/Bluetooth | RS232 serial, USB, and WiFi/Bluetooth | | |
| Operating Temperature | 14 to 104 °F / -10 to + | 14 to 104 °F / -10 to +40 °C | | | | |
| - | 92 lb / 42 kg | | | | | |
| Shipping Weight | 102 lb / 46 kg | | | | | |
| Guide Handles | 2 included | | | | | |
| Transport Wheels | 2 included | | | | | |
| Country of Origin | USA | | | | | |
| UPC Code | 809161139204 | 809161318203 | 809161325003 | 809161325102 | | |
| Model | 6400 | 6500 | 6600 | BRW1000 | | |
| Capacity x | 1000 lb x 0.2 lb | 1000 lb x 0.2 lb | 1000 lb x 0.2 lb | 1000 lb x 0.2 lb | | |
| | | 450 kg x 0.1 kg | 450 kg x 0.1 kg | 450 kg x 0.1 kg | | |
| Platform | 32 in x 36 in x 2.2 in | v | 32 in x 40 in x 2.2 in | | | |
| Size | 81 cm x 91 cm x 5.6 c | | 81 cm x 101 cm x 5.6 cm | | | |
| Ramp Size | 36 in W x 7.9 in L each 91 cm W x 20.2 cm L each | | 40 in W x 7.9 in L each 101 cm W x 20.2 cm L each | | | |
| Cable Length | 6 ft / 1.8 m coiled cable, 14 ft / 4.2 m fully extended (from scale to indicator) | | | | | |
| Power | Optional model 6800-1045 AC adapter or 6 AA batteries (not included | Optional model MV1PWR AC adapter or 6 C batteries (not included) | Optional model 6800-1045 AC adapter or 6 AA batteries (not included) | Optional model MV1PWR AC adapter or 6 C batteries (not included) | | |
| Indicator | Model 750 | MedVue® Model MV1 | Model 750 | MedVue® Model MV | | |

| Indicator | 6.1 in W x 6.8 in H x 1.8 in D | 9.8 in W x 6.8 in H x 1.8 in D | 6.1 in W x 6.8 in H x 1.8 in D | 9.8 in W x 6.8 in H x 1.8 in D | | |
|-------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|--|--|
| | | 24.9 cm W x 17.2 cm H x 4.6 cm D | 15.5 cm W x 17.2 cm H x 4.6 cm D | 24.9 cm W x 17.2 cm H x 4.6 cm D | | |
| LCD Digits | 0.7 in / 19 mm high LCD, 6 digit, 7 segment | 0.9 in / 22 mm high LCD, 5 digit, 7 segment | 0.7 in / 19 mm high LCD, 6 digit, 7 segment | 0.9 in / 22 mm high LCD, 5 digit, 7 segment | | |
| Keypad Buttons | ON/OFF, ZERO, UNITS, LOCK/RELEASE, BMI/ENTER, PRINT, arrow keys | ON/OFF, ZERO, UNITS, LOCK/RELEASE, NET/ GROSS, TARE, ID/HEIGHT, BMI, PRINT/ENTER, alphanumeric keys | ON/OFF, ZERO, UNITS, LOCK/RELEASE, BMI/ENTER, PRINT, arrow keys | ON/OFF, ZERO, UNITS, LOCK/RELEASE, NET/ GROSS, TARE, ID/HEIGHT, BMI, PRINT/ENTER, alphanumeric keys | | |
| Connectivity | RS232 serial | RS232 serial, USB and optional wired and Wi-Fi Ethernet | RS232 serial | RS232 serial, USB and optional wired and Wi-Fi Ethernet | | |
| Operating Temperature 14 to 104 °F / -10 to +40 °C | | | | | | |
| Net Weight | 92 lb / 42 kg | | 117 lb / 53 kg | | | |
| Shipping Weight | 102 lb / 46 kg | | 127 lb / 58 kg | | | |
| Guide Handles | 2 included | | | | | |
| Transport Wheels | 2 included | | | | | |
| Country of Origin | USA | | | | | |
| UPC Code | 809161302400 | 809161139204 | 809161302509 | 809161139303 | | |
| i81u812 | | | | | | |
| | | | | | | |

