

DETECTO 6550, 6560 and 6570 portable wheelchair scales offer time-saving and patient comfort benefits. The scales features 1,000 lb / 450 kg capacity, optional Wi-Fi for EMR/EHR, vertical foldup storage, two-way built-in ramps for accessibility from both sides, large 32 in x 36 in / 81 cm x 91 cm platform, clinical-grade accuracy to 0.2 lb / 0.1 kg, battery or AC power, and up to 99 tares (optional) to store wheelchair weights for efficient patient weighing



Manufacture: Detecto

SKU: 6570

UPC: 809161302301

Dimensions

X: 46.00 **Y:** 44.00 **Z:**
15.00

Please Call
(800)832-0055

Features

DETECTOs 6550, 6560 and 6570 portable wheelchair scales offer time-saving and patient comfort benefits. The scales features 1,000 lb / 450 kg capacity, optional Wi-Fi for EMR/EHR, vertical foldup storage, two-way built-in ramps for accessibility from both sides, large 32 in x 36 in / 81 cm x 91 cm platform, clinical-grade accuracy to 0.2 lb / 0.1 kg, battery or AC power, and up to 99 tares (optional) to store wheelchair weights for efficient patient weighing. Enjoy the time-saving benefits of these scales by using the convenient pushbutton or keypad tare to remove the wheelchair weight. OIML EC class III models are available

All the scales columns fold down and latch securely for easy transport and vertical foldup storage requiring minimal floor space.

The 6550, 6560 and 6570s MedVue® weight indicator is the clinical industrys most advanced, featuring EMR/EHR-ready serial, USB, and optional Wi-Fi connectivity, BMI calculation, yellow "quick keys" for basic weighing, and a multiline LCD display. The scale is powered by 6 C batteries (not included) or optional AC adapter

The platform is only 2.2 inches/56 mm high for easy patient accessibility and comfort while weighing either standing or in a wheelchair

● Features

- 1000 lb/450 kg Capacity

- 2-Way Easy Access Ramps
- 6 C Batteries (Not Included)
- BMI Calculation
- Easily-Collapsible Column with Quick Release Lever
- EMR/EHR Ready
- Integral Wheels Ease Transport
- Low-Profile 2 inch/56 mm High Platform
- OIML EC Class III Model Available
- Ramps Rest On Floor for Easier Patient Access
- Single-Pass Weighing with Keypad and Pushbutton Tare
- Spacious 32 in x 36 in / 81 cm x 91 cm Platform
- Vertical Fold-up Storage
- Wi-Fi and Ethernet Optional

Specifications

6570 Portable Wheelchair Scale with Seat

Model	6570	6570-AC	6570-C	6570-C-AC
Capacity x Readability	1000 lb x 0.2 lb 450 kg x 0.1 kg	1000 lb x 0.2 lb 450 kg x 0.1 kg	1000 lb x 0.2 lb 450 kg x 0.1 kg	1000 lb x 0.2 lb 450 kg x 0.1 kg
Power	Optional model 6800-1045 AC adapter or 6 AA batteries (not included)	AC adapter(included) or 6 AA batteries (not included)	Optional model 6800-1045 AC adapter or 6 AA batteries (not included)	AC adapter(included) or 6 AA batteries (not included)
Indicator	MedVue® Model MV1			
Indicator	9.8 in W x 6.8 in H x 1.8 in D			
Dimensions	24.9 cm W x 17.2 cm H x 4.6 cm D			
LCD Digits	0.9 in / 22 mm high LCD, 5 digit, 7 segment			
Display	Weight: 5-digit, 7-segment, 7/8 inch (22.2 mm) high LCD Height: 4-digit, 7-segment, 1/2 inch (12.7 mm) high LCD			
Keypad Buttons	ON/OFF, ZERO, UNITS, LOCK/RELEASE, NET/ GROSS, TARE, ID/HEIGHT, BMI, PRINT/ENTER, alphanumeric keys			
Connectivity	RS232 serial and USB	RS232 serial and USB	RS232 serial, USB, and WiFi/Bluetooth	RS232 serial, USB, and WiFi/Bluetooth
Operating Temperature	14 to 104 °F / -10 to +40 °C			
Resolution	5,000 divisions, max.			
Platform Dimensions	32 in x 36 in x 2.2 in / 81 cm x 91 cm x 5.6 cm			
Ramp Size	36 in (91.4 cm) W x 7.9 in (20.2 cm) L each			
Seat	Fold-up Seat Included			
Net Weight	140 lb / 63 kg			
Shipping Weight	150 lb / 68 kg			
Country of Origin	USA			
UPC Code	809161302301	809161317206	809161321302	809161325607

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:(800)832-0055) or [\(718\)336-5900](tel:(718)336-5900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.