Detecto 8500 Portable Stretcher Scale 800 lb x 0.2 lb



DETECTO's Stretcher Scale® is ideal for emergency arrivals into a hospital when time is of the essence for gathering patient weights. The DETECTO model 8500 can be used in the ER, dialysis, long-term care, and nursing homes.



Features

DETECTO's Stretcher Scale® is ideal for emergency arrivals into a hospital when time is of the essence for gathering patient weights. The DETECTO model 8500 can be used in the ER, dialysis, long-term care, and nursing homes. The spacious 60 in W x 32.5 in D/1,524 mm W x 826 mm D platform size accommodates all common stretcher types. DETECTO's Stretcher Scale® is engineered and manufactured at a light enough weight that it is easily portable to lift up and roll by nursing professionals. The model 8500 is 115 lb/52 kg net weight and the slim profile scale design fits easily through doorways of nearly any size. The scale's relatively low net weight, wheels, and guide handles all combine to make it easy to maneuver.

The Stretcher Scale® offers precision weighing for patients in stretchers, gurneys, or wheelchairs. The steel construction provides optimal durability that is built to last. The MedVue® indicator's Hold/Release key can hold the patient's weight after leaving the scale for better patient care. The scale features a 800 lb x 0.2 lb/360 kg x 0.1 kg capacity with clinical-grade accuracy. It is mobile for use in multiple clinical departments.

DETECTO's Stretcher Scale® has a 2-inch-high, low-profile platform with textured mat surface. The two-way-access ramps rest on the floor making it easy to roll patients onto the scale platform. The single-pass weighing feature saves time by allowing you to enter the stretcher or wheelchair tare weight using the numeric keypad on the indicator. You may also use the convenient pushbutton tare feature to remove the stretcher or wheelchair weight if you don't know the weight already. The

model 8500 comes with a wall or desk mount swivel bracket for the MedVue® weight indicator. An optional yellow guide rail kit is available for the 8500/8550 (8500-GUIDERAILS).

Features

- Spacious platform accommodates all common stretcher types
- Available with or without column for weight indicator (model 8500 without column; model 8550 with column)
- High-capacity digital scale for stretchers and wheelchairs
- Two integral wheels and guide handles for mobility
- 800 lb x 0.2 lb / 360 kg x 0.1 kg capacity
- Spacious 60 in W x 32.5 in D / 1,524 mm W x 826 mm D platform size
- Two integrated ramps included for easy access
- Steel construction for optimal durability
- Hold/Release key to hold weight after leaving the scale for better patient care
- Mobile for use in multiple clinical departments

Specifications

| MODEL | 8500 | 8550 | |
|---------------------------|--|--|--|
| Capacity x Readability | 800 lb x 0.2 lb 360 kg x 0.1 kg | 800 lb x 0.2 lb 360 kg x 0.1 kg | |
| LCD Display Dimension | 3.5 in W x 3 in H / 89 mm W x 76 mm H backlit blue LCD | | |
| Display | 5 digit, 7 segment, 7/8 inch (22 mm) high LCD weight digits | | |
| Resolution | 5,000 divisions, max. | | |
| Keypad | 19 key, color-coded, sealed membrane | | |
| Functions | Tare, Net/Gross, Hold/Release, Zero, metric conversion, ID storage, Height entry for Body Mass Index calculation, and printer output | | |
| Power | Optional model MV1PWR AC adapter or 6 C batteries (not included) | | |
| Battery Life | 7,560 weighments (with backlight fully ON) 10,620 weighments (with backlight fully OFF) | | |
| Connectivity | RS232 serial, USB and optional wired and Wi-Fi Ethernet | | |
| Cable Length | 6 ft / 1.8 m coiled cable, 14 ft / 4.2 m fully extended (from scale to indicator) | | |
| Connectivity | RS232 serial, USB and optional wired and Wi-Fi Ethernet | | |
| Mounting Bracket | 350-degree indicator swivel mounting bracket included | | |
| Operating Temperature | 14 to 104 °F / -10 to +40 °C | | |
| Construction Mild steel | | | |
| Included | Two ramps (assembly required) | | |
| Overall Dimensions | 76 in W x 38 in D x 2 in H 1,930 mm W x 965 mm D x 51 mm H | 76 in W x 38 in D x 44.8 in H 1,930 mm W x 965 mm D x 1,138 mm H | |
| MedVue Indicator | 9.8 in W x 8.3 in D x 7.8 in H 249 mm W x 211 in D x 198 mm H (including swivel mounting bracket) | | |

| Platform | 60 in W x 32.5 in D x 2 in H | |
|--------------------------------------|---|-----------------------------------|
| Dimensions | 1,524 mm W x 826 mm D x 51 mm H | |
| Ramp Dimensions | 7.5 in W x 32.5 in D x 2 in H 191 mm W x 826 mm D x 51 mm H | |
| Optional Guide Rail Dimensions | 24 in W x .1 in D x 3.3 in H 610 mm W x 3 mm D x 83 mm H (2 short rails per scale) and 27 in W x .1 in D x 3.3 in H 686 mm W x 3 mm D x 83 mm H (2 long rails per scale) | |
| Net Weight | 115 lb / 52 kg (including indicator and mounting bracket) | 130 lb / 59 kg |
| Country of Origin | USA | |
| Shipping Weight | 200 lb / 91 kg (including pallet) | 215 lb / 98 kg (including pallet) |
| UPC | 809161305005 | 809161305104 |
| Ontionat | | |

- Options:
- 8500-GUIDERAILS: Guide rail kit painted yellow for models, 8500/8550 (includes wheel side and handle side)
- MV1PWR: Medical-grade AC adapter power supply with US plug
- MVWIFI: Wireless option card
- MVIP: Wired Ethernet interface option

i81u812

