

Detecto EB-300-185B Rival Stainless Steel Legal for Trade Bench Scale 300 x 0.1 lb

Cardinal Scale's EB bench scales with 185 Rival weight indicators feature rechargeable battery power allowing them to be moved easily to multiple locations, bold 1-inch/25-mm high backlit LCD for high-visibility readouts, 3 platform sizes and 5 capacities available. Detecto EB-300-185B Rival Stainless Steel Legal for Trade Bench Scale 300 x 0.1 lb





Capacity x Readability

Non Legal Mode:300 lb x

0.1 lb

Legal For Trade: 300 lb x

0.1 lb Pan Size

24 x 20 in

Manufature: Detecto

SKU: **EB-300-185B** UPC: 809161328004

Dimensions

X: 29.00 Y: 29.00 Z:

12.00



Please Call (800)832-0055

Features

Cardinal Scale's EB bench scales with 185 Rival weight indicators feature rechargeable battery power allowing them to be moved easily to multiple locations, bold 1-inch/25-mm high backlit LCD for high-visibility readouts, 3 platform sizes and 5 capacities available. Capacities range from 15 lb/6 kg up to 300 lb/150 kg and the EB series is NTEP, OIML, and Measurement Canada legal for trade. Cardinal Scale's EB bench scales feature the strength and durability of a beautiful stainless steel scale base and column combined with the elegant and comfortable tactile feel of the ABS washdown 185B Rival weight indicator.

The backlit green LCD is visible in nearly any lighting level, indoors or outdoors. The bench scale's indicator mounted to the column tilts for letting you position it with the most convenient viewing

angle. The scale features a durable sturdy base for solid support, lift-off stainless steel platform, bi-directional RS232 port for printing or connection to a PC, pushbutton tare, auto shutoff, piece counting mode, and simple seven-button operation. They are ideal for farmers markets, processing, warehousing, recycling, distribution centers, and general purpose weighing.

Since the scale can be powered by 6 AA rechargeable batteries, it's completely portable for moving around to multiple locations in your facility. The battery level indicator lets you see how much battery life is left before recharging is needed. The indicator anti-slip mounting bracket includes rotational lock-in set points adjustable in discrete 15° increments for exact positioning of the display right where you want it.

- 3 Platform Sizes and 5 Capacities Available
- Rechargeable Battery Power
- Bold 1-inch/25-mm High Backlit LCD
- Capacities Ranging From 15 lb/ 6 kg up to 300 lb/150 kg
- Stainless Steel Construction
- Durable Sturdy Base for Solid Support
- Platform Sizes Available from 10 in W x 12 in D / 25 cm W x 30 cm D up to 24 in W x 20 in D / 61 cm W x 51 cm D
- Column-Mounted 185B Rival Weight Indicator
- Lift-Off Stainless Steel Platform
- Powered by 6 AA Batteries (not included) or AC Power
- Built-in, Bi-Directional RS232 Port for Printing or Connection to a PC
- Pushbutton Tare
- Stainless Steel Load Cell
- Pounds/Kilograms Conversion
- Gross, Tare, Net
- Auto Shutoff
- NTEP, Measurement Canada, and OIML approved
- Country of Origin: USA

These legal-for-trade Cardinal Scale EB bench scales feature a high-quality 304 stainless steel platform, sturdy solid base, and 185B Rival digital weight indicator mounted to the column. The lift-off platform cover simplifies clean-up in messy environments. The EB series is available in 15, 30, 60, 150 and 300 lb capacities in a variety of platform sizes (listed on the back page).

The bench scale's indicator mounted to the column tilts for letting you position it with the most convenient viewing angle. The scales feature an easy-toread bold 1-inch/25-mm high backlit LCD, Gross / Tare / Net conversion, adjustable filtering, selectable weight units, and auto shutoff. They are powered by either six "AA" Alkaline, Ni-Cad or NiMH batteries (not included) or the included 100 to 240 VAC 50/60Hz 12 VDC 1 A wall plug-in UL/CSA listed AC power adapter (Cardinal part number 8400-0182-0A).

Ideal for Farmers Markets, Processing, Warehousing, Recycling, Distribution Centers, and General Purpose Weighing

High visibility display for warehouses, commercial foodservice, manufacturing, and general weighing applications

- Push-button Tare
- Battery level indicator
- Gross, Tare, Net display
- StableSENSE® adjustable filtering
- 1 serial port
- Auto Shutoff and Sleep modes
- SMA level 2 compliant serial communications
- Piece counting mode
- Pounds and Kilograms weighing units

Cardinal Scale's EB bench scales feature the strength and durability of a beautiful stainless steel scale base and column combined with the elegant and comfortable tactile feel of the ABS washdown 185B Rival weight indicator. The backlit green LCD is visible in nearly any lighting level, indoors or outdoors.

Since the scale can be powered by 6 AA rechargeable batteries, it's completely portable for moving around to multiple locations in your facility. The battery level indicator lets you see how much battery life is left before recharging is needed.

ROTATIONAL DISPLAY POSITIONING The indicator anti-slip mounting bracket includes rotational lockin set points adjustable in discrete 15° increments for exact positioning of the display right where you want it.

Specifications

MODEL	EB-15-185B	EB-30-185B	EB-60-185B	EB-150-185B	EB-300-185B
Capacity x Readability Legal For Trade	15 lb x 0.005 lb	30 lb x 0.01 lb 15 kg x 0.005	60 lb x 0.02 lb 30 kg x 0.01	150 lb x 0.05 lb	300 lb x 0.1 lb 150 kg x 0.05
	6 kg x 0.002 kg	kg	kg	60 kg x 0.02 kg	kg
	NTEP Class III CC 03-031A Measurement Canada Indicator: AM-5526				
	OIML DK 0199.387 Rev. 3				
PLATFORM SIZE	10 in W x 12	=	14 in W x 16	14 in W x 16	24 in W x 20
	in D 25 cm W x 30	in D 25 cm W x 30	in D 36 cm W x 41	in D 36 cm W x 41	in D 61 cm W v 51
	cm D	cm D	cm D	cm D	cm D
Construction	Stainless steel scale base, column, and mounting bracket with ABS weight indicator enclosure				
Power Requirements	Six "AA" Alkaline, Ni-Cad or NiMH batteries (not included) OR 100 to 240				
	VAC 50/60Hz 12 VDC 1 A wall plug-in UL/CSA listed AC power adapter				
Dattom, Life	(Cardinal part number 8400-0182-0A)				
Battery Life Weight Display	70-hour typical operation with full charge Six-digit, seven-segment, 1.0 in (25 mm) high, backlit green LCD				
Compensated					
Temperature Range	14 to 104 °F (-10 to 40 °C)				
Operating Temperature Range	-10 to 122 °F (-23 to 50 °C)				
Humidity	90% non-condensing maximum				
Tare Capacity	Scale capacity				
Sample Rate	10 samples per second				
Auto Zero Range	0.5 or 1 through 9 divisions				
Keypad	7-key Membrane type Keys: ON/OFF, ZERO, TARE, NET/GROSS, UNITS, FN, PRINT				
Standard I/O	1 bi-directional RS-232 port				
Country of Origin	USA				

OVERALL DIMENSIONS

10 in W x 16 10 in W x 16 14 in W x 16.8 14 in W x 16.8 24 in W x 20.8 in D x 19.3 in in D x 19.3 in in D x 25.2 in in D x 25.2 in in D x 25.5 in Η Η Η Н Н 25 cm W x 41 25 cm W x 41 36 cm W x 43 36 cm W x 43 61 cm W x 53 cm D x 49 cm cm D x 49 cm cm D x 64 cm cm D x 64 cm cm D x 65 cm Н Η Η Н Н

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

Phone: <u>(800)832-0055</u> or <u>(718)336-5900</u> Chat with us via WhatsApp Chat

Address: 4802 Glenwood Rd. Brooklyn, NY 11234

© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.