

The smooth lines of the molded poly enclosure, lift-off stainless steel commodity tray, and sealed membrane keypad make cleaning the PS-7 easy. The commodity tray utilizes welded studs on the bottom of the tray that fit tightly into the weighbridge of the scale. The main board on each unit has a moisture resistant coating, adding additional protection from the elements of everyday use in the food industry.



Manufacture: Detecto

SKU: PS-7

UPC: 809161146004

Dimensions

X: 12.00 Y: 10.00 Z:
4.00

Weight: 4.00 lb

**Please Call
(800)832-0055**

Features

The smooth lines of the molded poly enclosure, lift-off stainless steel commodity tray, and sealed membrane keypad make cleaning the PS-7 easy. The commodity tray utilizes welded studs on the bottom of the tray that fit tightly into the weighbridge of the scale. The main board on each unit has a moisture resistant coating, adding additional protection from the elements of everyday use in the food industry. Comes with retail packaging in both English and Spanish. The PS-7 can be operated on AC or battery power and features a built-in rechargeable battery.

Features

- Easy-To-Read LCD Display
- Power-Saving "Auto-off" Feature
- IP52 Water Resistant Enclosure
- Switch Selectable Units
- NSF Certified
- Disable Different Units of Measure
- Easy-To-Clean, Removable Stainless Steel Tray
- Battery or AC Power

Specifications

Capacity:(can disable different units of measure)

- 7 lb x 0.1 oz
- 112 oz x 0.1 oz
- 112 oz x 1/8 oz
- 3000 g x 1 g
- 7 lb x 0.005 lb
- Display: 5-digit, 0.8" x 0.3" characters with fractions LCD digital display
- Dimensions: 8.03" W x 7.87" D x 2.44" H / 204mm W x 200mm D x 62mm H
- Platform Size: 8.02" W x 4.96" D /204mm W x 126mm D
- Construction: Molded poly enclosure with stainless steel commodity tray
- Tare: 100% of full scale capacity
- Keys: ON/OFF, ZERO, UNITS
- Zero: Established on power up routine and maintained by auto-zero circuitry
- Temperature: 40° to 105° F (5° to 40° C)
- Humidity: 25% ~95% RH
- Power: Built-in rechargeable battery pack included (7.2 VDC/1200mA) or 115 VAC 50/60 Hz or 230 VAC 50/60 Hz powering a 15 VDC 300mA wall plug-in UL/CSA listed power supply.
 - Features:
 - Power-saving selectable timing auto shut-off which only goes to sleep when using battery operation.
 - Low battery indicator.

The PS-7 Is Ideal For:

- Restaurants
- Cafeterias
- Deli's
- Pizza Parlors
- Food Service Professionals (industrial)

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
 - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.