

Large LCD display. High Resolution 1/6000 NTEP approved class III. AC (included) or rechargeable battery -- battery with over 100 hours of continuous use! Comparator for Hi-Lo check weighing, customizable hold feature. 7 modes



Easy Weigh®

Manufacture: Easy Weigh
SKU: **BX-300**

Please Call
(800)832-0055

Features

- NTEP Legal for Trade
- Large LCD display with 6 digit weighing
- Free Wet Cover included
- Large platform size: 16.5 x 20.5 inches (420 x 520 mm)
- High Resolution: 1/6000 NTEP approved class III
- Standard AC cord - no clumsy adaptor
- Built in rechargeable battery with over 100 hours of continuous use
- 7 weighing units: lbs, oz, kg, g, pcs, % and lb/oz
- Comparator feature for Hi-Lo Check Weighing
- Customizable Hold feature for high-motion weighing
- Large stainless steel removable platter
- Ultra quick response weight display
- Tough, high-quality UV-sealed keypad
- Large size heavy-duty cast aluminum platform
- Tilt and swivel display indicator head
- User-friendly PLU programming
- Quick operation keypad for high throughput
- Function Keys: G/N/T, Unit, Mode, Tare and Zero
- Internal power supply with long AC power cord

Specifications

- **Model:** BX-300R
- **Capacity / Graduation:** 300 x 0.05 lb
4800 x 1 oz
120 x 0.02 kg
- **Maximum Tare:** Can tare up to Maximum Capacity
- **NTEP Certificate Number:** Approved 1/6000 resolution, Legal for Trade
- **A/D Conversion Rate:** 50 updates/second
- **Connectivity:** RS232 port for connection to ECR, PC or serial printer
- **LCD:** 6 digits, 999,999 max
- **Platter Size:** 16.5 W x 20.5 L inches (420 x 520 mm)
- **Accreditation:** NTEP Class III, OIML, CE, ISO 9002, UL
- **Dimensions:** 16.5 W x 20.5 L x 37.0 H inches (420 x 520 x 940 mm)
- **AC - Internal Power Supply (AC cord):** 120 VAC, 60 Hz, AC power cord
- **AC - External Adapter:** 120 VAC, 60 Hz to 9VDC @ 800mA
- **Battery:** 100 hours with back light off or 48 hours with back light on (continuous use)
- **Power Consumption and Fuse Rating:** Approximately 10 watts
Fuse: 250 V, 1.5 Amp, 20 mm

Specifications

Specifications

Model	BX-120	BX-300	BX-600
Capacity / Graduation	120 x 0.02 lb 2000 x 0.5 oz 60 x 001 kg	300 x 0.05 lb 4800 x 1 oz 120 x 0.02 kg	600 x 0.1 lb 9600 x 2 oz 300 x 0.5 kg
Maximum Tare	Can tare up to Maximum Capacity		
NTEP Certificate Number	Approved 1/6000 resolution, Legal for Trade		
A/D Conversion Rate	50 updates/second		
LCD	Weight: 6 digits, 999,999 max		
Platter Size	16.5 W x 20.5 L inches (420 x 520 mm)		
Accreditation	NTEP Class III, OIML, CE, ISO 9002, UL		
Dimensions	16.5 W x 20.5 L x 37.0 H inches (420 x 520 x 940 mm)		
AC - Internal Power Supply (AC cord)	120 VAC, 60 Hz, AC power cord		
AC - External Adapter	120 VAC, 60 Hz to 9VDC @ 800mA		
Battery	100 hours with back light off or 48 hours with back light on (continuous use)		
Power Consumption and Fuse Rating	Approximately 10 watts Fuse: 250 V, 1.5 Amp, 20 mm		

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.