



Fairbanks 31784 Omega Counting Scale, 6 x 0.0005 lb

The Omega Counting Scale is a competitively priced, easy-to-use counting scale with many user-defined features. This scale is designed for a full-range of weighing applications: weighing, counting, checkweighing, checkcounting and kitting.



Capacity x Readability

6 lb x 0.0005 lb

Pan Size

13.9 x 9.6 in

Manufacture: Fairbanks

SKU: 31784

Weight: 6.00 lb

**Please Call
(800)832-0055**

Features

The Omega Counting Scale is a competitively priced, easy-to-use counting scale with many user-defined features. This scale is designed for a full-range of weighing applications: weighing, counting, checkweighing, checkcounting and kitting. There are several different sampling methods, each designed with a different cycle-of-operation in mind. This scale reduces material handling times while meeting the stringent requirements of today's lean manufacturing and inventory processes. This invaluable tool increases productivity and minimizes losses.

FEATURES

- Internal resolution of 1,000,000 counts
- Displayed resolution 30,000d
- Auto -resampling
- Four sampling methods
- Simultaneous weight display- weight, pieces, piece weight
- Net/Gross weight display
- Two RS232 outputs
- AC and/or lead acid rechargeable battery
- Auto sleep timer
- 99 parts look up (PLU)
- Remote scale interface (standard)
- Hi/Lo weighing and parts counting
- Audible beep operation
- 36 button keypad
- Accumulation- weight and piece count
- Bar code reader (tare, PLU and piece weight) sold separately
- User-selectable printing (bar code printing optional)

- Time and date

APPLICATIONS

Weighing, counting, checkweighing, checkcounting or kitting, the Omega Counting Scale is a cost-effective, high-performance scale designed for a full-range of weighing applications. The Omegas large, stainless steel platform can easily accommodate product bins. This scale is ideal for quarterly/semiannual inventories and parts counting applications.

ACCESSORIES

- Bar Code Reader
- GC 420d Printer
- Protective Scale Cover

Specifications

Model	31784	31785	31786	31787	31788
Capacity x Readability	6 x 0.0005 lb 3 kg x 0.2 g	15 x 0.0005 lb 6 kg x 0.2 g	30 x 0.001 lb 15 kg x 0.5 g	60 x 0.002 lb 30 kg x 1 g	100 x 0.002 lb 50 kg x 1 g
Platform Size	13.9 x 9.6 inch				
Displayed resolution	0,000d (100 lb = 50,000d)				
Units	Pounds and kilograms				
Display Type	Backlit LCD				
Display Character Height	0.57" tall				
Display Lines (3)	Weight - 6 characters; pieces - 7characters; Pieces - 7characters				
Internal resolution	1,000,000				
Operating Template	32 F to 104 F				
Relative Humidity					
Memory (PLU)	999 items				
Remote Scale Interface	Four 350 ohm load cells, 2 mV/V max				
Interface	Serial 1 R S232 for printer, computer or remote display; Serial2 R S232 for barcode reader only.				
Power	A/C adapter Input- 120 VAC 60 Hz 0.15A Output - 9 VAC 500 mA				
Battery	Built-in rechargeable, 6V lead acid				
Battery Life	15 to 20 hours continuous (local platform only)				
Battery recharge time	14 to 16 hours				
Approval	UL				

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

• Phone: [\(800\)832-0055](tel:(800)832-0055) or [\(718\)336-5900](tel:(718)336-5900)

• Chat with us via [WhatsApp Chat](#)

• Address: 4802 Glenwood Rd. Brooklyn, NY 11234

• © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.