

Intercomp's CS3000 utilizes a high visibility 1" / 25mm (optional 2" / 50mm) LCD display and infrared remote control. Capacities range from 500 lb / 250 kg to 600,000 lb / 300,000 kg. Crosby S-1 swivel hook for dynamic loads.



Capacity x Readability
 30000 lb x 10 lb

Manufature: Intercomp
SKU: 100685

Please Call (800)832-0055

Features

Intercomp offers the industry's most extensive line of crane scales, and can provide your company with a cost-effective solution to virtually every overhead industrial weighing application - ranging from 25 to 600,000 lbs/ 12.5 to 300,000 kg.

Our advanced design, value-packed with the industry's most desired features, makes Intercomp the first choice over other electronic units. Ultra high-resolution, A/D conversion delivers unsurpassed accuracy, and digital keypad setup and calibration enhance the ease of operation.

All crane unit electronics are shock-mounted in a weatherproof case and provide maximum protection against moisture, dust and rough usage. Features include a high-visibility digital readout for easy reading of weights and large pushbutton switches for simple, trouble-free operation.

Low-cost, high performance digital crane scale for medium capacity industrial applications. The unique design flexibility lets you choose the model and weighing capacity you need - NTEP certified from 300 to 20,000 lb/150 to 10,000 kg. The unit utilizes a high-visibility 0.8 inch/20 mm LED digital readout and the efficient micro-controller delivers up to 100 hours of operation on eight (8) D-cell batteries. Crosby eye hook and bottom swivel hook.

CS1500 Hanging Scales									
Model	100680	100681	100682	100683	100684	100685	100686	100687	100688
Capacity	500 x 0.2 lb	2000 x 1 lb	5000 x 1 lb	10,000 x 2 lb	20,000 x 5 lb	30,000 x 10 lb	50,000 x 10 lb	70,000 x 20 lb	100,000 x 20 lb

Graduation	250 x 0.1 kg	1000 x 0.5 kg	2500 x 0.5 kg	5,000 x 1 kg	10,000 x 2 kg	15,000 x 5 kg	25,000 x 5 kg	35,000 x 10 kg	45,000 x 10 kg
Weight	50 lb/23 kg	52 lb/24 kg	60 lb/27 kg	60 lb/27 kg	100 lb/45.5 kg	125 lb/57 kg	225 lb/102 kg	253 lb/115 kg	397 lb/180 kg
General	Zero, lb./kg, Tare Set/Display, Tare Clear, On, Off								
Display	5-digit, 1 inch liquid crystal display (LCD)								
Indicator	lb/ kg and Net								
Battery Life	Up to 400 hours continuous use								
Batteries	Eight (8) "D"-size disposable alkaline dry cells or rechargeable nicad cells.(Not included)								
Resolution	220-bit A/D converter delivers over 1,000,000 internal counts								
Auto-Zero	Satisfies all NIST/OIML requirements								
Zero	Up to 100% excluding NIST/OIML units								
Tare	Up to 100% of capacity								
Humidity	10 to 95% non-condensing								
Temperature	Operating -4 to +140°F/- 20 to +60°C								
Filtering	6-pole, 10 hertz low pass								
Speed	3 Seconds to typical reading								
Accuracy	+/- 0.1% of reading								
Maximum Overload	500% of capacity								
Enclosure	NEMA IV cast aluminum case								
Hook or Eye	Crosby-Laughlin or equivalent								
Custom Options	From 500-100000 lb /metric equivalent Substitute Bottom Shackle for Swivel Hook(Custom Order Only) Oversized top lifting eye on 500-10,000 lb/metric equivalent(Custom Order Only) Oversized top shackle on 20,000-100,000 lb/metric equivalent (Custom Order Only) Anti heat shield - Oversized hook and custom swivel - Foundry Package (Custom Order) Headroom Loss Adapter Adapter - replaces top eye or shackle(Customer Order Only)								

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.