



Intercomp TL6000 150005- Tension Link Scale without indicator, 25000 x 20 lb

The TL6000 is the industry standard bearer, delivering unsurpassed accuracy from 500 lbs to 300 tons in a lightweight, compact design.



Capacity x Readability
25000 lb x 20 lb

Manufacture: Intercomp
SKU: 150005
Weight: 26.00 lb

Please Call (800)832-0055

Features

Intercomp offers the industry's most extensive line of crane scales, and can provide your company with a cost-effective solution to virtually every overhead industrial weighing application - ranging from 25 to 600,000 lbs/ 12.5 to 300,000 kg.

A cost-effective solution for virtually any industrial application. Cranes, riggers, shipyards, construction sites, surveyors, inspectors and utilities demand cost-effective yet technologically advanced solutions for processing, monitoring and controlling overhead loads. The TL6000 is the industry standard bearer, delivering unsurpassed accuracy from 500 lbs to 300 tons in a lightweight, compact design.

The electronics are shock-mounted in a NEMA 4X/IP65 weatherproof aluminum or stainless steel enclosure for protection against moisture, dust and rough usage. Weights are easily viewed with the industry's largest digital LCD readout (1.2 inches / 30mm). The easy to use membrane switches provide simple, trouble-free operation.

Features include peak hold, set points for relay control and keypad setup/calibration. Operates on two (2) 9-volt alkaline batteries for up to 800 or more hours due to the high efficiency micro-controller. Hand-held remote control and wireless models are available.

Model	15000	150001	150002	150003	150004	150005	150006	150007	150008	150009	150010	150011	150012
Capacity	500 x 0.5 lb	1000 x 1 lb	2,000 x 2 lb	5,000 x 5 lb	10,000 x 10 lb	25,000 x 20 lb	50,000 x 50 lb	100,000 x 100 lb	160,000 x 200 lb	220,000 x 200 lb	350,000 x 500 lb	400,000 x 500 lb	500,000 x 500 lb
Graduation	250 x 0.2 kg	500 x 0.5 kg	1000 x 1 kg	2500 x 2 kg	5000 x 5 kg	12,500 x 10 kg	25,000 x 20 kg	50,000 x 50 kg	80,000 x 100 kg	110,000 x 100 kg	175,000 x 200 kg	200,000 x 200 kg	250,000 x 200 kg
Price	\$1125	\$1125	\$1125	\$1260	\$1463	\$1818	\$2012	\$3474	\$6746	\$8096	\$9896	\$11696	\$14396
Without Indicator	\$1125	\$1125	\$1125	\$1260	\$1463	\$1818	\$2012	\$3474	\$6746	\$8096	\$9896	\$11696	\$14396
With 900mhz Wireless	\$1575	\$1575	\$1575	\$1710	\$1913	\$2268	\$2462	\$3924	\$7196	\$8546	\$10346	\$12146	\$14846
With 868mhz Wireless	\$1575	\$1575	\$1575	\$1710	\$1913	\$2268	\$2462	\$3924	\$7196	\$8546	\$10346	\$12146	\$14846
Construction	Aluminum or Stainless Steel												
Accuracy	+/- 0.1% of applied load or +/-1 graduation; whichever is greater												
Display	Five digit, 1.2 inch/30 mm high LCD												
Control Keys	On/Off, Zero (100%), Tare (100%), Peak Hold and Mode												
Annunciators	Low Battery, Peak Hold, Set Points 1 & 2, lb, kg, tons, metric tons and dekaNewtons												
Power	Two (9V) batteries												
Operating Time	Up to 800 hours of continuous use. Wireless remote control models have reduced operating time.												
Operating Temperature:	-4 to 140° F/-20 to 60° C												
Enclosure:	Nema 4X/IP 65												
Overload	200% safe, 500% ultimate												
Calibration	Digital Keypad, Multi-Point												
Output	RS-232 and RS-485												

i81u812

- Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.