

The OS-2130D is a compact direct thermal desktop barcode printer that offers outstanding features and exceptional value. This easy-to-operate printer is ideal for low- to medium-volume printing needs. The OS-2130D is ideal for applications such as point-of-sale, weight scales, mailing, banking, ticketing, patient tracking, kiosks, and document labeling.

**T-Scale**

**Manufacture:** T-Scale  
**SKU:** OS-2130D  
Free Ground Shipping  
within the 48 continental  
US States

**Please Call**  
**(800)832-0055**

## Features

The OS-2130D is a compact direct thermal desktop barcode printer that offers outstanding features and exceptional value. This easy-to-operate printer is ideal for low- to medium-volume printing needs. The OS-2130D is ideal for applications such as point-of-sale, weight scales, mailing, banking, ticketing, patient tracking, kiosks, and document labeling. Key features of the OS-2130D include a USB port, an internal real time clock (RTC) and a buzzer. The USB allows easy connectivity with computers and other devices. The internal RTC facilitates time and date marking for standalone operation. The buzzer provides built-in error warning by beeping when media runs out or paper jams occur. With its easy operation, reliability, and space-saving size, the OS-2130D offers a high performance, cost-effective solution for your barcode and labeling requirements.

- Printing Method Direct Thermal
- Printing Resolution 203 dpi(8 dots/mm)
- Printing Speed Max. 4 ips
- Printing Length Max.100"(2540mm)
- Printing Width Max. 2.83"(71.88mm)
- Memory 8MB DRAM, 4MB Flash ROM
- CPU Type 32 bit RISC microprocessor
- Operation Interface LED Indicator x 2, Button(Feed) x 1
- Communication Interface USB device, RS-232, RJ-11
- Fonts Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" H(1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0 ~ 270 rotation Soft fonts and

- 2-byte Asian fonts are downloadable Ability to print any Windows True Type Font easily
- 1D Barcodes PPLA: Code 39, UPC-A, UPC-E, Code 128 subset A/B/C, EAN-13, EAN-8, HBIC, Codabar, Plessey, UPC2, UPC5, Code 93, Postnet, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128 Random, Weight, Telepen, FIM, Interleave 2 of 5 (Standard/with modulo 10 checksum/with human readable check digit/with modulo 10 checksum & shipping bearer bars), GS1 Data bar (RSS)
- PPLB: Code 39 Std. & Extended, UPC-A, UPC-E, UPC-Interleaved 2 of 5, Code 39 with check sum digit, Code 93, EAN-13, EAN-8 (Standard, 2 /5digit add-on), Codabar, Postnet, Code128 subset A/B/C, Code 128 UCC (shipping container code), Code 128 auto, UCC/EAN code 128 (GS1-128), Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, German Postcode, Matrix 2 of 5, UPC Interleaved 2 of 5, EAN-13 2/5 digit add-on, UPCA 2/5 digit add-on, UPCE 2/5 digit add-on, GS1 Data bar (RSS) 2D Barcodes PPLA/PPLB: MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, Composite codes
- Graphics PPLA/PPLB: PCX, BMP, IMG, HEX, GDI, Binary raster (PPLB Only) Emulation PPLA, PPLB
- Software-label Editing BarTender® from Seaguall Scientific Argobar Pro support ODBC Database Connection: Excel, CSV, MS Access, MS SQL, Oracle MySQL, dBASE (\*.dbf)
- Software-utility Printer Utility, Font Utility
- Driver tools Argox Seaguall Driver (Windows XP/Vista/Win7/Win8/Win10)
- Media Type Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper
- Media Max.width 3.14"(79.8mm) Min width 1" (25.4 mm) Max.length 100" (2540mm) Min length:0.196" (5mm) Thickness 0.0025"~0.01" (0.0635mm ~0.254mm) Max roll capacity core 0.5" / OD 4.3"(109 mm), or core 1" / OD 4" (102 mm) Core size 0.5"(12.7mm) and 1"(25.4mm) ID
- Printer Dimensions W 134mm x H 163mm x D 228mm
- Printer Weight 1.2 kgs
- Power Source Universal Switching Power supply. AC input voltage: 100~240V, 50~60Hz. DC Output: 24V, 2.5A
- Operation Environment Operation Temperature: 40°F~100°F (4°C~38°C), 0% ~ 90% non-condensing
- Storage Temperature: -4°F~122°F (-20°C~50°C)
- Real Time Clock Standard

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2021 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.