

The original signature Challenger packaging has been upgraded to NEMA 4 / IP65 levels. Manufactured in the USA in strict compliance with the highest Safety Standards, Challenger continues to sustain minimum 200% safe and 500% ultimate load ratings.



Capacity x Readability

Non Legal Mode: 5000 lb x 2
lb

Legal For Trade: 5000 lb x 2
lb

Manufacture: MSI

SKU: 139104

Dimensions

X: 28.70 Y: 9.00 Z: 14.00



Legal for Trade

**Please Call
(800)832-0055**

Features

Industry's standard crane scale for light to medium capacity applications The MSI-3460 "ScaleCore" measurement module features the industry leading weighing functions of previous Challenger designs plus much more. Long range viewing is enhanced with an ultra-bright LED digital display with 1.5 inch (38 mm) high digits with resolution settings of up to 10,000 divisions and precision 0.1% loading accuracy across an available capacity range of 250 to 15,000 lbs. Product operating time is extended to over 50 plus hours with a single 6-volt rechargeable battery.

The original signature Challenger packaging has been upgraded to NEMA 4 / IP65 levels. Manufactured in the USA in strict compliance with the highest Safety Standards, Challenger continues to sustain minimum 200% safe and 500% ultimate load ratings.

Available options include: RF remote control, MSI-8000 RF remote display and audible alarm. An electronics retrofit kit is available for customers who wish to upgrade their existing MSI-3260 or MSI-3360 Challengers to the new generation MSI-3460.

The MSI-3460 Crane Scale provides cost-effective light to medium capacity overhead weighing. For higher capacities, heavy duty, outdoor and continuous production use, MSI recommends MSI-4260, MSI-4300, MSI-6260CS or MSI-9300. Note: 15,000 lb (7,500 kg) unit comes standard with 12 ton top shackle.

Units	Pounds or Kilograms selectable
Resolution	2000-3750 divisions standard (Up to 10,000 d available)
Power	6 Volt Rechargeable Battery (115/230 VAC Rapid Charge Battery Charger included)
Operating Time	Up to 50 hours depending on programmed operating mode
Auto-Off Mode	Select for 15, 30, 45, 60 minutes or Off
Auto Sleep Mode	Power down during non-use and power up with weight change or any key press
Service Counter	Maintains two counters. The first counts number of lifts for inspection reminders and the second counts overloads for safety warnings
Operating Temperature Range	-4° to +122°F (-20° to +50°C)
Enclosure	NEMA 4/IP65, powder coated alodined cast aluminum corrosion resistant
Hook	Crosby 360° non-bearing swivel
Safe Overload	200% of rated capacity
Ultimate Overload	500% of rated capacity

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.