

After three decades of production, added advancements, and thousands of worldwide installations, the next generation Port-A-Weigh embedded with ScaleCore technology continues to reign as the industry standard. Along with Port-A-Weigh, the MSI product offering features the most comprehensive line of industrial crane scales. Now the MSI-4260 IS is intrinsically Safe



Capacity x Readability

Non Legal Mode: 2000 lb x 1 lb

Legal For Trade: 2000 lb x 1 lb

Manufacture: MSI

SKU: 156014

Dimensions

X: 28.70 Y: 9.00 Z: 14.00



Legal for Trade

**Please Call
(800)832-0055**

Features

The Industry Standard for Overhead Weighing After three decades of production, added advancements, and thousands of worldwide installations, the next generation Port-A-Weigh embedded with ScaleCore technology continues to reign as the industry standard. Along with Port-A-Weigh, the MSI product offering features the most comprehensive line of industrial crane scales and specialized overhead weighing solutions. For medium- to heavy-capacity and duty-cycle needs, the MSI-4260 meets or exceeds all industrial safety requirements, including OSHA, ANSI and ASME and is an economical choice for many bridge crane, foundry, and in-process material handling needs.

• Standard Features

- Crane unit with five-digit, 1.2 in (30 mm) LED display
- Top lifting eye or shackle, bottom thrust bearing swivel hook
- 12 volt rechargeable battery and universal 115/230 VAC, 50/60 Hz battery charger (NA plug)

- NTEP Certified configuration

Model	156013	156014	156015	156016	156017	156018	159019	156020	156021
Capacity x Readability	500 x 0.2 lb	2000 x 1.0 lb	5000 x 1.0 lb	10,000 x 2.0 lb	20,000 x 5.0 lb	30,000 x 10 lb	50,000 x 10 lb	70,000 x 20 lb	100,000 x 20 lb
	250 x 0.1 kg	1000 x 0.5 kg	2500 x 0.5 kg	5000 x 1.0 kg	10,000 x 2.0 kg	15,000 x 5.0 kg	25,000 x 5.0 kg	35,000 x 10 kg	50,000 x 10 kg
	NTEP CC 89-090		NTEP CC 89-090A1						-
Accuracy	± 0.1% of applied load ±1d								
Resolution	3,000 to 5,000 d standard (up to 10,000 d available)								
Enclosure	NEMA Type 4, IP66 marine grade 356 alloy anodized cast aluminum								
Legal for Trade	US Listings: FM16US0156X								
	IS / I, II, III / 1 / CDEFG / T4 Ta = -20°C to 50°C								
	I / 0 / AEx ia / IIB / T4 Ta = -20°C to 50°C Ga								
	20 / AEx ia / IIIC / T135°C Ta = -20°C to 50°C Da								
	Canadian Listings: FM16CA0092X								
	IS / I / 1 / CD / T4 Ta = -10°C to 50°C								
	IS / II, III / 1 / EFG / T4 Ta = -10°C to 50°C								
	I / 0 / Ex ia / IIB / T4 Ta = -10°C to 50°C Ga								
	20 / Ex ia / IIIC / T135°C Ta = -10°C to 50°C Da								
Intrinsic Safety									
	ATEX Listings: FM16ATEX0038X								
	II 1 G Ex ia IIB T4 Ga -10°C . Ta . 50°C								
Lifting Eye, Shackle & Hook	II 1 D Ex ia IIIC T135°C Da -10°C . Ta . 50°C								
	Crosby® or equal with 360° thrust-bearing swivel hook								
Design Overload	200% Safe / 500% Ultimate (except as noted)								
Functions	Power: Turns Unit ON or OFF								
	Zero: Zeros applied load up to 100% of capacity (limited range in NTEP/OIML configurations)								
	Tare: Tares applied load and displays weight in Net mode								
	F1: Programmable as TEST, UNITS, NET/GROSS, TOTAL & PEAK HOLD								
Display	Five- digit, 1.2 in (30 mm) LED with programmable brightness control								
Displayable Units	Pounds or Kilograms selectable								
Annunciators	COZ, Net, Gross, Total, Peak, Low Battery, lb/kg, Motion, Setpoints								
Power	12 volt rechargeable battery. 115/230 VAC approved battery charger is included								
Operating Time	Up to 200 hours between charging with typical use.								

Operating Temperature Range	5° F to 122°F (-15° C to 50°C)
Auto-Off Mode	Select for 15, 30, 45 minutes, 1 hour or Off
Auto Sleep Mode	Power down during non-use and power up with weight change or any key press
Service Counters	Counts number of lifts over percentage of capacity and lifts over capacity
Calibration	Digital
Filtering	OFF, LO, HI-1, HI-2 selectable
Warranty	One-year limited warranty

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.