

## MSI 159377 8000HD ScaleCore RF/Remote Display/18-72 VDC

The MSI-8000HD is the heavy-duty version of the reputable MSI-8000 RF handheld remote display. The milled anodized aluminum, IP68-rated enclosure is mountable in either a direct panel mount or optional tilt stand. MSI 159377 8000HD ScaleCore RF/Remote Display/18-72 VDC





Manufature: MSI SKU: **159377** Dimensions X: 28.70 Y: 9.00 Z: 14.00 Weight: 5.00 lb

Please Call (800)832-0055

## **Features**

Fortified by the acclaimed reputation of its star precursor, MSI-8000HD is the heavyduty version of the reputable handheld MSI-8000 RF Remote Display. The milled anodized aluminum, IP68-rated, enclosure is mountable in either a direct panel mount or optional tilt stand. The full waterproof construction resists most elements making it especially appealing to the petro-chemical, energy, marine, and aerospace industries. Fully compatible with all MSI ScaleCore-based crane scales and dynamometers, the MSI-8000HD provides utmost versatility for any application.

Fully ergonomic with user-definable function keys and a bold six-digit one inch display ease usability and readability. Process control, safety and other systems benefit with optional relays installed to optimize workflow and operator ease. The MSI-8000HD-1 and MSI-8000HD-2 may be used as a fully functional weigh meter with the standard inclusion of a precision 24-bit A/D. Additionally, the MSI-8000HD-2 has RF capability to transmit data to a secondary MSI-8000 or non-A/D MSI-8000HD.

Wi-Fi, Ethernet, or serial option cards are available for direct connections to networks and computers for advanced traceability and reporting

- IP68 Rugged Milled Aluminum enclosure
- Membrane Keypad for User Control Functionality
- User Definable Function Keys for added versatility
- Indicator or RF remote display with six-digit 1.0 in (26.4 mm) LCD screen

- IP68 milled aluminum enclosure
- Membrane keypad for remote-control functionality
- User definable function keys for added versatility
  Compatible with all ScaleCore™-based products including: MSI-7300 Dyna-Link 2, MSI-3460 Challenger 3, MSI-4260 Port-A-Weigh, MSI-7000 and MSI-7001
- Swivel tilt stand

## **Specifications**

**Optional** 

**Communications** Warranty

One-year limited warranty

## ScaleCore RF/Remote Display

| Model                    | 153591   | 154853           | 160476   | 159377    | 159376   |
|--------------------------|--|------------------|----------|-----------|----------|
| Туре                     | 85-265 VAC<br>(Most Common)  | Internal Battery | 7-36 VDC | 18-72 VDC | 9-36 VDC |
| Legal for Trade          | NTEP CC 15-110   |                  |          |           |          |
| <b>Features</b>          | Swivel tilt stand,IP68 milled aluminum enclosure   |                  |          |           |          |
| <b>Enclosure</b>         | NEMA Type 4, IP68 milled anodized aluminum with O-ring gaskets   |                  |          |           |          |
| Keypad                   | On/Off, Zero (100%), Tare, Print, and two user-defined keys for the following functions: peak hold, high resolution, total, view total, net/gross, units switching                 |                  |          |           |          |
| Display                  | Six-digit 1.0 in (26.4 mm) LCD   |                  |          |           |          |
| <b>Units Displayed</b>   | Pounds, kilograms, tons, metric tons, kilonewtons  |                  |          |           |          |
| Annunciators             | Stable, COZ, peak, kg, kN. lb, M, ton, setpoint, function LEDs. Channels: 1, 2, 3, 4, TTL  |                  |          |           |          |
| Power                    | 90-267 VAC, 9-36 VDC, 18-72 VDC, 120-300 VDC Optional battery power module available   |                  |          |           |          |
| Operating<br>Temperature | -4°F to 140°F (-20°C to 60°C)  |                  |          |           |          |
| RF Remote<br>Channels    | Up to four remote sensors, monitored individually, in pairs or sum all (non-A/D version only)  |                  |          |           |          |
| <b>Service Counters</b>  | A/D version only   |                  |          |           |          |
| A/D Inputs               | Two independent or summing load cell inputs  |                  |          |           |          |
| <b>Excitation</b>        | 4.8 V current limited and over-voltage protected   |                  |          |           |          |
| Filtering                | Off, Low, Hi-1, Hi-2   |                  |          |           |          |
| RF Radio Link            | 2.4 GHz 802.15.4 - Compatible with all ScaleCore <sup>™</sup> -based products including: MSI-7300 Dyna-Link 2, MSI-3460 Challenger 3, MSI-4260 Port-A-Weigh, MSI-7000 and MSI-7001 |                  |          |           |          |
| RF Effective Range       | Typically 100 or more feet (33 m)  |                  |          |           |          |
| Data I/O                 | Dual RS-232 comm ports   |                  |          |           |          |
| Wired Ethernet           | Up to 8 configurable relay outputs   |                  |          |           |          |

Wi-Fi, Bluetooth®, Serial RF, Frequent Hopping Spread Spectrum Optional

Contact US

718-336-5900

Returns

Store Policies

About Us

Phone: <u>(800)832-0055</u> or <u>(718)336-5900</u> Chat with us via <u>WhatsApp Chat</u>

Address: 4802 Glenwood Rd. Brooklyn, NY 11234

© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.