

## MSI 176960 8000HD Wi-Fi Meter/Internal Battery

The MSI-8000HD is the heavy-duty version of the reputable MSI-8000 RF handheld remote display. The milled anodized aluminum, IP68-rated enclosure is mountable in either a direct panel mount or optional tilt stand MSI 176960 8000HD Wi-Fi Meter/Internal Battery





Manufature: MSI SKU: **176960** Dimensions X: 28.70 Y: 9.00 Z: 14.00 Weight: 5.00 lb

Please Call (800)832-0055

## **Features**

Fortified by the acclaimed reputation of its star precursor, MSI-8000HD is the heavyduty version of the reputable handheld MSI-8000 RF Remote Display. The milled anodized aluminum, IP68-rated, enclosure is mountable in either a direct panel mount or optional tilt stand. The full waterproof construction resists most elements making it especially appealing to the petro-chemical, energy, marine, and aerospace industries. Fully compatible with all MSI ScaleCore-based crane scales and dynamometers, the MSI-8000HD provides utmost versatility for any application.

Fully ergonomic with user-definable function keys and a bold six-digit one inch display ease usability and readability. Process control, safety and other systems benefit with optional relays installed to optimize workflow and operator ease. The MSI-8000HD-1 and MSI-8000HD-2 may be used as a fully functional weigh meter with the standard inclusion of a precision 24-bit A/D. Additionally, the MSI-8000HD-2 has RF capability to transmit data to a secondary MSI-8000 or non-A/D MSI-8000HD.

Wi-Fi, Ethernet, or serial option cards are available for direct connections to networks and computers for advanced traceability and reporting

- IP68 Rugged Milled Aluminum enclosure
- Membrane Keypad for User Control Functionality
- User Definable Function Keys for added versatility
- Indicator or RF remote display with six-digit 1.0 in (26.4 mm) LCD screen

- IP68 milled aluminum enclosure
- Membrane keypad for remote-control functionality
- User definable function keys for added versatility
- Compatible with all ScaleCore<sup>™</sup>-based products including: MSI-7300 Dyna-Link 2, MSI-3460 Challenger 3, MSI-4260 Port-A-Weigh, MSI-7000 and MSI-7001
- Swivel tilt stand

## **Specifications**

Data I/O

Wired Ethernet
Optional

Communications Warranty

Dual RS-232 comm ports

One-year limited warranty

Up to 8 configurable relay outputs

## Wi-Fi Meter

176958	176960	176964	176966	176968
85-265 VAC	Internal Battery	7-36 VDC Non Isolated	18-72 VDC Isolated	9-36 VDC Isolated
NTEP CC 15-110				
Swivel tilt stand,IP68 milled aluminum enclosure				
NEMA Type 4, IP68 milled anodized aluminum with O-ring gaskets				
On/Off, Zero (100%), Tare, Print, and two user-defined keys for the following functions: peak hold, high resolution, total, view total, net/gross, units switching				
Six-digit 1.0 in (26.4 mm) LCD				
Pounds, kilograms, tons, metric tons, kilonewtons				
Stable, COZ, peak, kg, kN. lb, M, ton, setpoint, function LEDs. Channels: 1, 2, 3, 4, TTL				
90-267 VAC, 9-36 VDC, 18-72 VDC, 120-300 VDC Optional battery power module available				
-4°F to 140°F (-20°C to 60°C)				
Up to four remote sensors, monitored individually, in pairs or sum all (non-A/D version only)				
A/D version only				
Two independent or summing load cell inputs				
4.8 V current limited and over-voltage protected				
Off, Low, Hi-1, Hi-2				
2.4 GHz 802.15.4 - Compatible with all ScaleCore™-based products including: MSI-7300 Dyna-Link 2, MSI-3460 Challenger 3, MSI-4260 Port-A-Weigh, MSI-7000 and MSI-7001				
Typically 100 o	or more feet (33 m	)		
	85-265 VAC  NTEP CC 15-2  Swivel tilt stan  NEMA Type 4,  On/Off, Zero (2)  functions: peals  switching  Six-digit 1.0 in  Pounds, kilogr  Stable, COZ, p  3, 4, TTL  90-267 VAC, p  module available  -4°F to 140°F (2)  Up to four rem  (non-A/D versi  A/D version on  Two independent  4.8 V current lift  Off, Low, Hi-1,  2.4 GHz 802.1  including: MSI-Port-A-Weigh,	NTEP CC 15-110 Swivel tilt stand,IP68 milled alum NEMA Type 4, IP68 milled anod On/Off, Zero (100%), Tare, Print functions: peak hold, high resolu switching Six-digit 1.0 in (26.4 mm) LCD Pounds, kilograms, tons, metric Stable, COZ, peak, kg, kN. Ib, M 3, 4, TTL 90-267 VAC, 9-36 VDC, 18-72 V module available -4°F to 140°F (-20°C to 60°C) Up to four remote sensors, moni (non-A/D version only) A/D version only Two independent or summing lo 4.8 V current limited and over-ve Off, Low, Hi-1, Hi-2 2.4 GHz 802.15.4 - Compatible v including: MSI-7300 Dyna-Link 2 Port-A-Weigh, MSI-7000 and MS	85-265 VAC Internal Battery  NTEP CC 15-110  Swivel tilt stand,IP68 milled aluminum enclosure NEMA Type 4, IP68 milled anodized aluminum v On/Off, Zero (100%), Tare, Print, and two user-of functions: peak hold, high resolution, total, view switching  Six-digit 1.0 in (26.4 mm) LCD  Pounds, kilograms, tons, metric tons, kilonewton Stable, COZ, peak, kg, kN. lb, M, ton, setpoint, fr. 3, 4, TTL  90-267 VAC, 9-36 VDC, 18-72 VDC, 120-300 VI module available  -4°F to 140°F (-20°C to 60°C)  Up to four remote sensors, monitored individually (non-A/D version only)  A/D version only  Two independent or summing load cell inputs  4.8 V current limited and over-voltage protected Off, Low, Hi-1, Hi-2  2.4 GHz 802.15.4 - Compatible with all ScaleColincluding: MSI-7300 Dyna-Link 2, MSI-3460 Char	85-265 VAC Internal Battery  NTEP CC 15-110  Swivel tilt stand,IP68 milled aluminum enclosure  NEMA Type 4, IP68 milled anodized aluminum with O-ring gask On/Off, Zero (100%), Tare, Print, and two user-defined keys for functions: peak hold, high resolution, total, view total, net/gross, switching  Six-digit 1.0 in (26.4 mm) LCD  Pounds, kilograms, tons, metric tons, kilonewtons  Stable, COZ, peak, kg, kN. lb, M, ton, setpoint, function LEDs. 03, 4, TTL  90-267 VAC, 9-36 VDC, 18-72 VDC, 120-300 VDC Optional bat module available  -4°F to 140°F (-20°C to 60°C)  Up to four remote sensors, monitored individually, in pairs or su (non-A/D version only)  A/D version only  Two independent or summing load cell inputs  4.8 V current limited and over-voltage protected  Off, Low, Hi-1, Hi-2  2.4 GHz 802.15.4 - Compatible with all ScaleCore™-based prodincluding: MSI-7300 Dyna-Link 2, MSI-3460 Challenger 3, MSI-Port-A-Weigh, MSI-7000 and MSI-7001

Wi-Fi, Bluetooth®, Serial RF, Frequent Hopping Spread Spectrum Optional

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

Phone: <u>(800)832-0055</u> or <u>(718)336-5900</u> Chat with us via <u>WhatsApp Chat</u>

Address: 4802 Glenwood Rd. Brooklyn, NY 11234

© 2000 - 2023 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.