

Model	503413-0001	503413-0002	503413-0003	503413-0004	503413-0005	503413-0006	503413-0007	503413-0008	503413-0009
Capacity x Readability	500 x 0.2 lb	2000 x 1.0 lb	5000 x 1.0 lb	10,000 x 2.0 lb	20,000 x 5.0 lb	30,000 x 10 lb	50,000 x 10 lb	70,000 x 20 lb	100,000 x 20 lb
	250 x 0.1 kg	1000 x 0.5 kg	2500 x 0.5 kg	5000 x 1.0 kg	10,000 x 2.0 kg	15,000 x 5.0 kg	25,000 x 5.0 kg	35,000 x 10 kg	50,000 x 10 kg
Legal for Trade	NTEP								-
Accuracy	± 0.1% of applied load ±1d								
enclosure	NEMA 4, IP66 marine grade 356 alloy anodized cast aluminum								
Lifting Eye, Shackle & Hook	Crosby ® or equal with 360° thrust-bearing swivel hook								
Design Overload	200% Safe / 500% Ultimate (except as noted)								
Functions	Power: Turns Unit ON or OFF Zero: Zeros applied load up to 100% of capacity (limited range in NTEP/OIML configurations) Tare: Tares applied load and displays weight in Net mode F1: Programmable as TEST, UNITS, NET/GROSS, TOTAL & PEAK HOLD								

Display	Five- digit, 1.2 in (30 mm) LED with programmable brightness control
Displayable Units	Pounds or Kilograms selectable
Annunciators	COZ, Net, Gross, Total, Peak, Low Battery, lb/kg, Motion, Setpoints
Power	12 Volt rechargeable battery 115/230 VAC battery charger is included
Operating Time	Up to 200 hours between charging with typical use. Less with optional RF modem link
Operating Temperature Range	5° F to 122°F (-15° C to 50°C)
Auto-Off Mode	Select for 15, 30, 45 minutes, 1 hour or Off
Auto Sleep Mode	Power down during non-use and power up with weight change or any key press
Service Counters	Counts number of lifts over percentage of capacity and lifts over capacity
Calibration	Digital
Filtering	OFF, LO, HI-1, HI-2 selectable

Object Moved

This document may be found [here](#)

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

• Phone: [\(800\)832-0055](#) or [\(718\)336-5900](#)

• Chat with us via [WhatsApp Chat](#)

• Address: 4802 Glenwood Rd. Brooklyn, NY 11234

© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.

