



Minebea Combics 2 CAW-2S1U-50DD-I Stainless Steel Complete 12 X 12 Scale 60 X 0.002 lb

Combics provides support in all areas of your process chain, from manual formulations up to PC controlled production checks. The modular system allows tailor-made configuration of the individual components for each area. We also produce individual complete solutions according to your specific applications.



Minebea
intec
The true measure

Manufacture: Minebea Intec

SKU: CAW-2S1U50DDI

Dimensions

X: 12.00 **Y:** 12.00

Weight: 30.00 lb

Free Ground Shipping within the
48 continental US States

Please Call
(800)832-0055

Features

Combics provides support in all areas of your process chain, from manual formulations up to PC controlled production checks. The modular system allows tailor-made configuration of the individual components for each area. We also produce individual complete solutions according to your specific applications.

Based on the specific requirements of various industries and the basic legal conditions, Sartorius has developed intelligent solutions for all weighing applications, from incoming goods through to production on a large technical scale.

Amber backlit LCD display, 0.8 in, 13 segment, External calibration routine, RS-232C, Numeric keypad (with two "IDs") for entering identifier codes and preset tares, Info key for quick and easy display of tare input and ID codes, Date/time fully integrated, Three built-in LED checkweighing lights, Bar graph weighing range indicator, Optional barcode scanner for preset tare, reference weight and ID entry, Stored customer specific data records, and Two scale connections, analog or digital.

Weighing

The basic weighing function is available at all times.

Features

- Zero the weighing instrument by pressing a key
- Store the weight on the instrument as tare by pressing a key
- Tare container weight automatically
- Enter tare weight through bar code scanner
- Enter tare weight through numeric keypad
- Delete tare values by manual entering
- Press key to toggle the display between
- Gross and net values
- 1 stand 2nd weight unit or
- normal and 10-fold higher resolution
- Weighing with two scales
- Individual data ID codes with numeric values for identifying weight values
- Print weight value
- GMP-compliant printout
- Automatic printing
- Automatic data output

Standard Features

- Amber backlit LCD display, 0.8
- in, 13 segment
- External calibration routine
- RS-232C
- Numeric keypad (with two “IDs”) for entering identifier codes and preset tares
- Info key for quick and easy display of tare input and ID codes
- Date/time fully integrated
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- Optional barcode scanner for preset tare, reference weight and ID entry
- Stored customer specific data records
- Two scale connections, analog or digital
- Combics 2 indicator
- Mild Steel with IP65 protection, indicator IP44
- Stainless steel with IP67 protection, indicator IP69k
- 4 Platform dimensions
- 4 Capacities
- Ships from stock

Specifications

Supply Voltage:

- 9V

Power Requirements:

- 120-240, WAC, 17W / 23

Indicator Housing:

- VA maximum
- AISI 304 stainless steel

Indicator Dimensions:

- 11.9 W x 7.4 D x 3.5 in H

Operating Temperature:

- 14° F to 104° F (-10° C to 40° C)

Net Weight:

- 5 lb

Warranty:

- Two-year limited warranty
- Accessories one-year

Specifications

| Stainless Steel Combics Complete Scale CAIS2-U | | | | |
|---|---|--------------------|---------------------|----------------------|
| Model | 2S1U-10CC-I | 2S1U-50DD-I | 2S1U-100EE-I | 2S4UR-250GG-I |
| Dimension | 10" x 10" | 12" x 12" | 18" x 18" | 24" x 24" |
| Capacity / Readability (Lbs.) | 15 x 0.0005 | 60 x 0.002 | 150 x 0.005 | 300 x 0.01 |
| Capacity / Readability (Kg.) | 6 x 0.0002 | 30 x 0.001 | 60 x 0.002 | 150 x 0.01 |
| Legal For Trade | NO | | | |
| Cable Platform (ft.) | 10 | | | |
| Warranty | Two-year limited warranty, Accessories one-year | | | |
| Power Requirements | 120-240 VAC, 17, W / 23 VA maximum | | | |
| Supply Voltage | 9V | | | |
| Operating Tempature | 14° F to 104° F (-10° C to 40° C) | | | |
| Indicator Housing | AISI 304 stainless steel | | | |
| Indicator Dimensions | 11.9 W x 7.4 D x 3.5in H | | | |

i81u812

- [Contact US](#)
- [718-336-5900](#)
- [Returns](#)
- [Store Policies](#)
- [About Us](#)

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.

