

FM Approved: Classes 1,2,3, Division 1, Groups ABCDEGFT4, US and Canadian hazardous areas, when used with CIX53-U Can be used in areas where explosive gas and dust mixtures occur Documentation to verify intrinsic safety available upon request Completely constructed with AISI 304 stainless steel



**Includes
Safe Area
Power Supply**



This Item Contains the following items

- | | | | | |
|---|--|---|---|--|
| 1 x Minebea IIS64EDE-HX Combics 2 Explosion Proof Platform 15.8 in x 11.8 in - 141 lb x 0.0002 lb | 1 x Minebea M26 Cable from CIXS3 or CAIXS2 to IS-X | 1 x Minebea A19 485 interface for CIXS3 or CAIXS2 Explosion Proof Indicator | 1 x Minebea YPS02-ZKR Safe Area Power Supply (65 ft. of intrinsically safe cable) | 1 x Minebea CAIXS2 Combics 2 Explosion-FM approved indicator for direct connection with IS-X platforms |
|---|--|---|---|--|

Manufacture: Minebea Intec
SKU: **IS64EDE-HX-SAFE**

Dimensions

X: 10.00 Y: 10.00

Free Ground Shipping within the 48 continental US States

Please Call (800)832-0055

Features

Combics

Explosion Proof Bench and Floor Platforms

Standard Features

- FM Approved: Classes 1,2,3, Division 1, Groups ABCDEGFT4, US and Canadian hazardous areas, when used with CIX53-U
- Can be used in areas where explosive gas and dust mixtures occur
- Documentation to verify intrinsic safety available upon request
- Completely constructed with AISI 304 stainless steel
- All units are built for easy cleaning and disinfection and meet HACCP and FDA requirements for the food industry.
- Load cells are hermetically sealed, IP68 protection rated

Applications

- Pharmaceutical, chemical, electronics, food processing, precious metals, metal production and processing
- Regulatory Compliance
- NEMA, HACCP, FDA, GLP/GMP*, FM

Specifications

6.8 to 660 lb models

Model	CIXS2 ISXBBS-3-H	CIXS2 ISXBBS-6-H	CIXS2 IS16EDE-HX	CIXS2 IS34EDE-HX	CIXS2 IS64EDE-SX	CIXS2 S64EDE-HX	CIXS2 IS150IGG-HX	CIXS2 IS300IGG-HX
Capacity x Readability	6.8 x 0.00002 lb	13.5 x 0.00002 lb	35 x 0.0002 lb	75 x 0.0002 lb	141 x 0.002 lb	141 x 0.0002 lb	330 x 0.002 lb	660 x 0.005 lb
Pan Size	7.1" x 7.1"	7.1" x 7.1"	15.8" x 11.8"	15.8" x 11.8"	15.8" x 11.8"	15.8" x 11.8"	32" x 24"	32" x 24"
Base Design	Stainless Steel	Stainless Steel	Painted	Painted	Painted	Painted	Painted	Painted
Weighing Pan Indicator	Stainless Steel Weighing Pan CAIXS2 with 485 interface and Cable to IS-X							
FM Approved Base Interface	Class 1,2,3,Division 1,Groups A,B,C,D,E,F,G,T4 More info RS485							
Internal Calibration	Optional and must be ordered with the unit and is not field installable							
Power	Requires single YPS02-XUR for hazardous area connection or YPS02-ZKR for safe area connection							
* Hazardous area Power for USA only - for Canada Please Call (800)832-0055 or 718-336-5900								

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.