

You won't have to wait more than one second for a stable readout with this platform. With special menu codes activated, you can actually reduce the response time down to 800ms!



Minebea true measure

Manufature: Minebea Intec SKU: IS64EDEH Dimensions X: 15.80 Y: 11.80 Free Ground Shipping within the 48 continental US States

Please Call (800)832-0055

Features

Minebea IS Series Platforms

Ultra fast Response Time

You won't have to wait more than one second for a stable readout with this platform. With special menu codes activated, you can actually reduce the response time down to 800ms!

Standard Internal Calibration

Simply press one key to calibrate the platform at any time. Internal calibration is especially useful when the scale gets moved from one location to another, or when the temperature varies considerably.

Features

- BBE/CCE Models: rated IP54 EDE Models: rated IP65 FEG/IGG Models: Rated IP67
- Below Scale Weighing

-For all scales < 12kg hook supplied For FEG and IGG scales: No below scale weighing

Additional Features

When connected to Combics Indicator, feature and applications for Combics Series are available

- RS485 is standard with IS (RS232 is available option)
- Internal Calibration Weight
- Weight stabilizes in less than 1.5 seconds, with output rates of up to 50 times per second
- Use a combics 2 or Combics 3 indicator for a dual analog digital weighing solution

Specifications

Minebea IS Series Platforms		
Model	Dimension	Capacity(Lbs.)
IS06BBE-S	05.1"	1.3 x 0.000002
IS2CCE-S	8.5" x 8"	14.8 x 0.00002
IS6CCE-H	8.5" x 8"	13.6 x 0.00002
IS6CCE-S	8.5" x 8"	13.6 x 0.0002
IS12CCE-S	8.5" x 8"	26 x 0.0002
IS16EDE-H	15.8" x 11.8"	35 x 0.0002
IS34EDE-H	15.8" x 11.8"	75 x 0.0002
IS64EDE-S	15.8" x 11.8"	141 x 0.0002
IS64EDE-H	15.8" x 11.8"	141 x 0.002
IS64FEG-S	22" x 18"	141 x 0.0002
IS150IGG-H	32" x 24"	330 x 0.002
IS300IGG-H	32" x 24"	660 x 0.005
IS16EDE-H1	15.8" x 11.8"	35 x 0.05
IS64FEG-S1	22" x 18"	141 x 0.00002
IS150IGG-H1	32" x 24"	330 x 0.0002
IS300IGG-H1	32" x 24"	660 x 0.0005
Legal For Trade	NO	
Data Interface	RS485 is standard with IS (RS232 is available option)	
Special Order	Allow 2 additional weeks for delivery	

i81u812

