



Minebea MW1S1U-15DC-L Midrics Complete Bench 12.5 x 9.5, Stainless Steel Scales 30 x 0.002 lb

2 Indicators types to choose from, 7 weighing ranges from 3 kg to 300kg, 5 platform dimensions, Resolution 15.000 digits, Unit comes wired, calibrated and ready to weigh!



Minebea
intec
The true measure

Manufacture: Minebea Intec
SKU: MW1S1U-15DC-L

Dimensions

X: 12.50 Y: 9.50

Free Ground Shipping within the
48 continental US States

Please Call
(800)832-0055

Features

Midrics Complete Scales Stainless Steel Version

Features

- 2 Indicators types to choose from
- 7 weighing ranges from 3 kg to 300kg
- 5 platform dimensions
- Resolution 15.000 digits
- Unit comes wired, calibrated and ready to weigh!

Specifications

Maximum readability:	15.000d
Accuracy class:	Klasse III
Number of verification scale intervals:	3.000e, 2 x 3.000e
Data interface:	optional
Power supply:	100-240 V/AC

DC power supply:	optional, 24V/DC
AC power supply:	optional, 24V/AC
Temperature range:	-10°C ... +40°C
Electrical safety:	EN61010-1, EN60950 IEC1010-1, IEC950
Display- and Control unit:	remoted, optional with column for connecting to platform
Version:	All in Stainless steel 1.4301 (V2A)
Ingress Protection Rate:	Display- and Control unit IP65 Platform IP 67 (load cell IP 68)
Weighing system:	Design1 and design2 : Stainless steel Single Point load cell C 3 Design3 : 4 load cells C3
Load plate:	Stainless steel 1.4301 AISI 304 4 adjustable leveling feet
Others:	Built-in level indicator Overload stop
Battery operation:	Optional via internal or external rechargeable battery pack
Limitation of emissions:	EN61326 Kl. B, (IEC61326)
Defined immunity to interference:	EN61326 Ind. (IEC61326)

Specifications

Midrics Complete Bench Stainless Steel Scales		
Model	Dimension	Capacity(Lbs.)
MW1S1U-3DC-LU	12.5 x 9.5	5 x 0.001
MW1S1U-6DC-LU	12.5 x 9.5	10 x 0.002
MW1S1U-15DC-L	12.5 x 9.5	25 x 0.005
MW2S1U-3DC-LU	12.5 x 9.5	5 x 0.001
MW2S1U-6DC-LU	12.5 x 9.5	10 x 0.002
MW2S1U-15DC-L	12.5 x 9.5	25 x 0.005
MW1S1U-30ED-L	15.75 x 11.8	50 x 0.01
MW1S1U-60ED-L	15.75 x 11.8	100 x 0.02
MW2S1U-30ED-L	15.75 x 11.8	50 x 0.01
MW2S1U-60ED-L	15.75 x 11.8	100 x 0.02
MW1S1U-30FE-L	19.5 x 15.75	50 x 0.01
MW1S1U-60FE-L	19.5 x 15.75	100 x 0.02
MW1S1U-150FE	19.5 x 15.75	250 x 0.05
MW2S1U-30FE-LU	19.5 x 15.75	50 x 0.01
MW2S1U-60FE-LU	19.5 x 15.75	100 x 0.02
MW2S1U-150FE	19.5 x 15.75	250 x 0.02
Legal For Trade	YES	
Approval	NTEP Approved	
Cable	2,5m	
Data Interface	Optional (RS232, RS422, RS485, Digital I/O 5/5, Analog Output)	

Display- and Control unit:	Remoted, optional with column for connecting to platform
Weighing system:	Design1 and design2: Single Point load cell C 3
Battery operation:	Optional via internal or external rechargeable battery pack

i81u812

[Contact US](#)

[718-336-5900](#)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](#) or [\(718\)336-5900](#)
 - Chat with us via [WhatsApp Chat](#)
 - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.