

2 Indicators types to choose from, 7 weighing ranges from 3 kg to 300kg, 5 platform dimensions, Resolution 15.000 digits, Unit comes wired, calibrated and ready to weigh!



**Minebea**  
**intec**  
The true measure

Manufature: Minebea Intec

SKU: MW2P1U-30FE-L

## Dimensions

X: 19.50    Y: 15.75

Free Ground Shipping within the  
48 continental US States

**Please Call  
(800)832-0055**

## Features

### Midrics Complete Scales Painted Version

## Features

- 2 Indicators types to choose from
- 7 weighing ranges from 3 kg to 300kg
- 5 platform dimensions
- Resolution 15.000 digits
- Unit comes wired, calibrated and ready to weigh!

## Specifications

|                                  |                                                                |
|----------------------------------|----------------------------------------------------------------|
| Maximum readability:             | 15,000 digits                                                  |
| Data interface:                  | Optional (RS232, RS422, RS485, Digital I/O 5/5, Analog Output) |
| Power supply:                    | 100-240 V/AC                                                   |
| DC power supply:                 | optional, 24V/DC                                               |
| AC power supply:                 | optional, 24V/AC                                               |
| Temperature range:               | -10°C ... +40°C (14°F...104°F)                                 |
| Electrical safety:               | EN61010-1, EN60950<br>IEC1010-1, IEC950                        |
| Display- and Control unit:       | Remoted, optional with column for connecting to platform       |
| Version:                         | Display- and Control unit stainless steel, platform steel      |
| Ingress Protection Rate:         | Display- and Control unit IP65<br>Platform IP 65               |
| Weighing system:                 | Design1 and design2: Single Point load cell C 3                |
| Load plate:                      | Design1 and design2: stainless steel 1.4301 (V2A)              |
| Others:                          | 4 adjustable leveling feet<br>Overload stops                   |
| Defined immunity to interference | Acc. to EN 61326-1, industrial environments (IEC61326-1)       |

## Specifications

|                             |                                                                                                                                       |                                |                                |                                |                                |                                |                                |                                |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Models with Painted Steel   | MW2P1U-3DC-L                                                                                                                          | MW2P1U-6DC-L                   | MW2P1U-15DC-L                  | MW2P1U-30ED-L                  | MW2P1U-60ED-L                  | MW2P1U-30FE-L                  | MW2P1U-60FE-L                  | MW2P1U-150FE-L                 |
| Models with Stainless Steel | MW2S1U-3DC-L                                                                                                                          | MW2S1U-6DC-L                   | MW2S1U-15DC-L                  | MW2S1U-30ED-L                  | MW2S1U-60ED-L                  | MW2S1U-30FE-L                  | MW2S1U-60FE-L                  | MW2S1U-150FE-L                 |
| Capacity x Readability      | 6 x 0.0005 lb<br>3 x 0.0002 kg                                                                                                        | 15 x 0.001 lb<br>6 x 0.0005 kg | 30 x 0.002 lb<br>15 x 0.001 kg | 60 x 0.005 lb<br>30 x 0.002 kg | 120 x 0.01 lb<br>60 x 0.005 kg | 60 x 0.005 lb<br>30 x 0.002 kg | 120 x 0.01 lb<br>60 x 0.005 kg | 300 x 0.02 lb<br>150 x 0.01 kg |
| Pan Size                    | 12.6 in x 9.4 in                                                                                                                      |                                |                                | 15.7 in x 11.8 in              |                                | 19.7 in x 15.7 in              |                                |                                |
| Platform (mm)               | 320 x 240 x 85-100                                                                                                                    |                                |                                | 400 x 300 x 96-111             |                                | 500 x 400 x 110-125            |                                |                                |
| Functions                   | counting, checkweighing, classification, totalizing, net-total formulation, animal weighing, weighing in percent, neutral measurement |                                |                                |                                |                                |                                |                                |                                |
| Legal for Trade             | YES                                                                                                                                   |                                |                                |                                |                                |                                |                                |                                |

|                                 |                                                             |
|---------------------------------|-------------------------------------------------------------|
| <b>Protection rating</b>        | IP65                                                        |
| <b>Adjustable Leveling Feet</b> | YES                                                         |
| <b>Temperature range</b>        | -10°C ... +40°C                                             |
| <b>Display</b>                  | 20 mm LCD with backlit                                      |
| <b>Battery operation</b>        | Optional via internal or external rechargeable battery pack |

i81u812

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2023 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.