

2 Indicators types to choose from, 7 weighing ranges from 3 kg to 300kg, 5 platform dimensions, Resolution 15.000 digits, Unit comes wired, calibrated and ready to weigh!



Minebea
intec
 The true measure

Manufature: Minebea Intec

SKU: MW2S1U-15DC-L

Dimensions

X: 12.50 Y: 9.50

Free Ground Shipping within the
 48 continental US States

Please Call
(800)832-0055

Features

Midrics Complete Scales Stainless Steel Version

Features

- 2 Indicators types to choose from
- 7 weighing ranges from 3 kg to 300kg
- 5 platform dimensions
- Resolution 15.000 digits
- Unit comes wired, calibrated and ready to weigh!

Specifications

Maximum readability:	15.000d
Accuracy class:	Klasse III
Number of verification scale intervals:	3.000e, 2 x 3.000e
Data interface:	optional
Power supply:	100-240 V/AC
DC power supply:	optional, 24V/DC
AC power supply:	optional, 24V/AC
Temperature range:	-10°C ... +40°C
Electrical safety:	EN61010-1, EN60950 IEC1010-1, IEC950
Display- and Control unit:	remoted, optional with column for connecting to platform
Version:	All in Stainless steel 1.4301 (V2A)
Ingress Protection Rate:	Display- and Control unit IP65 Platform IP 67 (load cell IP 68)
Weighing system:	Design1 and design2 : Stainless steel Single Point load cell C 3 Design3 : 4 load cells C3
Load plate:	Stainless steel 1.4301 AISI 304
Others:	4 adjustable leveling feet Built-in level indicator Overload stop
Battery operation:	Optional via internal or external rechargeable battery pack
Limitation of emissions:	EN61326 Kl. B, (IEC61326)
Defined immunity to interference:	EN61326 Ind. (IEC61326)

Specifications

Models with Painted Steel	MW2P1U-3DC-L	MW2P1U-6DC-L	MW2P1U-15DC-L	MW2P1U-30ED-L	MW2P1U-60ED-L	MW2P1U-30FE-L	MW2P1U-60FE-L	MW2P1U-150FE-L
Models with Stainless Steel	MW2S1U-3DC-L	MW2S1U-6DC-L	MW2S1U-15DC-L	MW2S1U-30ED-L	MW2S1U-60ED-L	MW2S1U-30FE-L	MW2S1U-60FE-L	MW2S1U-150FE-L
Capacity x Readability	6 x 0.0005 lb 3 x 0.0002 kg	15 x 0.001 lb 6 x 0.0005 kg	30 x 0.002 lb 15 x 0.001 kg	60 x 0.005 lb 30 x 0.002 kg	120 x 0.01 lb 60 x 0.005 kg	60 x 0.005 lb 30 x 0.002 kg	120 x 0.01 lb 60 x 0.005 kg	300 x 0.02 lb 150 x 0.01 kg
Pan Size	12.6 in x 9.4 in		15.7 in x 11.8 in		19.7 in x 15.7 in			

Platform (mm)	320 x 240 x 85-100	400 x 300 x 96-111	500 x 400 x 110-125
Functions	counting, checkweighing, classification, totalizing, net-total formulation, animal weighing, weighing in percent, neutral measurement		
Legal for Trade	YES		
Protection rating	IP65		
Adjustable Leveling Feets	YES		
Temperature range	-10°C ... +40°C		
Display	20 mm LCD with backlit		
Battery operation	Optional via internal or external rechargeable battery pack		

i81u812

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:(800)832-0055) or [\(718\)336-5900](tel:(718)336-5900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2023 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.