

Minebea SIWRDCP-V10 is a compact industrial scale in which a standard strain gauge weigh cell is used. Speed-up technology makes the Signum uniquely fast, which means Signum bench scales can weigh in half a second.



Manufacture: Minebea Intec
SKU: SIWRDCP-V10
Weight: 30.00 lb
 Free Ground Shipping within the 48 continental US States

Please Call (800)832-0055

Features

Minebea SIWRDCP-V10 is a compact industrial scale in which a standard strain gauge weigh cell is used. Speed-up technology makes the Signum uniquely fast, which means Signum bench scales can weigh in half a second. Minebea preconfigured Signum offers exceptional performance features and is a very easy-to-operate bench scale. The SIWRDCP-V10 is extremely rugged and resistant, and perfectly adapts to any ambient conditions in an industrial environment. With Signum, anything is possible: pick and choose your level of applications and different resolutions, and enjoy the benefits of a wide variety of interfaces and options for IP65 protection, use in harsh areas and for many more features. Sartorius Signum is a compact scale built exactly the way you want it – without compromises.

Model	SIWRDCP-V6	SIWRDCP-V7	SIWRDCP-V8	SIWRDCP-V9	SIWRDCP-V10	SIWRDCP-V11	SIWRDCP-V12	SIWRDCP-V13	SIWRDCP-V14	SIWRDCP-V15
Capacity	3 kg	6 kg	15 kg	35 kg	60 kg	6 kg	6 kg	15 kg	35 kg	60 kg
Readability	0.1 g	0.2 g	0.5 g	1.0 g	2.0 g	0.2 g	1.0 g	0.5 g	1.0 g	2.0 g
Repeatability	0.2 g			1 g	2 g	0.2 g			1 g	2 g
Linearity	0.3 g		0.4 g	0.8 g	1.5 g	3 g	0.4 g	0.8 g	1.5 g	3 g
Weighing Modes	Carats,Grains,Milligrams,Pounds,Ounces,Pennyweight,Grams,Troy Ounces,KiloGrams									
Weigh Cell	Strain Gauge									
Standard Features	Basic Weighing, RS232 interface, Underhook									
Indicator/Platform Material	Die-Cast Aluminum - (AISI304) (Stands up to most citrus applications)									
Indicator Cable Length	3 meters (coiled in units base)									
Operating Temperature	-10°C to 40°C (14°F to 104°F)									
External Calibration	Requires 2,000 g Cal. Weight	Requires 5,000 g Cal. Weight		Requires 10,000 g Cal. Weight	Requires 20,000 g Cal. Weight	Requires 5,000 g Cal. Weight				
Display Type	Backlit Liquid Crystal Display with 14 Segments									
Power	AC Powered Only									
Platform Size	12.6" x 9.4"									
Dimensions (W x D)	16.4" x 5.2"									
Protection Rating	IP65									
Functions	Zero, Tare					Zero, Tare, Counting, Checkweighing, Classification, Averaging(animal weighing), Totalizing, Neutral Measurement, % Weighing, Formulation				
Level	Weigh Only Level 1					Applications Level 2				

Application Levels and Their Capabilities

Level Capabilities	Level 1	Level 2	Level 3
Keypad	6 Keys	14 Keys	17 Keys
Display	14 Segments	14 segments plus application symbols	14 segments plus application symbols
Weighing	Yes	Yes	Yes
Averaging	N/A	Yes	Yes
Reference Scale Connection	N/A	Yes	Yes
Counting	N/A	Yes	Yes
Totalizing	N/A	Yes	Yes
Checkweighing	N/A	Yes	Yes
Product Data Memory	N/A	N/A	Yes
Date/Time	N/A	Option A31	Option A31
SQ min (min sample qty)	Yes	Yes	Yes

ID Codes (4x40 characters)	N/A	N/A	Yes
-------------------------------	-----	-----	-----

i81u812

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2023 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.