



**Minebea Signum SIWRDCP-V6 Washdown LEVEL 1 Industrial Scale 3 kg x 0.1 g**

Minebea SIWRDCP-V6 is a compact industrial scale in which a standard strain gauge weigh cell is used. Speed-up technology makes Signum uniquely fast, which means Signum bench scales can weigh in half a second.



Manufacture: Minebea Intec  
 SKU: **SIWRDCP-V6**  
 Weight: 30.00 lb  
 Free Ground Shipping with the 48 continental US States

**Please Call (800)832-0**

**Features**

Signum compact industrial scale series has a choice of three powerful technologies, each with a different level of performance: The standard weighing system Signum Regular models enables resolutions of up to 35,000d; Signum Advanced models feature a mechatronic weighing system with resolutions of up to 65 and Signum Supreme models are equipped with a monolithic weigh cell for resolutions of up to 350,000d. Signum offers users a premium scale that is remarkably easy to use and offers a broad range of options for adaptation to specific customer needs.

| Model                       | SIWRDCP-V6   | SIWRDCP-V7                   | SIWRDCP-V8                    | SIWRDCP-V9                    | SIWRDCP-V10                  | SIWRDCP-V11 | SIWRDCP-V12 | SIWRDCP-V13 | SIWRDCP-V14 |
|-----------------------------|--|------------------------------|-------------------------------|-------------------------------|------------------------------|-------------|-------------|-------------|-------------|
| Capacity                    | 3 kg   | 6 kg                         | 15 kg                         | 35 kg                         | 60 kg                        | 6 kg        | 6 kg        | 15 kg       | 35 kg       |
| Readability                 | 0.1 g  | 0.2 g                        | 0.5 g                         | 1.0 g                         | 2.0 g                        | 0.2 g       | 1.0 g       | 0.5 g       | 1.0 g       |
| Repeatability               | 0.2 g  |                              | 1 g                           |                               | 2 g                          |             | 0.2 g       |             | 1 g         |
| Linearity                   | 0.3 g  |                              | 0.4 g                         | 0.8 g                         | 1.5 g                        | 3 g         | 0.4 g       | 0.8 g       | 1.5 g       |
| Weighing Modes              | Carats,Grains,Milligrams,Pounds,Ounces,Pennyweight,Grams,Troy Ounces,KiloGrams |                              |                               |                               |                              |             |             |             |             |
| Weigh Cell                  | Strain Gauge   |                              |                               |                               |                              |             |             |             |             |
| Standard Features           | Basic Weighing, RS232 interface, Underhook                                     |                              |                               |                               |                              |             |             |             |             |
| Indicator/Platform Material | Die-Cast Aluminum - (AISI304) (Stands up to most citrus applications)          |                              |                               |                               |                              |             |             |             |             |
| Indicator Cable Length      | 3 meters (coiled in unit's base)   |                              |                               |                               |                              |             |             |             |             |
| Operating Temperature       | -10°C to 40°C (14°F to 104°F)  |                              |                               |                               |                              |             |             |             |             |
| External Calibration        | Requires 2,000 g Cal. Weight   | Requires 5,000 g Cal. Weight | Requires 10,000 g Cal. Weight | Requires 20,000 g Cal. Weight | Requires 5,000 g Cal. Weight |             |             |             |             |
| Display Type                | Backlit Liquid Crystal Display with 14 Segments                                |                              |                               |                               |                              |             |             |             |             |
| Power                       | AC Powered Only  |                              |                               |                               |                              |             |             |             |             |
| Platform Size               | 12.6" x 9.4"   |                              |                               |                               |                              |             |             |             |             |
| Dimensions (W x D)          | 16.4" x 5.2"   |                              |                               |                               |                              |             |             |             |             |



Protection Rating

IP65

Functions

Zero, Tare

Zero, Tare, Counting, Checkweighing, Classification, Averaging(anim weighing), Totalizing, Neutral Measurement, % Weighing, Formulation

Level

Weigh Only Level 1

Applications Level 2

Application Levels and Their Capabilities

| Level Capabilities            | Level 1     | Level 2                              | Level 3                              |
|-------------------------------|-------------|--------------------------------------|--------------------------------------|
| Keypad                        | 6 Keys      | 14 Keys                              | 17 Keys                              |
| Display                       | 14 Segments | 14 segments plus application symbols | 14 segments plus application symbols |
| Weighing                      | Yes         | Yes                                  | Yes                                  |
| Averaging                     | N/A         | Yes                                  | Yes                                  |
| Reference Scale Connection    | N/A         | Yes                                  | Yes                                  |
| Counting                      | N/A         | Yes                                  | Yes                                  |
| Totalizing                    | N/A         | Yes                                  | Yes                                  |
| Checkweighing                 | N/A         | Yes                                  | Yes                                  |
| Product Data Memory           | N/A         | N/A                                  | Yes                                  |
| Date/Time                     | N/A         | Option A31                           | Option A31                           |
| SQ min (min sample qty)       | Yes         | Yes                                  | Yes                                  |
| ID Codes<br>(4x40 characters) | N/A         | N/A                                  | Yes                                  |

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

• Phone: (800)832-0055 or (718)336-5900

• Chat with us via [WhatsApp Chat](#)

• Address: 4802 Glenwood Rd. Brooklyn, NY 11234

• © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.