

Backed by our commitment to accurate and precise measurement, the OHAUS Starter Series of electrodes are designed to produce exact results time and time again. The Starter Series includes pH, reference, oxidation-reduction potential (ORP), conductivity, dissolved oxygen (DO), and temperature electrodes that can be used in combination with Starter bench and portable meters.



Manufacture: Ohaus

SKU: 30378544

Weight: 1.00 lb

Free Ground Shipping
within the 48
continental US States

Please Call
(800)832-0055

Features

Measurement Range	0.00 – 20.0 mg/L(ppm)
Working Environment	10°C – 40°C, 85%RH, non-condensing
Working Environment	50°F – 104°F, 85%RH, non-condensing
Net Weight	105.0 g (3.7 oz)
Dimensions (ØDiameter)	16.0 mm (0.63 in)
Electrode Type	DO
Cable (Length)	1m
Temperature Range	0 °C – 60 °C (32 °F – 140 °F)
Shaft Material	Plastic
Dimensions (Length)	125.0 mm (4.9 in)
Measurement Range DO (%) (ppm)	0 % – 20 ppm
Temperature Sensor	No

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:(800)832-0055) or [\(718\)336-5900](tel:(718)336-5900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.