



Ohaus CX-621 (30428200) Compass CX Compact Scale, 620 g x 0.1 g

Designed with energy efficiency in mind, the Compass CX series offers a battery life of up to 1,000 continuous hours, allowing for uninterrupted operation. Featuring a slim, stackable and light-weight design,



Capacity x Readability

620 g x 0.1 g

Pan Size

5 x 5.6 in

Manufacture: Ohaus

SKU: 30428200

UPC:

745809823718

Weight: 3.00 lb

Free Ground Shipping
within the 48
continental US States

**Please Call
(800)832-0055**

Features

Designed with Energy Efficient Weighing in Mind for Workplace & In-the-Field Weighing

Designed with energy efficiency in mind, the Compass CX series offers a battery life of up to 1,000 continuous hours, allowing for uninterrupted operation. Featuring a slim, stackable and light-weight design, the CX fits ideally in lab, industrial, education, and even household settings. The streamlined two-button operation means that the balance can be operated easily, and large backlit LCD display enables easy viewing of weighing results.

- **Low Power Consumption Design Allows for Uninterrupted Operation** Designed with energy efficiency in mind, the Compass CX series features alkaline batteries capable of up to 1,000 hours of continuous use, providing peace of mind for daily weighing applications.
- **Improved Functionality with Large Backlit LCD and Two-Button Operation** Combined with a simplified two-button operation, the Compass CX's large backlit display increases readability in dim lighting conditions, and makes it easier to view results from a distance.
- **Practical Space-Saving Design for Convenient Storage** The Compass CX comes in an

ingenious space-saving design, which allows you to stack up to 4 scales to save storage space. Additionally, the CX features a standard stainless steel pan for durable use.

Other Standard Features and Equipment ABS housing, slip-resistant feet, stability indicator, mechanical and software overload/underload protection, low battery indicator, auto shut-off

Compliance

- Product Safety: IEC/EN 61010-1; CAN/CSA C22.2 No. 61010-1; UL Std. No. 61010-1
- Electromagnetic Compatibility: IEC/EN 61326-1 Class B, Basic environments; FCC Part 15 Class B; Canada ICES-003 Class B
- Compliance Marks: CE; RCM

Specifications

Model	CX-221 30428199	CX-621 30428200	CX-1201 30428201	CX-2200 30428202	CX-5200 30428203
Capacity x Readability	220 x 0.1 g	620 x 0.1 g	1200 x 0.1 g	2200 x 1 g	5200 x 1 g
Span					
Calibration					
Mass (Not Included)	200 g	500 g	1 kg	1 kg	2 kg
Stabilization Time (s)	1.5		2	1.5	
Construction	ABS housing and stainless steel pan				
Calibration	User-selectable external span / Digital with external weight				
Tare Range	Full capacity by subtraction				
Weighing Units	g, N, oz	g, N, oz, lb:oz			
Application Modes	Weighing				
Power Requirement	3 AA batteries (included) or AC adapter (not included)				
Typical Battery Life	1,000 hours				
Display Type	Liquid crystal display (LCD) with backlight				
Display Size	0.71 in. digits / 18 mm				
Pan Size (W x D)	5 in × 5.6 / 128 × 142 mm				
Balance					
Dimensions (W × D × H)	5.3 × 7.9 × 1.6 in. / 135 × 201 × 41 mm				
Shipping					
Dimensions (W × D × H)	6.7 × 9.3 × 2.2 in. / 170 × 235 × 55 mm				
Net Weight	1.1 lb / 0.51 kg				

**Shipping
Weight**

1.5 lb / 0.7 kg

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:(800)832-0055) or [\(718\)336-5900](tel:(718)336-5900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.