

Economical line of digital bench scales ideal for general weighing and simple counting applications in production, packaging, warehouse, inventory, shipping and receiving areas. Feature a simple, yet rugged, tubular-frame base design and indicators with t



**Capacity x
Readability**

Non Legal Mode:33
lb x 0.005 lb

Legal For Trade: 33
lb x 0.01 lb

Pan Size
12 x 14 in

Manufacture: Ohaus
SKU: D32XW15VR
Free Ground Shipping
within the 48 continental
US States



Legal for Trade

Please Call
(800)832-0055

Features

Designed with affordability in mind, but with no compromise on quality!

The OHAUS Defender™ 3000 Xtreme Series economy line of bench scales is ideal for general weighing and simple counting applications in wet or damp environments. The Defender 3000 Xtreme Series feature a simple, yet rugged, tubular-frame base design and indicators with tactile keys, backlit LCD display, built-in rechargeable battery operation and flexible mounting capabilities. The Defender 3000 Xtreme Series is the solution to your weighing applications that require dependability within an affordable budget.

Standard Features Include:

- Four capacity models: 60lb/30kg, 150lb/60kg, 300lb/150kg, and 600lb/300kg
- Maximum resolution 1:6000-7500d
- 3304 stainless steel pan with stainless steel frame and stainless steel IP67 load cell
- Indicator features a stainless steel housing with NEMA 4X / IP65 protection
- Adjustable non-slip rubber leveling feet with externally visible level indicator
- Multiple weighing units: lb, oz, lb:oz, kg, g
- Parts counting mode with selectable sample sizes, last sample size and average piece weight data
- 1-in/25mm high LCD weight display with high-contrast backlight
- Built-in RS232 for printing and data connection
- Internal universal switching power supply and 58-hour internal rechargeable battery included

Features

Stainless steel housing with backlit LCD weight display, tactile membrane switches, built-in bidirectional RS232C with manual/continuous/interval printing, hardware configuration lockout switch, internal universal switching power supply and internal sealed lead-acid rechargeable battery. Software included for parts counting mode with selectable sample sizes, selectable span calibration points, averaging level, auto-zero tracking, power saving auto-off, Geo Code geographical gravity calibration adjustment and software menu lockouts. Stainless steel pan with stainless steel tubular frame, non-slip rubber leveling feet with locking nuts, externally visible level bubble, stainless steel IP67 load cell, down-stops for overload protection, hollow tubular stainless steel columns

Compliance

- Safety and EMC: EN60950, EN61326, FCC Class A, CE (AC adapter), cULus
- Quality: OHAUS quality management system registered to ISO 9001:2008

Specifications

Model Number	D32XW15VR (30369114)	D32XW30VR (83999817)	D32XW60VR (83999818)	D32XW60VL (83999819)	D32XW150VL (83999820)	D32XW150VX (83999821)	D32XW300VX (83999822)
Capacity x Readability	33 x 0.005 lb 528 x 0.1 oz 15 x 0.002 kg 15000 x 2 g	60 x 0.01 lb 960 x 0.2 oz 30 x 0.005 kg 30000 x 5 g	150 x 0.02 lb 2400 x 0.5 oz 60 x 0.01 kg 60000 x 10 g	150 x 0.02 lb 2400 x 0.5 oz 60 x 0.01 kg 60000 x 10 g	300 x 0.05 lb 4800 x 1 oz 150 x 0.02 kg 150000 x 20 g	300 x 0.05 lb 150 x 0.02 kg 150,000 x 20 g 4,800 oz x 1 oz	600 x 0.1 lb 300 x 0.05 kg 300,000 x 50 g 9,600 x 0.2 oz
(lb:oz)	30 lb x 0.1 oz	60 lb x 0.2 oz	-	-	300 lb x 1 oz	300 lb x 1 oz	600 lb x 2 oz
Maximum Displayed Resolution	1:7500	1:6000	1:7500	1:7500	1:7500	1:7500	1:6000
Legal for Trade	NTEP Indicator: 08-066A1 Base: 08-021 Canada: Indicator AM-5713C Rec 1 Base: AM-5667						
Legal Capacity x Readability	33 X 0.01 lb 15 kg X 5 g	66 X 0.02 lb 30 kg X 10 g	132 X 0.05 lb 60 kg X 20 g	132 X 0.05 lb 60 kg X 20 g	330 X 0.1 lb 150 kg X 50 g	330 X 0.1 lb 150 kg X 50 g	660 X 0.2 lb 300 kg X 100 g
Approved Resolution	1:3000						
Scale Protection	NEMA 4X / IP65						
Base Construction	304 stainless steel pan with stainless steel frame, non-slip rubber leveling feet						
Platform Dimensions (WxDx min H)	12 x 14 x 4.8 in 305 x 355 x 123 mm			16.5 x 21.6 x 5.4 in 420 x 550 x 136 mm		19.7 x 25.6 x 5.8 in 500 x 650 x 147 mm	
Column	13.8 in / 350 mm fixed height, stainless steel			27.6 in / 700 mm fixed height, stainless steel			
Leveling Component	Externally visible level bubble and adjustable leveling feet with locking nuts						
Safe Overload Capacity	125% of rated capacity						
Indicator Construction	Stainless steel						
Weighing Units	lb, oz, lb:oz, kg, g						
Functions	Weighing, Parts Counting						

Weight Display	6-digit, 7-segment backlit LCD, 1 inch / 25 mm high digits			
Keyboard	4 function mechanical keys, raised, tactile			
Stabilization Time	Within 2 seconds			
Auto-zero Tracking	Off, 0.5, 1 or 3 divisions			
Key Zeroing Range	2% or 100% of capacity			
Span Calibration	5 lb/kg to 100% of capacity, user selectable			
Power	100 - 240 VAC/50-60 Hz internal switching power supply with internal rechargeable sealed lead-acid battery (58-hour typical operation with full charge)			
Interface	Bidirectional RS232C			
Operating Temperature Range	14°F to 104°F / -10°C to 40°C, Maximum relative humidity 80 % for temperatures up to 88°F / 31°C, decreasing linearly to 50 % relative humidity at 104°F / 40°C, non condensing			
Net Weight	33 lb 15 kg	53 lb 24 kg	60 lb 27 kg	84 lb 38 kg
Shipping Weight	41 lb 19 kg	61 lb 28 kg	67 lb 30 kg	96 lb 44 kg
Shipping Dimensions	25.3 x 19.6 x 8.5 in 642 x 497 x 212 mm	33.7 x 22.2 x 8.9 in 857 x 564 x 225 mm	40.2 x 27 x 9.7 in 1022 x 687 x 247 mm	

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
 - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.