

Explorer delivers accurate results within seconds, improving operator efficiency, productivity and throughput, with a stabilization time up to 50% faster. Features include Fast stabilization time - Intuitive SOFTWARE - Ingenious DRAFTSHIELD - Practical TOUCHLESS SENSORS - intelligent calibration and more


Capacity x Readability

Non Legal Mode: 10.2 kg x 0.1 g

Legal For Trade: 10.2 kg x 0.1 g

Pan Size

7.5 x 7.9 in

Manufacture: Ohaus

 SKU: **EX10201N**

UPC: B00BZBYIWO

Weight: 16.00 lb

Free Ground Shipping within the 48 continental US States



Legal for Trade

Please Call (800)832-0055

Features

Explorer delivers accurate results within seconds, improving operator efficiency, productivity and throughput, with a stabilization time up to 50% faster.

- Fast stabilization time
 - Improves operational efficiency
 - Increases throughput
 - Improves productivity
- Optimized linearity and repeatability specifications
 - Provides accurate and repetitive results
- Superior vibration filtering
 - Provides balance stability in unstable environments

Intuitive SOFTWARE

SmarText™ 2.0 is OHAUS' easy-to-use graphical software featuring 14 applications, QWERTY and numeric keypads, and below-minimum weight indication.

- Color VGA display with icons for simple menu navigation
 - High resolution, 5.7 in (145 mm) color TFT display reproduces highly readable operating software
 - Resistive touch screen display quickly responds to operator's touch or stylus
- 14 built-in applications with customization capabilities to meet the varying needs in laboratory and industrial settings
- Minimum Weight capability with visual warning feature
- QWERTY keyboard and numeric keypad to quickly input GLP and GMP data and other application data • User Manager with administrator capability
- Library function to store and recall customized applications
- Alternate RS232 command feature adapts the balance to existing data acquisition software
- External input for zero, tare or print operations via the external foot switch accessory
- Audible and visual feedback for button presses as well as the indication of the check weighing status

The all-new Explorer® Series of Analytical and Precision balances — a product so extraordinary, it's like nothing you've seen before!

Ingenious DRAFTSHIELD

Explorer's draftshield provides ample access and visibility to the weighing chamber and features antistatic coated glass

- Frameless, flip-top design provides unobstructed access to the weighing chamber
- The expansive side entry 6.3 x 9.4 in (160mm x 240mm) allows you to freely place and remove large weigh boats or other large vessels in the weighing chamber
- Antistatic coated glass helps dissipate static charges in the weighing chamber that could adversely affect the weighing results
- Side doors seamlessly glide on top-mounted bearings, helping to prevent any potential bind up when balance is left uncleaned
- Easy to install and remove glass panels and a stainless steel bottom make Explorer extremely easy to clean
- A draftshield chamber light is available when the balance is used in low-lighting environments

Practical TOUCHLESS SENSORS

Explorer features four touchless sensors for hands-free operation of print, calibration, tare, and other selectable functions

- Hands-free operation
 - Improves weighing efficiency
 - Eliminates sample residue transfer
 - Minimizes contamination
- Two sensors on the base and two on the display can be set up individually to allow for remote operations

Completely re-imagined from the ground up, the OHAUS Explorer® rises to a whole new level.

Intelligent calibration

AutoCal™ ensures performance and assists with routine maintenance by automatically calibrating the balance daily

- Fully-automatic internal calibration system
- No need for external masses
- Eliminates cost to maintain external weights
- Self-calibrates the system when it senses a temperature change sufficient enough to affect weighing accuracy, or every 11 hours

Intuitive user setup

Explorer is the industry's most easy-to-use balance, featuring leveling assistance and instructional messaging for quick out-of-the-box setup and use.

- Easy to view illuminated level indicator placed at the front of the balance

- The Explorer® is a revolutionary shift in the way users interact and operate a weighing instrument, all based on our ingeniously practical design philosophy

Explorer's modular design features a color touch display that can be separated from the weighing base.

- ## Practical approvals*

Explorer is designed and engineered to meet stringent NTEP requirements for use in legal applications such as pharmacies, jewelry stores and retail outlets. The Explorer has been designed to meet or exceed the Class I and II accuracy requirements in accordance with the National Institute of Standards and Technology (NIST) Handbook 44. In addition to being designed to meet or exceed the Class I and II accuracy requirements for a prescription balance, the Explorer will also be approved for Counting for Prescription Filling. Explorer will make it easy to comply with the regulations requiring that an approved balance be installed in every operating pharmacy.

Other Standard Features & Equipment:

Menu lock switch, security bracket, integral weigh below hook for below balance weighing applications, removable stainless steel weighing platform, stability indicator, overload and underload indicators, auto standby, powered by an ENERGY STAR® qualified adapter for a better environment.

Applications

The OHAUS Explorer's advanced applications simplify even the most complex laboratory measurements. Whether it's determining the difference between initial and residual weights or calculating the density of solids and liquids, Explorer eliminates the need for time-consuming manual calculations and data logging. The high resolution display and innovative user interface make balance setup and application use effortless.

- **Weighting** - Determine the weight of items in the selected unit of measure. Minimum Weight feature is also available.
- **Percent Weighting** - Measure the weight of a sample displayed as a percentage of a pre-established Reference Weight
- **Dynamic Weighting** - Weigh an unstable load. Balance takes an average of weights over a time period.
- **Totalization** - Measure cumulative weight of multiple items. Cumulative total may exceed Balance capacity
- **Differential Weighting** - Store sample weights and calculate the difference between initial weights and final weights
- **Peak Hold** - Capture and store highest weight in a series. Both stable and unstable weights are captured
- **Parts Counting** - Count samples of uniform weight. Choose Standard Counting, Check Counting, or Fill Counting
- **Pipette Adjustment** - Check pipette values by weight analysis, with built-in water density table
- **Check Weighting** - Compare the weight of a sample against target limits. Choose from Standard, Nominal-weight, or Nominal-Percent
- **Filling** - Fill a container to a target weight. Progress bar displays filling status
- **Formulation** - For compounding and recipe making. The number of components can be from two to 99.
- **Density Determination** - Determine density of solids more dense than water, solids less dense than water, liquids, or porous material.
- **Ingredient Costing** - Determine cost of formula or recipe based on known cost/quantity of components or ingredients.
- **SQC** - Monitor and/or control processes to eliminate under and over filling.

Specifications

Model	EX124	EX224	EX324	EX223	EX423	EX623	EX1103	EX2202	EX4202	EX6202	EX10202	EX6201	EX10201	EX12001	EX24001	EX36001	
Automatic Door	EX124/AD	EX224/AD	EX324/AD	-	-	-	-	-	-	-	-	-	-	-	-	-	
External Calibration	-	-	-	EX223/E	EX423/E	-	-	EX2202/E	EX4202/E	EX6202/E	-	EX6201/E	-	-	-	-	
Certified Models	EX124N/AD	EX224N EX224N/AD	EX324N EX324N/AD	-	EX423N	-	EX1103N	-	EX4202/E	-	EX10202N	-	EX10201N	-	-	-	
Capacity (g)	120	220	320	220	420	620	1100	2200	4200	6200	10200	6200	10200	12000	24000	35000	
Readability (g)	0.0001			0.001				0.01				0.1					
Repeatability std (g)	±0.0001			±0.001				±0.01				±0.1					
Linearity (g)	±0.0002			±0.002				±0.02				±0.2					
Stabilization Time (sec)																	
Pan Size	Ø 3.5 in / 90 mm			Ø 3.5 in / 90 mm				7.5 x 7.9 in / 190 x 200 mm						14.84 × 12.24 in / 377 × 311 mm			
Weighing Applications	Weighing, Percent Weighing, Parts Counting, Check Weighing, Dynamic/Animal Weighing, Filling, Totalization, Formulation, Differential Weighing, Density Determination, Peak Hold, Ingredient Costing, Pipette Adjustment, SQC																
Weighing Units	Gram, Milligram, Kilogram, Carat, Ounce, Ounce Troy, Pound, Pennyweight, Grain, Newton, Momme, Mesghal, Hong Kong Tael, Singapore Tael, Taiwan Tael, Tical, Tola, Baht, 3 Custom Units																
Calibration	AutoCal™ on 5°C temperature change, 11 hours, and external calibration																
Tare Range	To capacity by subtraction																
Power Requirements	AC adapter input: 100-240 VAC 0.6A 50-60 Hz																
Display Type	Full-color VGA graphic display, 4-wire resistive touch screen																
Display Size	5.7 in / 145 mm (diagonal)																
Display Housing Dimensions (W x H x D)	7.7 x 3.5 x 6.0 in / 195 x 90 x 154 mm																
Base Housing Dimensions (W x H x D)	9.1 x 13.8 x 15.5 in / 230 x 350 x 393 mm							9.1 x 3.9 x 15.5 in / 230 x 98 x 393 mm						14.84 × 4.72 × 17.44 in / 377 × 120 × 443 mm			
Communication	Standard RS232, USB, Optional Ethernet or 2nd RS232																
Operating Temperature Range	50°F (10°C) to 86°F (30°C)																

Operating Humidity Range	80% max up to 86°F/30°C decreasing linearly to 50% at 104°F/40°C, non-condensing			
Storage Conditions	-14°F (-10°C) to 140°F (60°C) at 10% to 90% relative humidity, non-condensing			
Net Weight	15.2 lb / 6.9 kg	9.5 lb / 4.3 kg	11 lb / 5 kg	22 lb / 10 kg
Shipping Weight	21.1 lb / 9.6 kg	15 lb / 6.8 kg	16.3 lb / 7.4 kg	25.8 lb / 12.5 kg
Shipping Dimensions	21 x 15 x 21 in / 55 x 38.5 x 55.1 cm	21 x 15 x 12 in / 55 x 38.5 x 29.1 cm		26.18 x 20.67 x 13.00 in / 665 x 525 x 330 mm

Dimensions

i81u812

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.