

Frontier rotors extend the functionality of Frontier centrifuges by increasing the number of tubes of varied types and sizes that can be used in conjunction with each of the centrifuge models. Easy to clean and operate, the rotors are durably constructed to withstand demanding centrifugation



## **Features**

Frontier rotors extend the functionality of Frontier centrifuges by increasing the number of tubes of varied types and sizes that can be used in conjunction with each of the centrifuge models. Easy to clean and operate, the rotors are durably constructed to withstand demanding centrifugation.

Maximum Capacity (Rotor)	8 x 1.5 / 2.0 ml
Maximum Relative Centrifuge Force (x g	2,560 g
Net Weight	38.8 g (0.08 lb)
Maximum Speed	6,000 rpm
Outer/Inner Radius	4.5 cm
Rotor Style	Angel
Aerosol tight	Not applicable
Maximum loading height	45 mm
Maximum loading weight	27 g
Acceleration Time(sec)	2/2
Angle	45°
Deceleration Time(sec)	2/2

Dimensions (Width)	9.0 cm (3.54 in)
Dimensions (Height)	2.4 cm (0.94 in)
Dimensions (Length)	9.0 cm (3.54 in)
Tube diameter without adapter	12 mm / 2.0 ml,1.5 ml
Working Environment	5°C – 40°C, 80%RH, non-condensing
Multiple Maximum Speeds	No

i81u812

