

The PR is equipped with 3 essential weighing modes, RS-232 connectivity for data transfer and storage, and internal calibration (in select models), making it ideal for routine weighing applications Ohaus PR124/E - Analytical Balance with External Calibration 120 g x 0.1 mg



**Capacity x  
Readability**

120 g x 0.1 mg

**Pan Size**

90 mm (Diameter)

Manufacture: Ohaus

SKU: 30529066

Weight: 16.00 lb

Free Ground Shipping  
within the 48 continental  
US States

**Please Call  
(800)832-0055**

## Features

### Designed for Routine Weighing Applications in Your Workplace

The PR is equipped with 3 essential weighing modes, RS-232 connectivity for data transfer and storage, and internal calibration (in select models), making it ideal for routine weighing applications

Equipped with an easy-to-read, bright backlit display and a simple user interface, the PR is incredibly easy to operate, with almost no training required.

The PR's small footprint saves desktop space while providing a large weighing surface. The PR is durably constructed, and features a stainless steel pan to withstand day-to-day use in the workplace.

- **Applications** Basic Weighing, Parts Counting, Percent Weighing
- **Display** Backlit liquid crystal display (LCD)
- **Operation** AC adapter (included)
- **Construction** ABS top housing, removable stainless steel pan, removable glass draftshield with sliding top door, integrated weigh-below-hook, security bracket, calibration lock
- **Design Features** User-selectable environmental filters and brightness settings, auto-tare, auto-dim, user-selectable span calibration points, software lockout and reset menu, user-selectable communication settings and data print options, user-definable project and user IDs, software overload/underload indicator, stability indicator

## Specifications

<b>Model</b>	<b>PR64/E</b>	<b>PR124/E</b>	<b>PR224/E</b>	<b>PR223/E</b>	<b>PR523/E</b>	<b>PR1602/E</b>	<b>PR2202/E</b>	<b>PR4202/E</b>	<b>PR2201/E</b>	<b>PR4201/E</b>
	<b>30430060</b>	<b>30529066</b>	<b>30430062</b>	<b>30529239</b>	<b>30430063</b>	<b>30529067</b>	<b>30430064</b>	<b>30430065</b>	<b>30529238</b>	<b>30430066</b>

Model with InCal	PR124		PR224		30529065 30430061					
<b>Standard Capacity x Readability</b>	62 g x 0.1 mg	120 g x 0.1 mg	220 g x 0.1 mg	220 g x 1 mg	520 g x 1 mg	1600 x 0.01 g	2200 x 0.01 g	4200 x 0.01 g	2200 x 0.1g	4200 x 0.1g
<b>Pan Size</b>	Ø 3.54 in. / 90 mm			Ø 4.72 in. / 120 mm		Ø 7.09 in. / 180 mm				
<b>Stabilization Time (s)</b>	2					1				
<b>Units</b>	g, mg, ct, dwt, grain, oz, ozt					g, kg, ct, dwt, grain, oz, ozt, lb				
<b>modes</b>	Basic Weighing, Parts Counting, Percent Weighing									
<b>Draftshield Size</b>	6.8 x 5.1 x 8.1 in. / 172 x 131 x 205 mm					N/A				
<b>Power Supply</b>	Power input: 100–240V ~ 200mA 50–60Hz 12–18VA Power output: 12 VDC 0.5A									
<b>Overall Dimensions (W x D x H)</b>	7.9 x 12.5 x 11.9 in. / 201 x 317 x 303 mm					7.9 x 12.5 x 3.7 in. / 201 x 317 x 93 mm				
<b>Operating Conditions</b>	50°F to 86°F / 10°C to 30°C									
<b>Storage Conditions</b>	14°F to 140°F / -10°C to 60°C at 10% to 90% relative humidity, non-condensing									
<b>Net Weight</b>	10 lb / 4.5 kg					7.7 lb / 3.5 kg				
<b>Shipping Weight</b>	15.4 lb / 7 kg					11 lb / 5 kg				
<b>Shipping Dimensions (W x D x H)</b>	20 x 15 x 21 in. / 507 x 385 x 531 mm					21.5 x 15 x 11.5 in. / 550 x 385 x 291 mm				

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.