

Ohaus PX4201 - Pioneer PX Precision Balance with Internal Calibration 4200 x 0.1 g

The OHAUS Pioneer Series of analytical and precision balances (Internal and Extenal Calibration models) are designed for basic routine weighing in a variety of laboratory, industrial and education applications. With the right combination of performance and features, the OHAUS Pioneer offers uncomplicated performance for all your basic weighing needs.





Capacity x Readability 4200 g x 0.1 g Pan Size 7.09 in

Manufature: Ohaus SKU: PX4201 Weight: 11.00 lb Free Ground Shipping within the 48 continental US States

Please Call (800)832-0055

Features

The new Ohaus Pioneer PX series Laboratory Balances is the latest addition of Ohauss Laboratory Scales. Ohaus to the existing Pioneer Plus series and simply gave it a modern upgrade. They took all the wonderful Features and made them better.

The Best Balance For Basic Weighing!

The OHAUS Pioneer Series of analytical and precision balances are designed for basic routine weighing in a variety of laboratory, industrial and education applications. Now with both internal and external calibration models and the right combination of performance and features, the OHAUS Pioneer offers uncomplicated performance for all your basic weighing needs.

Standard Features Include:

- Easy to Clean Analytical Draftshield Pioneers draftshield is designed with all glass panels, including three sliding doors. All panels are easy to remove and replace, and together with a stainless steel bottom, make it fast and easy to clean.
- Upfront Level Indicator Pioneer has been designed with an up-front level indicator, so that users can
 quickly ensure the balance is level prior to use
- Bright Backlit Display The bright backlit LCD display is easy-to-view in any environment.
- Selectable Environmental Settings Three filter modes and adjustable zero tracking adjust balance

sensitivity to environmental disturbances, or application requirements.

Removable Doors Provide Convenient Access and Easy Cleaning

To address the ease of cleaning requirement often expressed by routine users, Pioneers draftshield has been designed with easy to remove doors and panels. Disassembly takes just seconds and all components including the balance housing can be quickly wiped clean. Periodic cleaning made easy helps avoid sample contamination and extends product life. In addition, a standard in-use cover provides added protection against accidental spillage and helps minimize the chance of damage to the display and keypad. Should breakage occur, each replacement door or panel can be installed in seconds.

Backlit Display Bolsters Visibility

The bright backlit LCD display provides ample lighting, making the display very easy-to-view in laboratories with dim lighting

Selectable Environmental Settings For Working in Practically Any Condition

To help adapt the balance to real life working conditions, Pioneer is designed with selectable environmental settings. When working in harsh environments, the balance can be adjusted to compensate for vibrations and other disturbances. Conversely, the balance can be adjusted for working in slow filling applications where sensitivity is a must.

Standard Features:

- Integral Security Bracket: Allows you to secure your balance to a workstation to prevent unwarranted movement or theft
- RS232 Interface: Pioneers RS232 allows connection to an Ohaus printer or a computer. Sends Balance ID plus spaces for recording User ID, Project ID, time and date
- Integral Menu Lock: A combination of software and a mechanical switch locks menus, including calibration
- Weigh-Below Hook: Pioneers built-in weigh-below hook allows you to suspend an item below the balance to calculate density/specific gravity
- Up-Front Level Indicator: A quick glance at the up-front level indicator helps to ensure that the balance is level prior to each use
- Multiple Application Modes and Units: Pioneer features basic weighing, parts counting and percent weighing, density weighing, and dynamic weighing and 15 international weighing units including one custom unit
- Backlit Display: Enables optimal viewing of results in various lighting conditions

Specifications

Interface

RS232, USB

Model with Internal Calibration	PX1602 30430055	PX2202 30429841	PX3202 30429842	PX4202 30429843	PX6202 30699094	PX2201 30430056	PX4201 30429844	PX1200 3086807
Model with External Calibration	PX1602/E 30430058			PX4202/E 30429852		PX2201/E 30430059	PX4201/E 30429853	PX12001 3086807
Capacity x Resolution	1600 x 0.01 g		3200 x 0.01 g	4200 x 0.01 g		2200 x 0.1 g	4200 x 0.1 g	12000 x 0.1 g
Stabilization Time (s)	1 s							
Linearity (<u>+g</u>)	0.02 g					0.2 g		
Linearity (<u>+g</u>)	0.01 g					0.1 g		
Pan Diameter (in / mm)	7.09 in / 180 mm							7.6 x 9.8
Draft Shield	-	-	-	-	-	-	-	-
Warranty	2 Years							

Milligram, Gram, Kilogram, Ounce, Pound, Carat, Pennyweight, Ounce Troy, Grain, Units Newton, Hong Kong Tael, Singapore Tael, Taiwan Tael, Momme, Tical (MM), Mesghal,

Tola (India), 1 custom unit

Product Length x Width x Height

12.6 x 8.2 x 3.9 in

12.6 x 8. x 4 in

Shipping weight (lbs)

11 lb

Power

Input Voltage (VAC) 100-240 V Frequency: 50-60 Hz

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

Phone: <u>(800)832-0055</u> or <u>(718)336-5900</u> Chat with us via WhatsApp Chat

Address: 4802 Glenwood Rd. Brooklyn, NY 11234

© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.