

Starter pen meters provide what should be expected of a small, economical pen meter: simple, fast, straightforward, no-frills operation time and time again. With durable ABS housing, a protective sensor cap, and automatic shutdown feature that preserves battery life, Starter pen meters can endure consistent use in rugged environments.



Manufacture: Ohaus

SKU: 30073971

UPC:

B00YGNDFA4

Weight: 2.00 lb

Free Ground Shipping
within the 48
continental US States

Please Call
(800)832-0055

Features

Accurate Electrochemistry Measurement At Your Fingertips

Starter pen meters provide what should be expected of a small, economical pen meter: simple, fast, straightforward, no-frills operation time and time again. With durable ABS housing, a protective sensor cap, and automatic shutdown feature that preserves battery life, Starter pen meters can endure consistent use in rugged environments.

Equipped with a wrist strap that prevents unintentional dropping, Starter pen meters are feature an IP67 waterproof design that can prevent water damage when dropped in to liquid. After more than a century of perfecting the art of measurement through our durable weighing products, OHAUS precision is now available in a line of pen meters that provide accurate measurement of pH, oxidation-reduction potential (ORP), conductivity, salinity, and total dissolved solids (TDS). Starter pen meters are the economical option when you are simply looking for meters that will provide accurate measurement without restriction.

Convenient pH Testing

The ST20 offers a convenient way to measure pH, or the relative acidity or alkalinity of a sample at a given temperature. The pH pen meter can be completely operated with just one hand, freeing up your other hand to handle samples.

| Model | ST20 | ST10 |
|--------------------------|----------------------|----------------------|
| Range | 0.00 - 14.00 | 0.0 - 14.0 |
| Resolution | 0.01 pH | 0.1 pH |
| Accuracy | 0.05 pH | 0.1 pH |
| Temperature Range | 0.0-99°C | N/A |
| Temperature Compensation | Yes | N/A |
| Display | Dual | Single |
| Calibration | 3 Point | N/A |
| Buffer Group | 4.01 | N/A |
| | 7.00 | |
| | 10.01 | |
| Automatic Shutdown | 6 Minutes of Non-Use | 6 Minutes of Non-Use |
| Battery | 4 AG13 1.5V | 4 AG13 1.5V |
| | Micro Alkaline | Micro Alkaline |
| | Batteries | Batteries |
| Size/Weight | 185 x 45 x 38 mm | 185 x 45 x 38 mm |
| | 110g | 110g |

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.