

Starter pen meters provide what should be expected of a small, economical pen meter: simple, fast, straightforward, no-frills operation time and time again. With durable ABS housing, a protective sensor cap, and automatic shutdown feature that preserves battery life, Starter pen meters can endure consistent use in rugged environments.



Manufacture: Ohaus
SKU: **30073975**
UPC: B00YGN2WCQ
Weight: 2.00 lb
**Free Ground
Shipping within the
48 continental US
States**

**Please Call
(800)832-0055**

Features

Accurate Electrochemistry Measurement At Your Fingertips

Starter pen meters provide what should be expected of a small, economical pen meter: simple, fast, straightforward, no-frills operation time and time again. With durable ABS housing, a protective sensor cap, and automatic shutdown feature that preserves battery life, Starter pen meters can endure consistent use in rugged environments.

Equipped with a wrist strap that prevents unintentional dropping, Starter pen meters are feature an IP67 waterproof design that can prevent water damage when dropped in to liquid. After more than a century of perfecting the art of measurement through our durable weighing products, OHAUS precision is now available in a line of pen meters that provide accurate measurement of pH, oxidation-reduction potential (ORP), conductivity, salinity, and total dissolved solids (TDS). Starter pen meters are the economical option when you are simply looking for meters that will provide accurate measurement without restriction.

Small but Productive Conductivity Meters

Starter pen meters are the choice for basic testing needs of the total ionic concentration within a solution. With six models that can measure within three different conductivity ranges, there is a Starter conductivity meter for every application that requires portable operation and quick results.

Model	ST20C-C	ST20C-B	ST20C-A
Range	0.00 - 19.99 ms/cm	0 - 1999 μ s/cm	0.0 - 199.9 μ s/cm
Resolution	10 μ s/cm	1 μ s/cm	0.1 μ s/cm
Accuracy	\pm 1.5% FS	\pm 1.5% FS	\pm 1.5% FS
ATC	With Temperature Display	With Temperature Display	With Temperature Display
Display	Dual	Dual	Dual
Automatic Shutdown	6 minutes of Non-Use	6 minutes of Non-Use	6 minutes of Non-Use
Battery	4 AG13 1.5V Micro Alkaline Battery	4 AG13 1.5V Micro Alkaline Battery	4 AG13 1.5V Micro Alkaline Battery

Size/Weight	185 x 45 x 38 mm 110g	185 x 45 x 38 mm 110g	185 x 45 x 38 mm 110g
--------------------	--------------------------	--------------------------	--------------------------

Model	ST10C-C	ST10C-B	ST10C-A
Range	0.00 - 19.99 ms/cm	0 - 1999 µs/cm	0.0 - 199.9 µs/cm
Resolution	10 µs/cm	1 µs/cm	0.1 µs/cm
Accuracy	± 2.5% FS	± 2.5% FS	± 2.5% FS
ATC	Without Temperature Display	Without Temperature Display	Without Temperature Display
Display	Single	Single	Single
Automatic Shutdown	6 minutes of Non-Use	6 minutes of Non-Use	6 minutes of Non-Use
Battery	4 AG13 1.5V Micro Alkaline Battery	4 AG13 1.5V Micro Alkaline Battery	4 AG13 1.5V Micro Alkaline Battery
Size/Weight	185 x 45 x 38 mm 110g	185 x 45 x 38 mm 110g	185 x 45 x 38 mm 110g

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:(800)832-0055) or [\(718\)336-5900](tel:(718)336-5900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.