

Ideal for laboratory and industrial applications, the OHAUS Scout comes in a slim, stackable design with large backlit LCD. Features include superior overload protection, multiple weighing units and application modes. Geared for high performance in your facility with fast stabilization time and high resolution weighing results, these portable balances set a new standard in laboratory and industrial weighing





Please Call (800)832-0055

Features

Setting New Standards in Laboratory & Industrial Weighing — The Next Generation of Scout Balances

Ideal for laboratory and industrial applications, the OHAUS Scout comes in a slim, stackable design with large backlit LCD. Features include superior overload protection, multiple weighing units and application modes. Geared for high performance in your facility with fast stabilization time and high resolution weighing results, these portable balances set a new standard in laboratory and industrial weighing

Standard Features Include:

- Bright Backlit LCD & 4 Button Control Enable Efficient Operation and Ease of Use Combined with a simplified 4 button operation, the Scout's large backlit display increases readability in low light working conditions, and is easier to view from a distance.
- Bolstered by Superior Overload Protection and Impact-Resistant Pan Support Integrated superior overload protection and impact-resistant pan support safeguard against shock and overloading the balance in rugged and demanding environments.
- Better Performance and Higher Capacities Widen the Range of Weighing Applications Stabilization time as fast as 1 sec and advanced weighing technology, lead to improved productivity in your facility. Increased capacity unlocks a wider range of weighing applications.

Improved Experience with Backlit Display and 4 Button Operation

Poor lighting environment is not an issue with the Sout. The large, bright backlit LCD display improves readability in conditions where lighting is poor, and makes it easy to see the results from a distance. 4 clearly marked buttons remove complexity, and guide you quickly and easily through setup, unit of measure changes, calibration and more

Durability Guaranteed with Superior Protective Features

The Scout equipped with superior overload protection rated at 10 times the capacity of the balance, high strength stainless steel pan, impact-resistant pan support and integrated transportation/storage lock, delivers the same durable quality that you expect from OHAUS products. To complement our signature durability, we've designed the Scout to be stackable when utilizing the optional stacking and storage cover, which also protects the balance when not in use.

Most Versatile Portable Balance in its Class

With the Scout, it's all about accuracy, efficiency and possibilities! Stabilization time as fast as 1 sec means increased productivity in any facility or lab. With improved resolution, you can count on extremely precise and repeatable weighing results. Additionally, the increased capacity of the Scout gives you more flexibility in your weighing applications.

Draftshield Model Available (SPX123) Scout's ingenious draftshield (1mg models only) was designed with an easy to remove top cover piece. This serves as a wind protection ring which keeps the weighing surface stable in rough environments, while maintaining weighing speed.

Built-in Application Modes

- Weighing Determines the weight of items on the pan in the selected unit of measure.
- Parts Counting Counts the number of pieces on the pan using a uniform weight.
- Percent Weighing Measures the weight of a sample displayed as a percentage of a pre-established reference weight.
- Check Weighing Compares the weight of a sample against target limits.
 Totalization Measures cumulative weight of multiple items. Cumulative total may exceed balance capacity.
- Display Hold Manually holds the last stable weight or the first highest stable weighing value on the display.

Specifications

Model	SPX123	SPX223	SPX222	SPX422	SPX622	SPX1202	SPX2202	SPX421	SPX621	SPX2201	SPX6201	SP
Capacity X Readability (g)	120 x 0.001	220 x 0.001	220 x 0.01	420 x 0.01	620 x 0.01	1200 x 0.01	2200 x 0.01	420 x 0.1	620 x 0.1	2200 x 0.1	6200 x 0.1	82
Repeatability (Std. Dev.) (g)	0.00	02		0.01		0.0	02		0	.1		

Linearity (g)	+/-0.003		±0.01		±0.02	±0.03		±0.1			±0.2	
Capacity X Readability (kg)	-	-	-	-	-	1.2 x 0.00001 kg	2.2 x 0.00001 kg	-	-	2.2 x 0.0001 kg	6.2 x 0.0001 kg	8.2
Capacity × Readability (lb)	-	-	-	-	1.36690 x 0.00005 lb	2.64555 x 0.00005 lb	4.85020 x 0.00005 lb	-	1.3670 x 0.0005 lb	4.8500 x 0.0005 lb	13.6685 x 0.0005 lb	18 0.
Span Calibration Mass*	100 g	200 g	200 g	200 g	300 g	1 kg	2 kg	200 g	300 g	2 kg	5 kg	
Linearity Calibration Mass*	50, 100 g	100, 200 g	100, 200 g	200, 400 g	300, 600 g	500g, 1 kg	1 kg, 2 kg	200, 400 g	300, 600 g	1 kg, 2 kg	3 kg, 5 kg	4 k
Stabilization Time (s)	1.5	1.5	1	1	1	1.5	1.5	1	1	1	1	
Construction	ABS housing & stainless steel pan											
Draftshield	Y	es			No							
Calibration	User-selectable external span or linearity calibration/Digital with external weight											
Tare Range	Full capacity by subtraction											
Weighing Units	g, kg, ct, N, oz, ozt, dwt, lb, lb:oz, grn											
Application Modes	Weighing, Parts Counting, Percent Weighing, Check Weighing, Totalization, Display Hold											
Power Requirements	AC adapter (included) or 4 AA batteries (not included)											
Typical Battery Life (Hours)	80		120		8	30		120			80	
Communication	Available as an accessory:RS232, USB Host, USB Device, Ethernet or Bluetooth®											
Display Type	Liquid crystal display (LCD) with backlight											
Display Size	0.78 in/20 mm digits											
Overload Capacity	10 times rated capacity											
Operating Temperature Range	50°F / 10°C to 104°F / 40°C at 10% to 85% relative humidity, non-condensing											
Storage Conditions	-20°C (-4°F) to 55°C (131°F) at 10% to 90% relative humidity, non-condensing											
Pan Size (W × D)	3.7in 93 mm diameter		12	4.7in 120 mm diameter			0.7 X 5.5 m 170 × 140 mm 120		120 mm		6.7 x 5.5 in 170 × 140 mm	
Dimensions W x H x D	8 × 8.7 × 4.1 in 8 × 8.8 × 2.1 in 202 × 222 × 103 mm 202 × 224 × 54 mm											
Dimensions W x H x D	11.8 × 9.8 × 5.1 in11.8 × 9.8 × 3.4 in300 × 250 × 129 mm300 × 250 × 86 mm											
Net Weight	1 kg											
Shipping Weight	1.5 kg											
* Calibration weights are inc	ludod with n	adale un ta 6	20a canacit									

* Calibration weights are included with models up to 620g capacity.

Other Standard Features and Equipment

Transportation lock, stainless steel pan, menu & calibration lockout switch, slip-resistant and adjustable feet, leveling bubble, mechanical and software overload/underload protection, stability indicator, auto tare, low battery indicator, auto shut-off, user selectable printing options, user selectable communication settings

Compliance
 Product Safety: IEC/EN 61010-1; CAN/CSA C22.2 No. 61010-1; UL Std. No. 61010-1
 Electromagnetic Compatibility: IEC/EN 61326-1 Class B; FCC Part 15 Class B; Industry Canada ICES-003 Class B

*Volume Discounts Available We Accept Educational Institutes Purchase Orders Email Us or Call 800-832-0055 Accessories

- RS232 Interface Kit 30268982
 USB Host Interface Kit 30268983
 USB Device Interface Kit 30268984

- USB Device Interface Kit 30268984
 Bluetooth Interface Kit 30268985
 Ethernet Interface Kit 30268986
 Stacking & Storage Cover (6 pcs) 30268987
 Stacking & Storage Cover (1 pc) 30268988
 Printer, Impact, SF40A, AM. 30064203
 Auxiliary Display Kit 30269019
 Security Device 80850043
 Top Loading Kit for Density Determination 30269020
 Carrying Case 30269021
 In-use Cover 30269022

i81u812



Phone: (800)832-0055 or (718)336-5900 Chat with us via <u>WhatsApp Chat</u> Address: 4802 Glenwood Rd. Brooklyn, NY 11234 © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.