



Ideal for laboratory and industrial applications, the OHAUS Scout comes in a slim, stackable design with large backlit LCD. Features include superior overload protection, multiple weighing units and application modes. Geared for high performance in your facility with fast stabilization time and high resolution weighing results, these portable balances set a new standard in laboratory and industrial weighing





Capacity x Readability 420 g x 0.01 g Pan Size 4.7 in (Diameter)

Manufature: Ohaus SKU: 30253020 UPC: B01AJ08BY2 Weight: 4.00 lb Free Ground Shipping within the 48 continental US States

> Please Call (800)832-0055

> > 82

Features

Setting New Standards in Laboratory & Industrial Weighing — The Next Generation of Scout Balances

Ideal for laboratory and industrial applications, the OHAUS Scout comes in a slim, stackable design with large backlit LCD. Features include superior overload protection, multiple weighing units and application modes. Geared for high performance in your facility with fast stabilization time and high resolution weighing results, these portable balances set a new standard in laboratory and industrial weighing

Standard Features Include:

- Bright Backlit LCD & 4 Button Control Enable Efficient Operation and Ease of Use Combined with a simplified 4 button operation, the Scout's large backlit display increases readability in low light working conditions, and is easier to view from a distance.
- Boistered by Superior Overload Protection and Impact-Resistant Pan Support Integrated superior overload protection and impact-resistant pan support safeguard against shock and overloading the balance in rugged and demanding environments.
- Better Performance and Higher Capacities Widen the Range of Weighing Applications Stabilization time as fast as 1 sec and advanced weighing technology, lead to improved productivity in your facility. Increased capacity unlocks a wider range of weighing applications.

Improved Experience with Backlit Display and 4 Button Operation

Poor lighting environment is not an issue with the Scout. The large, bright backlit LCD display improves readability in conditions where lighting is poor, and makes it easy to see the results from a distance. 4 clearly marked buttons remove complexity, and guide you quickly and easily through setup, unit of measure changes, calibration and more

Durability Guaranteed with Superior Protective Features

The Scout equipped with superior overload protection rated at 10 times the capacity of the balance, high strength stainless steel pan, impact-resistant pan support and integrated transportation/storage lock, delivers the same durable quality that you expect from OHAUS products. To complement our signature durability, we've designed the Scout to be stackable when utilizing the optional stacking and storage cover, which also protects the balance when not in use.

Most Versatile Portable Balance in its Class

With the Scout, it's all about accuracy, efficiency and possibilities! Stabilization time as fast as 1 sec means increased productivity in any facility or lab. With improved resolution, you can count on extremely precise and repeatable weighing results. Additionally, the increased capacity of the Scout gives you more flexibility in your weighing applications.

Draftshield Model Available (SPX123) Scout's ingenious draftshield (1mg models only) was designed with an easy to remove top cover piece. This serves as a wind protection ring which keeps the weighing surface stable in rough environments, while maintaining weighing speed.

Built-in Application Modes

- Weighing Determines the weight of items on the pan in the selected unit of measure.
- Parts Counting Counts the number of pieces on the pan using a uniform weight.
- Percent Weighting Measures the weight of a sample displayed as a percentage of a pre-established reference weight.
- Check Weighing Compares the weight of a sample against target limits.
 Totalization Measures cumulative weight of multiple items. Cumulative total may exceed balance capacity.
- Display Hold Manually holds the last stable weight or the first highest stable weighing value on the display.

Specifications

Model	SPX123	SPX223	SPX222	SPX422	SPX622	SPX1202	SPX2202	SPX421	SPX621	SPX2201	SPX6201	s
Capacity X Readability	120 x 0.001	220 x 0.001	220 x 0.01	420 x 0.01	620 x 0.01	1200 x 0.01	2200 x 0.01	420 x 0.1	620 x 0.1	2200 x 0.1	6200 x 0.1	8

Repeatability (Std. Dev.) 0.01 0.002 0.02 0.1 (g)

Linearity (g)	+/-0.003		±0.01		±0.02	±0.03		±0.1			±0.2	
Capacity X Readability (kg)					-	1.2 x 0.00001 kg	2.2 x 0.00001 kg	-	-	2.2 x 0.0001 kg	6.2 x 0.0001 kg	8.2
Capacity × Readability (lb)	-	-	-	-	1.36690 x 0.00005 lb	2.64555 x 0.00005 lb	4.85020 x 0.00005 lb	-	1.3670 x 0.0005 lb	4.8500 x 0.0005 lb	13.6685 x 0.0005 lb	18 0.
Span Calibration Mass*	100 g	200 g	200 g	200 g	300 g	1 kg	2 kg	200 g	300 g	2 kg	5 kg	
Linearity Calibration Mass*	50, 100 g	100, 200 g	100, 200 g	200, 400 g	300, 600 g	500g, 1 kg	1 kg, 2 kg	200, 400 g	300, 600 g	1 kg, 2 kg	3 kg, 5 kg	4 k
Stabilization Time (s)	1.5	1.5	1	1	1	1.5	1.5	1	1	1	1	
Construction			ABS housing & stainless steel pan									
Draftshield	Yes		No									
Calibration			U	User-selectable external span or linearity calibration/Digital with external weight								
Tare Range	Full capacity by subtraction											
Weighing Units					g, kg,	ct, N, oz, ozt	, dwt, lb, lb:o	z, grn				
Application Modes	Weighing, Parts Counting, Percent Weighing, Check Weighing, Totalization, Display Hold											
Power Requirements			AC adapter (included) or 4 AA batteries (not included)									
Tuninal Dattamy Life	80				80			120				
Typical Battery Life (Hours)	8	80	120		3	30			120		80	
	8	30		lable as an a		80 8S232, USB 1	Host, USB De	evice, Etherr		oth®	80	
(Hours)	8	80		lable as an a	accessory:R					oth®	80	
(Hours) Communication	8	30		lable as an a	accessory:R	S232, USB I	(LCD) with b			oth®	80	
(Hours) Communication Display Type	8	30		lable as an a	accessory:R	RS232, USB I ystal display	(LCD) with b			oth®	80	
(Hours) Communication Display Type Display Size	8	30	Avai		accessory:R Liquid cr	RS232, USB F ystal display 0.78 in/20	(LCD) with b mm digits ed capacity	acklight	net or Bluetoo		80	
(Hours) Communication Display Type Display Size Overload Capacity Operating Temperature	8	30	Avai	0°F / 10°C to	accessory:F Liquid cr	RS232, USB I ystal display 0.78 in/20 10 times rat	(LCD) with b mm digits ed capacity 85% relative	acklight humidity, no	net or Bluetoo	9	80	
(Hours) Communication Display Type Display Size Overload Capacity Operating Temperature Range	3.7		Avai 5	0°F / 10°C to	accessory:R Liquid cr 0 104°F / 40° 0 55°C (131°	28232, USB I ystal display 0.78 in/20 10 times rat C at 10% to 6 F) at 10% to	(LCD) with book mm digits ed capacity 85% relative 90% relative	acklight humidity, no	net or Bluetoo	g 6.7 x		
(Hours) Communication Display Type Display Size Overload Capacity Operating Temperature Range Storage Conditions Pan Size	3.7 93 mm (8 × 8.7	7in	Avai 5	0°F / 10°C to 20°C (-4°F) to 4.7in	accessory:R Liquid cr 0 104°F / 40° 0 55°C (131°	28232, USB I ystal display 0.78 in/20 10 times rat C at 10% to 6 F) at 10% to	(LCD) with bomm digits ed capacity 85% relative 90% relative 5.5 in	humidity, no humidity, no 4.7in 120 mm diameter × 2.1 in	net or Bluetoo	g 6.7 x	5.5 in	
(Hours) Communication Display Type Display Size Overload Capacity Operating Temperature Range Storage Conditions Pan Size (W × D) Dimensions	3.7 93 mm (8 × 8.7 202 × 222 11.8 × 9.	7in diameter × 4.1 in	Avai 5	0°F / 10°C to 20°C (-4°F) to 4.7in	accessory:R Liquid cr 0 104°F / 40° 0 55°C (131°	28232, USB I ystal display 0.78 in/20 10 times rat C at 10% to 6 F) at 10% to	(LCD) with b mm digits ed capacity 85% relative 90% relative 5.5 in 140 mm 8 × 8.8	humidity, no humidity, no 4.7in 120 mm diameter × 2.1 in • × 54 mm 3 × 3.4 in	net or Bluetoo	g 6.7 x	5.5 in	

Other Standard Features and Equipment

Transportation lock, stainless steel pan, menu & calibration lockout switch, slip-resistant and adjustable feet, leveling bubble, mechanical and software overload/underload protection, stability indicator, auto tare, low battery indicator, auto shut-off, user selectable printing options, user selectable communication settings

1.5 kg

Shipping Weight

- Product Safety: IEC/EN 61010-1; CAN/CSA C22.2 No. 61010-1; UL Std. No. 61010-1
 Electromagnetic Compatibility: IEC/EN 61326-1 Class B; FCC Part 15 Class B; Industry Canada ICES-003 Class B

*Volume Discounts Available

We Accept Educational Institutes Purchase Orders Email Us or Call 800-832-0055 Accessories

- RS232 Interface Kit 30268982
 USB Host Interface Kit 30268983
- USB Device Interface Kit 30268984

- USB Device Interface Kit 30268984
 Bluetooth Interface Kit 30268985
 Ethernet Interface Kit 30268986
 Stacking & Storage Cover (6 pcs) 30268987
 Stacking & Storage Cover (1 pc) 30268988
 Printer, Impact, SF40A, AM. 30064203
 Auxiliary Display Kit 30269019
 Security Device 80850043
 Top Loading Kit for Density Determination 30269020
 Carrying Case 30269021
 In-use Cover 30269022

i81u812

718-336-5900 Contact US Returns Store Policies About Us

Phone: (800)832-0055 or (718)336-5900 Chat with us via WhatsApp Chat Address: 4802 Glenwood Rd. Brooklyn, NY 11234 © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.

^{*} Calibration weights are included with models up to 620g capacity.