



Ohaus Scout STX123 (30253005) Touch Screen Portable Balance 120 x 0.001 g

Ideal for laboratory & industrial applications, the OHAUS Scout features an easy to navigate color touchscreen display & a slim design which allows stackable storage. Geared for superior performance with fast stabilization time and high resolution weighing results, these portable balances set a new standard for a broad range of weighing applications. Features also include superior overload protection and expanded connectivity options.



Capacity x Readability

120 g x 1 mg

Pan Size

3.7 in (Diameter)

Manufacture: Ohaus

SKU: 30253005

UPC: B01AJ082EQ

Weight: 4.00 lb

Free Ground Shipping within the
48 continental US States

**Please Call
(800)832-0055**

Features

Setting New Standards in Laboratory & Industrial Weighing — The Next Generation of Scout Balances

Ideal for laboratory & industrial applications, the OHAUS Scout features an easy to navigate color touchscreen display & a slim design which allows stackable storage. Geared for superior performance with fast stabilization time and high resolution weighing results, these portable balances set a new standard for a broad range of weighing applications. Features also include superior overload protection and expanded connectivity options.

Standard Features Include:

- **Quick and Efficient Navigation with the Informative Color Touchscreen Display** - Large, resilient color touchscreen allows for effortless operation of the Scout through its informative icon driven menu structure, guiding the user through every step of the weighing application.
- **Fast Weighing Speed and High Resolution Deliver Repeatable and Reliable Results** - Stabilization time as fast as 1 sec means increased productivity in your facility. Equipped with advanced weighing technology, the Scout also ensures repeatable and reliable weighing results.
- **Superior Overload Protection & Stackable Storage Drive Overall Durability** - Integrated superior overload protection system rated at 10 times the capacity protects the balance in rugged and demanding environments. The space-saving, slim design allows for stackable storage.
- **Multiple Connectivity Options for Greater Flexibility in Communication** - With expanded connectivity options including RS232, USB Host, USB Device, Ethernet and Bluetooth®, the Scout provides added versatility to your data collection and transfer needs.

Navigate and Operate the Balance Easily with the Informative Touchscreen Display

Portable balance operation has never been easier, faster or as intuitive as the new OHAUS Scout with color touchscreen display. You'll navigate easily through the Scout's resistive touchscreen interface and icon-driven menu structure, maneuver efficiently in and out of application modes, change weighing units with a simple press of the screen and execute setup and calibration functions in no time. The OHAUS Scout with color touchscreen display creates a new level of unmatched efficiency and functionality in portable weighing.

A real-time clock function keeps accurate time even during power loss. Additionally, GLP/GMP tracking capabilities assist in the monitoring and reporting of data.

Increased Efficiency and Productivity in your Facility

It's all about accuracy and efficiency with the OHAUS Scout Touchscreen balance. Stabilization time as fast as 1 sec means increased productivity in the lab, or on the line. With improved resolution, you can count on extremely precise and repeatable weighing results time and time again.

Scout's Signature Durability Remains Unrivaled

You would expect nothing less from OHAUS than the most durable portable weighing product - that's why we've included our superior overload protection rated at 10 times the capacity of the balance, high strength stainless steel pan, impact-resistant pan support and integrated transportation/storage lock. We've even ensured that the high quality, resistive touchscreen is built to last. To complement our signature durability, the Scout Touchscreen is designed to be stackable when utilizing the included stacking and storage cover, which also protects the balance when not in use.

Versatile Data Collection and Transfer With expanded connectivity options now featuring Bluetooth®, the OHAUS Scout offers more versatility for convenient data logging, communication and remote functionality. Utilize the Bluetooth® accessory to remotely control the balance from your mobile device or tablet for Android™*. Perform functions such as Zero, Tare, Print, Power Off and more. Other accessories include RS232, USB Device, USB Host and Ethernet. With the USB Host option, you can simply save and transfer data from the balance to a USB drive.

Draftshield Model Available Scout's ingenious draftshield (1mg models only) was designed with an easy to remove top cover piece. This serves as a wind protection ring which keeps the weighing surface stable in rough environments, while maintaining weighing speed.

Built-in Application Modes

- **Weighing** — Determines the weight of items on the pan in the selected unit of measure.
- **Parts Counting** — Counts the number of pieces on the pan using a uniform weight.
- **Percent Weighing** — Measures the weight of a sample displayed as a percentage of a pre-established reference weight.
- **Check Weighing** — Compares the weight of a sample against target limits.
- **Totalization** — Measures cumulative weight of multiple items. Cumulative total may exceed balance capacity.
- **Dynamic Weighing** - Weighs an unstable sample load. The balance takes an average of weights over a period of time.
- **Density Determination** - Determines density of solids or liquid. With the integrated weigh below hook, it is possible to perform specific gravity tests for objects that cannot be easily placed on the weighing pan
- **Display Hold** — Manually holds the last stable weight or the first highest stable weighing value on the display.
- **Mole Weighing** — Measures the weight of a sample and calculates it into Moles automatically.

Specifications

Model	STX123	STX223	STX222	STX422	STX622	STX1202	STX2202	STX421	STX621	STX2201	STX6201	STX1201
Capacity X Readability (g)	120 x 0.001	220 x 0.001	220 x 0.01	420 x 0.01	620 x 0.01	1200 x 0.01	2200 x 0.01	420 x 0.1	620 x 0.1	2200 x 0.1	6200 x 0.1	8200 x 0.1
Repeatability (Std. Dev.) (g)	0.002			0.01		0.02			0.1			
Linearity (g)	+/-0.003			±0.01	±0.02	±0.03			±0.1		±0.2	
Capacity X Readability (kg)	-	-	-	-	-	1.2 x 0.00001 kg	2.2 x 0.00001 kg	-	-	2.2 x 0.0001 kg	6.2 x 0.0001 kg	8.2 x 0.0001 kg
Capacity x Readability (lb)	-	-	-	-	1.36690 x 0.00005 lb	2.64555 x 0.00005 lb	4.85020 x 0.00005 lb	-	1.3670 x 0.0005 lb	4.8500 x 0.0005 lb	13.6685 x 0.0005 lb	18.6685 x 0.0005 lb
Span Calibration Mass*	100 g	200 g	200 g	200 g	300 g	1 kg	2 kg	200 g	300 g	2 kg	5 kg	10 kg
Linearity Calibration Mass*	50, 100 g	100, 200 g	100, 200 g	200, 400 g	300, 600 g	500g, 1 kg	1 kg, 2 kg	200, 400 g	300, 600 g	1 kg, 2 kg	3 kg, 5 kg	4 kg, 10 kg
Stabilization Time (s)	1.5	1.5	1	1	1	1.5	1.5	1	1	1	1	1
Construction	ABS housing & stainless steel pan											
Draftshield	Yes											
Calibration	No											
Tare Range	User-selectable external span or linearity calibration/Digital with external weight											
Weighing Units	Full capacity by subtraction											
Application Modes	mg, g, kg, ct, N, oz, ozt, dwt, lb, lb:oz, grn, hkt, sgt, twt, tical, tola, customer unit 1											
Power Requirements	Weighing, Parts Counting, Percent Weighing, Check Weighing, Animal/Dynamic Weighing, Totalization, Density Determination, Display Hold											
Typical Battery Life (Hours)	AC adapter (included) or 4 AA batteries (not included)											
Communication	7 hours											
Display Type	Available as an accessory: RS232, USB Host, USB Device, Ethernet or Bluetooth®											
Display Size	4.3" (109 mm) full-color VGA graphic touchscreen display with user-controlled brightness											
Overload Capacity	4.3 in/109 mm (diagonal)											
Operating Temperature Range	10 times the rated capacity											
Storage Conditions	50°F / 10°C to 104°F / 40°C at 10% to 85% relative humidity, non-condensing											
Pan Size (W x D)	-20°C (-4°F) to 55°C (131°F) at 10% to 90% relative humidity, non-condensing											
Dimensions W x H x D	3.7in 93 mm diameter			4.7in 120 mm diameter			6.7 x 5.5 in 170 x 140 mm			4.7in 120 mm diameter		
Dimensions W x H x D	8 x 8.7 x 4.1 in 202 x 222 x 103 mm						8 x 8.8 x 2.1 in 202 x 224 x 54 mm					
Net Weight							11.8 x 9.8 x 5.1 in 300 x 250 x 129 mm					
Shipping Weight							1 kg					
							1.6 kg					

* Calibration weights are included with models up to 620g capacity.

Other Standard Features and Equipment

Transportation lock, stainless steel pan, menu & calibration lockout switch, slip-resistant and adjustable feet, leveling bubble, mechanical and software overload/underload protection, stability indicator, auto tare, low battery indicator, auto shut-off, user selectable printing options, user selectable communication settings

- **Compliance**
- Product Safety: IEC/EN 61010-1; CAN/CSA C22.2 No. 61010-1; UL Std. No. 61010-1
- Electromagnetic Compatibility: IEC/EN 61326-1 Class B; FCC Part 15 Class B; Industry Canada ICES-003 Class B

***Volume Discounts Available**
We Accept Educational Institutes Purchase Orders
[Email Us](#) or Call 800-832-0055 Accessories

- RS232 Interface Kit - 30268982
- USB Host Interface Kit - 30268983
- USB Device Interface Kit - 30268984
- Bluetooth Interface Kit - 30268985
- Ethernet Interface Kit - 30268986
- Stacking & Storage Cover (6 pcs) - 30268987
- Stacking & Storage Cover (1 pc) - 30268988
- Printer, Impact, SF40A, AM. 30064203

- Auxiliary Display Kit - 30269019
- Security Device - 80850043
- Top Loading Kit for Density Determination - 30269020
- Carrying Case - 30269021
- In-use Cover - 30269022

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)

- Chat with us via [WhatsApp Chat](#)

- Address: 4802 Glenwood Rd. Brooklyn, NY 11234

- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.