



Rice Lake 106915 Summit 4 x 4 LCD Floor Scale Legal for Trade 230 Volt 5000 x 1 lb

The Rice Lake Summit 3000 floor scale and indicator package is an economical choice for many industrial weighing tasks, with a durable low-profile deck that fits well into many material handling environments. This Legal for Trade scale comes with our easy-to-use and straightforward model 120 digital weight display or optional 120 PLUS digital weight display and 20 feet of load cell cable.



Capacity x Readability

Non Legal Mode: 5000 lb
x 1 lb

Legal For Trade: 5000 lb
x 1 lb

Pan Size

4 x 4 ft

Manufacture: Rice Lake

SKU: 106915



Legal for Trade

Please Call
(800)832-0055

Features

The Rice Lake Summit 3000 floor scale and indicator package is an economical choice for many industrial weighing tasks, with a durable low-profile deck that fits well into many material handling environments. This Legal for Trade scale comes with our easy-to-use and straightforward model 120 digital weight display or optional 120 PLUS digital weight display and 20 feet of load cell cable. Standard Features

- Summit® 3000 Floor Scale
- 4 NTEP Certified alloy steel-shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- 4 adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–20NF) located in the center of the deck for easy lifting
- 20 ft of EL147 load cell cable with quick disconnect
- Package configured and calibrated for 5,000 divisions 120 Digital Weight Indicator
- 120 Digital Weight Indicator: Large 0.8 in (20.3 mm) light emitting diode (LED) display
- 120 Digital Weight Indicator: 5-button operation
- 120 Digital Weight Indicator: Full front panel digital calibration and configuration 120 PLUS Digital Weight Indicator
- 120 PLUS Digital Weight Indicator: Large 0.8 in backlit liquid crystal display (LCD)
- 120 PLUS Digital Weight Indicator: 115 or 230 VAC wall adapter with rechargeable battery

Specifications

MODEL	78772	78773	106913	106914	78780	78781	106915	106916	78776	78777	106917	106918
Capacity x Readabilit	5000 lb x 1 lb	10000 lb x 2 lb	5000 lb x 1 lb	10000 lb x 2 lb	5000 lb x 1 lb	10000 lb x 2 lb	5000 lb x 1 lb	10000 lb x 2 lb	2,500 kg x 0.5 kg	5000 kg x 1 kg	2,500 kg x 0.5 kg	5000 kg x 1 kg
Legal for Trade	Base: NTEP CC 92-001A9, Class III 5,000 d Indicator: NTEP CC 03-059, Class III/IIIL 6,000 d								Base: Measurement Canada AM-5530, Class III 5,000 d Indicator: Measurement Canada AM 5517			
Platform dimensions	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft	4 x 4 ft
Indicator	120		120 Plus		120		120 Plus		120		120 Plus	
Power (Indicator)	115 VAC (120)		115 VAC (120 PLUS)		230 VAC (120)		230 VAC (120 PLUS)		115 VAC Canadian Weights and Measures (120)		115 VAC Canadian Weights and Measures (120 PLUS)	
Display	LED - display 0.8in (20.3mm)6-digit, 7-segment		LCD - display Large 0.8 in backlit		LED - display 0.8in (20.3mm)6-digit, 7-segment		LCD - display Large 0.8 in backlit		LED - display 0.8in (20.3mm)6-digit, 7-segment		LCD - display Large 0.8 in backlit	
Cable Length	20 ft (6.1 m) (for connecting junction box to indicator)											
Warranty	Summit 3000 weldment and load cells two years, all other components one year											
Approvals	NTEP CC 92-001A9, Class III 5,000 d Measurement Canada AM-5530, Class III 5,000 d											
Serial Output	7 or 8 data bits; even, odd or no parity											
Printer Port	Output-only RS-232 or active 20 mA current loop											
EDP Ports	Full duplex RS-232 (1200-38400 bps)											

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
 - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.